

HITACHI

Inspire the Next

CP-X275WT



- 1,200 ANSI lumens
- HDTV theater ready
- 5 lbs.
- RGB/component/composite/S-video inputs
- Short throw lens
- Kensington security slot
- Native XGA resolution (1,024 x 1,280 compressed)
- Manual zoom & manual focus
- Color temperature and gamma correction
- Reverse image function for ceiling mount
- Vertical keystone correction
- Whisper mode 34dB
- Slide lens cover
- Digital zoom & freeze function
- Comes with carry case
- 16:9 mode

SPECIFICATIONS

Model name	CP-X275WT		
Liquid crystal panel structure	0.7" polysilicon active-matrix TFT x 3		
Number of pixels	786, 432 pixels (H1,024 x V768)		
Resolution	1,024 x 768 color pixels		
Colors	16.7 million colors		
Aspect ratio	Native 4:3/16:9 compatible		
Lens	Manual zoom 1:1.2 (F2.0 - 2.3)		
Throw ratio (distance:width)	1.16 ~ 1.46 : 1		
Lamp	150W UHB (130W in whisper mode)		
Brightness	1,200 ANSI lumens (960 ANSI lumens in whisper mode)		
Expected lamp life	2,000 hours		
Contrast ratio	300 : 1		
Speakers	1W x 1		
Power supply	AC90-132V/AC220-240V 50/60Hz		
Power consumption	240W		
Operating temperature	0 ~ 35°C (32° ~ 95°F)		
Input signals	RGB	VGA, SVGA, XGA, SXGA/UXGA (COMPRESSED), MAC13", MAC16"	
	Composite video	NTSC, NTSC4.43, PAL, PAL-M, PAL-N, SECAM, PAL60, S-video	
	Component video	480i, 625i, 480p, 1,080i, 720p	
Acoustic noise level	39dB (34dB in whisper mode)		
H sync	15kHz ~ 78kHz		
V sync	50Hz ~ 120Hz		
Vertical keystone correction	Digital keystone +/- 10°		
Horizontal keystone correction	-		
Approvals	UL, C-UL, FCC Class B, CE, TUV		
Input/Output terminals	RGB input	Analog RGB	15-pin D-sub connector x 1
		Audio	Stereo mini jack x 1
	Video input	S-video	Mini DIN 4-pin input connector x 1
		Composite video	RCA jack x 1
	Component video	RCA jack x 3	
	Audio	RCA jack x 2 (L/R)	
	Control terminals		15-pin D-sub connector x 1
	Compatible controls		RS-232C (Serial)
			-
Chassis	Dimensions	10.9" x 2.4" x 8.3" (W x H x D)	
	Weight	5 lbs.	
	Supplied accessories	Card type remote control, batteries (AA), power cord (U.S., UK, Euro), RGB cable, RCA component cable, multiple language operator/safety manual, handle strip and carrying case.	
Replacement parts	Lamp	CPX275 LAMP (Part #: DT00461)	
	Remote control	Card type remote (Part #: HL01444) Mouse kit (Part #: RMU101) Optional	



Screen Size 4.3		Throw distance	
Diagonal*	Width*	Min*	Max*
40	32	37	46
60	48	57	69
80	64	77	93
100	80	98	116
120	96	116	139
150	120	145	174
200	160	194	233

Throw ratio: 1.16 ~ 1.46:1 (distance:width)

*: Measured in inches

CP-S225/CP-X275 Dimensions (incl.protruding part)

