

**ANSI Luminance and Resolution**

2500 ANSI Lumens*, XGA Resolution (1024 x 768)

Auto Setup

One Button Auto Set Up

Side Shot

Horizontal Keystone Correction

Power Zoom

Powered Zoom/Focus Lens and Short Focal Lens

Air Shot

A Sony original wireless transmission capability

The Sony VPL-CX75 wireless mobile projector combines a portable, stylish design with high brightness picture and easy to use Auto set-up features. Compact design, simple controls, and quick startup will help you present like a pro ? and bright, crisp images will make your content come alive. Designed to help the mobile professional deliver brilliant presentations at sales meetings, training seminars, even executive boardrooms.

VPL-CX75

Display



SuperLife

Model

VPL-CX75

Projection System

3 LCD panels, 1 lens projection system

Panel

0.79-inch XGA LCD panel with Micro Lens Array 2,359,296 pixels (786,432 pixels x 3)

Projection Lens

1.2 times F1.6 to 1.78, f23.5 to 28.2 mm

Lamp

165W UHP

Screen Coverage

40 to 300 inches (measured diagonally)

Keystone Correction Range

Max. +/-30 degrees horizontally, +/-20 degrees vertically*

Light Output

2500 ANSI lm (lamp mode high)
(standard: approx. 2000 ANSI lm)

Color System

NTSC3.58, PAL, SECAM, NTSC4.43,
PAL-M, PAL-N, PAL60

Resolution

Video: 750 TV lines; RGB: 1024 x 768
pixels

Acceptable Signals

Computer: fH 19-92 kHz, fV 48-92 Hz (up
to SXGA+ (fV: 60 Hz))
Video: 15 kHz RGB/Component 50/60 Hz,
Progressive Component 50/60 Hz,
DTV (480/60i, 575/50i, 480/60p, 540/60p,
575/50p, 720/60p, 720/50p, 1080/60i,
1080/50i), Composite video, Y/C video

Speaker

Mono 1 W (max.) x 1

Power Requirements

AC 100 to 240 V, 50/60 Hz

Power Consumption

Max: 240 W; Standby: 9 W (standard)

Dimensions (W/H/D)

298x69x243.5 mm / 11 3/4 x 2 3/4 x 9 5/8
inches

Mass

kg: Approx. 2.9 kg
lb: Approx. 6 lb 8 oz

Noise Level

<30db

Video Inputs

Composite Video : Pin Jack, S-Video : mini
DIN 4 pin. Audio : Stereo mini Jack

Input A

Analog RGB/Component : HD 15 pin
Audio : Stereo mini Jack (shared by A/B)

Output

Analog RGB/Component : HD 15 pin
Audio : Stereo mini Jack (variable out),
USB for mouse (Up, B type)

USB

Upstream (B type, female x 1)

Remote

RS-232C: D-sub 9-pin female x 1

Regulations

UL1950, cUL (CSA 60950), DHHS, DNHW,
FCC Class B, IC Class B, DEMKO
(EN60950), CE (LVD, EMC), C-Tick,
Dentori, VCCI Class B

Wireless LAN

80211b wireless card included

Supplied Accessories

Remote Commander Unit (RM-PJM17)
Presentation Tool (RM-PJP1)
(2) AA Size Batteries, Soft Carrying Case,

USB Storage Media, USB cable A type-B
type

HD D-sub 15 pin cable, USB Cable,
Wireless Lan Card (IFU-WLC1) and
Wireless LAN Module (IFU-WLM1)

Optional Accessories

Projector Lamp: LMP-C161

Ceiling Mount: PAM-100

Extended Warranty: 3rd and 4th year

©2004 Sony Electronics Inc. All rights reserved.
Features and specifications are subject to change
without notice. All trademarks referenced herein are
trademarks of Sony or their respective owners.

SONY

Sony Electronics Inc.
16765 West Bernardo Drive
San Diego, CA 92127

LIKE NO OTHER