

CP718e

Head of the Class

For affordable and reliable BOXLIGHT quality, the CP718e is the obvious choice. An ideal fit for school use, it offers full XGA resolution for clarity and brightness and is HDTV compatible.



CP718e

Specifications



BRIGHTNESS

2200 lumens

RESOLUTION

1024 x 768 XGA (Native)

1280 x 1024 SXGA (Supported)

DISPLAY TYPE

0.63" HTPS TFT LCD x3

CONTRAST RATIO

500:1

ASPECT RATIO

4:3 Native

16:9 Compatible

THROW RATIO

1.45 ~ 1.74 (x screen width)

PROJECTION LENS

Manual Zoom & Focus

ZOOM RATIO

1:1.2

DIAGONAL IMAGE SIZE

40" - 300"

THROW DISTANCE

4' - 30'

KEystone

+/- 30° Vertical

LAMP

205 watt NSH

LAMP LIFE

3000 Hours

INPUTS

VGA (Computer 2/YPbPr)

VGA Computer 1

S-Video

Composite Video

Audio (3.5 mm)

OUTPUTS

Audio (3.5 mm)

VGA

PROJECTOR CONTROLS

USB

RS232 (DIN)

COMPATIBILITY

VGA, SVGA, XGA, SXGA, MAC

EDTV / SDTV / HDTV

480i/p, 576i/p, 720p, 1080i

FCC CERTIFICATION

FCC-B, UL, TUV-CB, c-UL, CB, CE, CCC

VIDEO COMPATIBILITY

NTSC, NTSC 4.43, PAL B/G/H/I/M/N 60, SECAM

AUDIO

1 x 2w Mono Speaker

DECIBEL RATING

33 dB

H-REFRESH RATE

15 - 69 kHz

V-REFRESH RATE

43 - 85 kHz

POWER SUPPLY

AC 100 - 240 Volts (50/60 Hz)

POWER CONSUMPTION

250 Watts

DIMENSIONS (WxDxH)

12.2" x 10.6" x 3.8"

WEIGHT

6.8 lbs

WARRANTY

3 Year Parts & Labor / 90 Day Lamp

Special features of the CP718e include:

3-D Comb Filtering-

Eliminates artifacts resulting in better video quality.

Anti-Theft-

Secure and protect your projector with a Kensington lock.

Auto Ceiling Mount-

Automatically adjusts the picture to the orientation of the projector.

Auto Keystone Correction-

Projector will automatically correct a trapezoidal image!

