

Combining form and function, the powerhouse Runco LS-3 offers Runco performance in a stylish package. Incredible value for the video perfectionist who demands as much of an impression from a projector when its turned off as when its turned on. 1080p resolution, advanced connectivity and legendary video performance will create an unmatched theater experience in any environment.

*Light*  
**STYLE**



### LightStyle LS-3 Specifications

<b>Projector Type:</b>	Digital Light Processing™ (DLP™), Single-Chip, 16:9 SuperOnyx™ DMD™
<b>Native Resolution:</b>	Full HD, 1920 x 1080
<b>Aspect Ratios:</b>	Native (Pixel-to-Pixel), 16:9, Letterbox, 4:3, 4:3 narrow, Letterbox
<b>Video Standards:</b>	HDMI and DVI with HDCP for digital video, Component and RGB HDTV (1080p, 1080i, 720p), Component and RGB EDTV (576p, 480p), Component, Composite and S-Video SDTV (576i, 480i), RGB SCART with adapter, NTSC (M,4.43), PAL (B,G,H,I,N,M), SECAM (M)
<b>DTV Compatibility:</b>	480i, 480p, 576i, 576p, 720p, 1080i 50/60, 1080p 24/50/60
<b>Picture Size (16:9 screens):</b>	Recommended Width: 72 – 92 in. Maximum Width: 120 in.
<b>Throw Distance Factor x Screen Width:</b>	1.85 – 2.40 (distance/width) – Standard lens, 1.56 - 1.86 (distance/width) - Optional short-throw lens
<b>Horizontal and Vertical Offset</b>	Vertical: Up to 60% of screen height down, 25% up from center of screen – ceiling mounted
<b>Light Output:</b>	CSMS** Specifications: Home Theater Calibration: 691 ANSI Lumens; 44 Foot-Lamberts (fL); 1000 ANSI Lumens*
<b>Contrast Ratio:</b>	CSMS** Contrast Ratio: 385:1; 10,000:1 typical (sequential)*
<b>Lamp:</b>	230W
<b>Lamp Life:</b>	4000 hours (typical)
<b>Inputs:</b>	(2) HDMI; (1) Component; (1) RGB (HD15); (1) S-video; (1) Composite; (1) RS-232
<b>12V Output:</b>	1 programmable
<b>Power Requirements:</b>	100V – 240V AC, 50-60Hz, 350W
<b>Operating Environments:</b>	50° - 104° F (10° - 40° C), 0% - 85% relative humidity (non-condensing)
<b>Dimensions:</b>	20.6" (523mm) L x 17.7" (450mm) W x 7.6" (194mm) H
<b>Regulatory Approvals:</b>	FCC Part 15 Class B, CE Class B, UL, cUL, CB, RoHS, WEEE, local conformances as required