



*Cine*VERSUM

photo by courtesy of Frankston HiFi - Australia



# **BLACKWING mk2011 SERIES**

**HD VIDEO-PROJECTORS FOR 2D AND 3D HOME-CINEMA**



# BLACKWING mk2011 SERIES

## HD VIDEO-PROJECTORS FOR 2D AND 3D HOME-CINEMA



Stylishly designed in Paris, France, the Cineversum Blackwing projectors combine a first-class optical engine with luxurious materials



Enter a new world with Blackwing 3D Series

Watching 3D content on a flat-panel TV is like looking into a doll-house. Only the Blackwing Series can reproduce the immersive experience of 3D commercial theatres in the comfort of your home.



**2D and 3D, sacrifice nothing !**

If you expect the best 2D projection system and want 3D done right, there is only one solution: contact the local Cineversum authorized dealer or installer.

Contact: [info@cineversum.com](mailto:info@cineversum.com)

Model Version	BlackWing High Brightness	BlackWing One	BlackWing Two	BlackWing Three
Model Part Number	R9201104	R9201101	R9201102	R9201103
Panel Technology	3-chip LCOS 0.7 inch panel - Full-HD 1920x1080 Resolution			
Screen Size (16:9)	60" - 240" diagonal			
Lamp Consumption	220 W Bulb - up to 3000 hours (with lamp used in standard mode)			
Brightness	1700 ansi lumens	1300 ansi lumens		
Contrast Ratio	30 000:1	50 000:1	70 000:1	100 000:1
Noise Level	Less than 19 dB			
Inputs	2x HDMI rev 1.4a 1x Component (3 RCA) 1x Analogue PC (Dsub15)	2x HDMI rev 1.4a 1x Component (3 RCA)	2x HDMI rev 1.4a 1x Component (3 RCA) 1x Analogue PC (Dsub15)	
Adjustable Lens Aperture	16 steps			
SLM™, Smart Lamplife Management	NO		Automatic (Configurable)	
Expert Calibration Menu	NO		YES (for calibration expert only)	
Picture Mode Presets	3	6	7 + 4 for calibration expert	
Home-cinema Video Processing	Crystal Motion®		Crystal Motion® True Cinema Black®	
Film Tone	NO		YES	
Screen Adjustment	3 Modes		99 Modes	
3D Compatibility	Frame Sequential with Active Shutter Glasses. Frame Packing, Side-by-Side and Above-Below			
CMS Functions	YES (7-Axis)	NO	YES (7-Axis)	
Optic	Full-glass Motorized (zoom & focus)			
Throw Ratio	1.4 - 2.8:1 (2x zoom)			
Screen Offset	Motorized Optical Shift +/- 80% vertically +/- 34% horizontally			
Weight	15.0 kg (33.7 lbs)			
Dimensions (LxWxH)	550 x 530 x 200 mm (21.7 x 20.9 x 7.9 inches)			
Home Automation	RS-232 (Dsub 9) / LAN P.J45	RS-232 (Dsub 9)	RS-232 (Dsub 9) / LAN P.J45	
12V Trigger	1			
Digital Keystone	YES (not compatible with 3D Mode)			
Box dimensions	610x580x410 mm 21 kg			
3D Glasses	Active Shutter Glasses (P/N R1048205)			
Ceiling Mount Kit	Optional (P/N R9852067)			
Cinemascope Kit	Cine-Twist Kit (P/N T9006000)			

