



Versatile Projector with Embedded Media Player

The Vivitek D863 is a high-performance digital projector that offers exceptional digital images with full color saturation. This projector features native XGA resolution, multiple connectivity options and 3000 ANSI Lumen of brightness. Add 3D-ready capabilities, and the D863 is the ideal projector for just about any multimedia/video applications. Great functionality, high performance and excellent value for money, all found in the Vivitek D863.

Features

- 3,000 ANSI lumens of brightness with a 15,000:1 contrast
- DLP® and BrilliantColor™ technologies from Texas Instruments
- XGA (1024 x 768) resolution with a maximum resolution up to UXGA (1600 x 1200)
- Powerful and easy to use multimedia utility (application) allows the projector to be controlled and monitored through a PC with a USB or network connection (RJ-45)
- Integrated media and document viewer conveniently plays documents, photos, videos and audio files without the need to connect a PC
- Assortment of connectivity options for easy connection to a variety of multimedia devices (HDMI, VGA, USB)
- 3D Ready through DLP-Link
- Top-loading, sliding cover for quick and easy lamp replacement
- Built-in 10W audio speaker
- Sealed optical engine, minimizing the impact of dust and smoke
- Security solutions include: Kensington® security slot, security bar, keypad lock

Specifications	
Brightness	3000 ANSI Lumen
Native Resolution	XGA (1024 x 768)
Max. Resolution	Up to UXGA (1600 x 1200) @60Hz
Contrast Ratio	15,000:1 (Full On/Off)
Lamp Life and Type	≈6000/4500 Hours (Eco/ Normal Mode), 190W
Lamp Part #	5811117175-SU
Display Type	Single 0.55" DLP® Technology by Texas Instruments
Throw Ratio	1.6 to 1.92:1 (Distance/Width)
Image Size (Diagonal)	25.6" to 308"
Projection Distance	1.0 to 10.0 m
Projection Lens	F=2.50-2.72, f=17.81-21.35mm
Zoom Ratio	1.2x
Aspect Ratio	4:3 Native, 16:10 & 16:9 Compatible
Offset	128% ±10%
Keystone Correction	±40° Vertical
Color Spectrum	1.07 Billion
Horizontal Scan Rate	15, 30 to 90 KHz
Vertical Scan Rate	43 to 120 Hz
Speaker	10 Watt
Projection Method	Table Top or Ceiling Mount (Front or Rear)
Computer Compatibility	UXGA, SXGA+, SXGA, WXGA, XGA, SVGA, VGA Resized; VESA Standards; PC and Macintosh Compatible
Video Compatibility	SDTV (480i, 576i), EDTV (480p, 576p), HDTV (720p, 1080i/p), NTSC (M, 3.58/4.43 MHz), PAL (B, D, G, H, I, M, N), SECAM (B, D, G, K, K1, L)
I/O Connection Ports	RCA(L/R), Audio-In (Mini-Jack), VGA-Out, USB (Type A)(x2), Audio-Out (Mini-Jack), RJ45, RS-232C, Mini-USB (Service)
Security	Kensington® Lock Port
Weight	2.7 kg
Dimensions (W x H x D)	285 x 122 x 261 mm
Noise Level	32dB/34dB (Std./Boost Mode)
Power	Supply: AC 100-240V, 50/60Hz Consumption: 230W (Standard Mode), 260W (Boost Mode), < 0.5W (Standby Mode)
Warranty	3 Years, 1 Year (or 1,000h) on the Lamp
Standard Accessories	AC Power Cord, VGA Cable, Carrying Case, Remote Control, Lens Cap, Documentation Kit
Optional Accessories	Replacement Lamp, Remote and Carrying Case
UPC	814964335425

