

Christie Mirage WQ-L

Christie Mirage WQ-L – (2560 x 1600) WQXGA,
solid state illumination, dual input, part number: 130-001102-01

Image	brightness	• 800 ANSI lumens
	contrast	• 10,000:1 dynamic contrast (under LED control) • No mechanical iris required
	uniformity	• 95% brightness and color uniformity after electronic adjustment
Display technology	type	• Revolutionary solid state projector using a single TI Darkchip 3™ DMD with a solid state illumination engine (no color wheel) and sealed optics
	native resolution	• 2560 x 1600 WQXGA
	output frame rate	• True 120Hz 3D (60Hz per eye content) or 120Hz via frame doubled content (30Hz per eye)
Input	signal format	• 2560 x 1600 WQXGA ¹
	input frame rate	• 2560 x 1600 @ 60Hz x 2 frame-locked with Dual input 3D for true 120Hz (60Hz per eye 3D) or 2560 x 1600 @ 60Hz x 1 for frame doubled output to 120Hz ²
Inputs/ outputs, control and networking	inputs	• External PC is required for projector operations via Ethernet • Additional Ethernet connections for Christie ArrayLOC™ network • 2 x RS-232 ports and 1 x RS-422 port • 2 x Dual-link DVI-D
Optical system	lens mount	• Mechanical, horizontal and vertical lens shift • No shutter required • No iris required – user programmable illumination parameters (eliminates the need for a mechanical shutter)
	illumination	• Solid state illumination • Illumination lifetime greater than 50,000 hrs (to 50% output)
	ArrayLOC™	• Manages the brightness and color levels of all projectors within an array to a common level, in real-time with no additional latency
Lenses	fixed	• 0.68:1 fixed • 0.80:1 fixed
	zoom	• 1.28-1.71:1 zoom
	offsets	• 0.68:1 lens features ±5% (horizontal) and ±5% (vertical) offset when mounted in landscape orientation ³ • 0.80:1 lens features ±75% (horizontal) and ±100% (vertical) offset when mounted in landscape orientation ³ • 1.28-1.71:1 lens features ±75% (horizontal) and ±100% (vertical) offset when mounted in landscape orientation ³
Accessories	standard	• Line cord • Christie Twist
	optional	• User kit (includes manual, IR remote) • Christie AutoCal™ • Christie Twist Pro™ • Rugged Motion Platform kit ⁴ to withstand 5g shock load (purpose-built) • Ruggedized transit case • Remote IR sensor • Christie MotoBlend™ optical blending ⁵
Enhanced feature sets	• Minimum Processing Latency (MPL™) • Auto power up • Menus in 5 languages • Christie ArrayLOC – automatic, continuous management of brightness and color space levels of all projectors in the array to a common level, in real-time	
Power requirements	operating voltage	• 100-240 VAC 50/60Hz
	operating current	• 12A max 100-120 VAC, 6A 200-240 VAC (lower in normal operational modes)
	dissipation	• 2316 BTU/hr max (lower in normal operational modes)
Dimensions	size	• 400 x 400 x 406mm (without lens)
	weight	• 40kg (without lens)
	shipping weight	• 80kg (without lens)
Operating environment	• Temperature: 40-95°F (5-40°C) • Humidity: 20-80% non condensing	
Operating orientation	• Portrait and landscape	
Regulatory approvals	• Directives (EC) 2011/65/EU (RoHS) • 2012/19/EU (WEEE) • Regulation (EC) No. 1907/2006 (REACH) • CAN/CSA C22.2 No. 60950-1 • UL 60950-1 • IEC 60950-1 • FCC, Part 15, Subpart B, Class A • EN55022/CISPR22 Class A • EN55024 / CISPR24 ; ICEES003 / NMB003 (A) • The product is designed to comply with the rules and regulations required for the product to be sold in various regional markets, including: USA/Canada, EU, Argentina, Brazil, Australia/New Zealand, Kuwait, China, Korea, Japan, Hong Kong, Mexico, Ukraine, Russia, India, South Africa, Singapore, UAE, and Saudi Arabia	
Limited warranty	• Standard warranty: Two years parts and labor • Extended warranty options available • Contact an authorized Christie representative for full details of our limited warranty	

¹ Standard VESA timing of 2560 x 1600 with reduced blanking.

² Frame doubling functionality is included in hardware, but not available until new firmware is released in Q1-2014.

³ Each offset is specified with the other at zero. Simultaneous horizontal and vertical offsets may limit the adjustment range of each.

⁴ Mirage WQ-L is available with a Ruggedized Motion Platform kit. These are purpose built to interface with customers' motion platform structures and available on a build-to-order basis. For details, please contact your Christie sales representative.

⁵ For details, please contact your Christie sales representative.

Corporate offices

Christie Digital Systems USA, Inc.
USA – Cypress
ph: 714 236 8610

Christie Digital Systems Canada Inc.
Canada – Kitchener
ph: 519 744 8005

Worldwide offices

Australia
ph: +61 (0) 7 3624 4888

Brazil
ph: +55 (11) 2548 4753

China (Beijing)
ph: +86 10 6561 0240

China (Shanghai)
ph: +86 21 6278 7708

Eastern Europe and
Russian Federation
ph: +36 (0) 1 47 48 100

France
ph: +33 (0) 1 41 21 44 04

Germany
ph: +49 2161 664540

India
ph: +91 (080) 6708 9999

Japan (Tokyo)
ph: 81 3 3599 7481

Korea (Seoul)
ph: +82 2 702 1601

Republic of South Africa
ph: +27 (0)11 510 0094

Singapore
ph: +65 6877 8737

Spain
ph: +34 91 633 9990

United Arab Emirates
ph: +971 4 3206688

United Kingdom
ph: +44 (0) 118 977 8000

Independent sales
consultant offices

Italy
ph: +39 (0) 2 9902 1161



For the most current specification information, please visit www.christiedigital.com

Copyright 2013 Christie Digital Systems USA, Inc. All rights reserved. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. Christie Digital Systems Canada Inc.'s management system is registered to ISO 9001 and ISO 14001. Performance specifications are based on current research, specifications are subject to change without notice. Printed in Canada on recycled paper. 3688 Oct 13

CHRISTIE®