

LH710 DLP® Laser Projector

LH710 Features

- IP5X certified dustproof laser engine
- 4000 ANSI Lumens High Brightness
- 360° projection and 24/7 operation
- Digital shrink and shift
- Filter free



Connectivity

- HDMI (1.4a)
- PC (D-sub 15pin)
- Monitor out (D-sub 15pin, Female)
- Audio in (mini jack)
- Audio out (mini jack)
- RS232 In (D-sub 9pin, male)
- LAN Port (RJ45 for Network)
- USB Type A-2 (5V, 1.5A, Service)
- Component Video in
- Composite Video in (RCA)
- RCA Audio in-L/R
- IR Receiver (Front + Top)
- 12V Trigger
- Kensington anti-theft lock slot

SPECIFICATIONS		LH710
DISPLAY	Projection System	DLP® Single 0.48" WUXGA
	DMD type	DC3 DMD chip
	Native Resolution	1920 x 1080 pixels, 16:9
	Brightness	4,000 Lumens
	Contrast Ratio*	3,000,000:1
	Display Color	1.07 Billion Colors
	Aspect Ratio	Native 16:9 (5 aspect ratio selectable)
	Light Source	Laser
	Light Source life*	20,000 hrs
OPTICAL	Throw Ratio	1.13 ~ 1.46
	Zoom Ratio	1.3x
	Lens Control	Manual Focus
	Lens shift	NA
	Keystone Correction	2D keystone, V: ±30 degree; H: ±30 degree
	Projection Offset	105%
	Projection Size	30" ~ 300"
AUDIO	Built-in Speaker	10W x2
SPECIAL FEATURE	Security (anti-theft)	Security Bar, Kensington anti-theft lock slot
	Feature	Digital Shrink and Shift, 360° Projection, LumiExpert, LAN Control (AMX/ PJ Link/Crestron), MDA, DMS Local Compatibility, FW upgrade via LAN
COMPATIBILITY	Resolution Support	VGA (640 x 480) to WUXGA_RB (1920 x 1200)
	Horizontal Frequency	15 ~ 102KHz
	Vertical Scan Rate	23 ~ 120 Hz
	HDTV Compatibility	480i, 480p, 576i, 567p, 720p, 1080i, 1080p
	Video Compatibility	NTSC, PAL, SECAM
POWER	Power Consumptions (Max/Normal/Eco)	Max 392W / Normal 392W / Eco 320W
	Standby Power consumption	Normal < 0.5W, Network < 2W.
	Power Supply	100 ~ 240V AC
DIMENSION AND WEIGHT	Product Dimensions (WxHxD)	416 x 166 x 312 mm
	Product Weight	6.3 Kg (13.0 lbs)
OPERATION CONDITION	Noise Level (Normal/Eco)	34/29 dB
	Operating Temperature*	0 ~ 40°C
OSD	On-Screen Display Languages	Arabic/ Bulgarian/ Croatian/ Czech/ Danish/ Dutch/ English/ Finnish/ French/ German/ Greek/ Hindi/ Hungarian/ Italian/ Indonesian/ Japanese/ Korean/ Norwegian/ Polish/ Portuguese/ Romanian/ Russian/ Simplified Chinese/ Spanish/ Swedish/ Turkish/ Thai/ Traditional Chinese/ Vietnamese / Farsi (30 Languages)
ACCESSORIES	STANDARD	OPTIONAL
	Power Cord (by region) Remote Control w/ Battery (RCE016) HDMI cable Warranty Card (by region) QSG	3D Glasses (5J.J9H25.002) Ceiling mount (CMG3) WDC10/WDC10C WDC20 Qcast Mirror

ENVIRONMENT NOTICE

* The Contrast is measure by Full On Full Off standard.

* LightSource life results will vary depending on environmental conditions and usage. Actual product's features and specifications are subject to change without notice.

* Storage: Temperature: -20~60°C; Humidity: 10~90%RH (without condensation)



HDMI (1.4a)

PC (D-sub 15pin)

Monitor out (D-sub 15pin, Female)

Audio in (mini jack)

Audio out (mini jack)

RS232 In (D-sub 9pin, male)

LAN Port (RJ45 for Network)

USB Type A-2 (5V, 1.5A, Service)

Component Video in

Composite Video in (RCA)

RCA Audio in-L/R

IR Receiver (Front+Top)

12V Trigger

Kensington anti-theft lock slot

BenQ America Corp.

www.BenQ.us

BenQ is a registered trademark of BenQ Corp. All rights reserved. Product names, logos, brands and other trademarks featured or referred to in this material are the property of their respective trademark holders. Specifications subject to change without notice.



Because it matters