

Accessories and Lenses

Supplied Accessories	Remote control, power cord, AA batteries x 2, user's manual cd, RGB cable
-----------------------------	---

Replacement Parts

Remote Control	HL03171
-----------------------	---------

Projection Throw Chart

Screen Size	16:10	Throw Distance			
		Diagonal	Width	Min	Max
60	51	59	97		
80	68	78	129		
100	85	98	162		
120	102	117	194		
150	127	146	241		
200	170	196	323		
250	212	244	403		
300	254	292	483		

Throw Ratio: 1.15 - 1.9 : 1 (distance : width)
Screen size and throw distance are measured in inches.

Specifications

Display	Projection Technology	Single Chip DLP
	Resolution	WUXGA 1920 x 1200
	Brightness	5,000 ANSI lumens
	Colors	1.07 billion colors
	Aspect Ratio	Native 16:10. 4:3 and 16:9 compatible
	Contrast Ratio	20,000 : 1
	Throw Ratio (distance : width)	1.15 -1.9 : 1
Operation	Focus Distance	59" - 196"
	Display Size	36.7" - 201.9"
	Lens	Manual zoom x 1.65, manual focus & lens shift
	Expected Light Source Life*	Approximately 20,000 hours
Compatibility	Speaker Output	10W
	Keystone	H: +/-25° and V: +/-30°
	Computer	VGA, SVGA, XGA, WXGA, WXGA+, SXGA, SXGA+, WSXGA+, UXGA, WUXGA, MAC16", 480p, 576i, 576p, 720p, 1080i, 1080p
	H-Sync	15.0 kHz - 91 kHz
	V-Sync	24 Hz - 85 Hz
	Composite Video	NTSC, NTSC4.43, PAL, PAL-M, -N, SECAM
	Component Video	480i, 480p, 576i, 576p, 720p, 1080i, 1080p
	HDMI	480p, 576p, 720p, 1080i, 1080p Computer signal TMDS clock 27 MHz - 162 MHz
	MHL	480p, 720p, 1080i, 1080p Computer signal TMDS clock 27 MHz - 162 MHz
	Connectors	Digital Input
Computer Input 1		15-pin mini D-sub x 1 (shared with analog component video input)
Computer Monitor Output		15-pin mini D-sub x 1
Video Input		
Composite Video		RCA jack x 1
Component Video		15-pin mini D-sub x 1 (shared with analog computer input)
Audio Input		3.5 mm stereo mini jack x 1, 2RCA jack (L/R) x 1
Audio Output		2RCA jack (L/R) x 1
Microphone Input		3.5 mm mono mini jack
Network (LAN) Wired		RJ-45 jack x 1
HDBaseT		RJ-45 jack x 1
USB-A		USB type A x 1
Control Terminals		9-pin D-sub x 1 (RS-232 control)
Ratings & Warranty	3D Sync	Mini DIN 3-pin connector x 1
	Power Supply	AC 100V - 130V (50/60Hz) , 5.0A AC 200V - 240V (50/60Hz) , 2.5A
	Power Consumption	Normal: 460W
	Operating Temperature	32°F - 95°F (0°C-35°C) Normal mode 32°F - 104° (0°C-40°C) Eco mode
	Dimensions (W x D x H)	14.2" x 17.2" x 5.8"
	Weight	Approximately 23.1 lbs.
	Approvals	UL 60950-1 / cUL FCC Part 15 subpart B class A
Warranty	3 year limited parts and labor Extended Service Contract available (additional cost)	

* Actual light source life will vary by individual light source based on environmental conditions, selected operating mode, user settings and usage. Hours of average light source life specified are not guaranteed and do not constitute part of the product or light source warranty. Light source brightness decreases over time.



HI0555-9/17
All specifications subject to change without notice.
DLP and the DLP logo are registered trademarks of Texas Instruments. Crestron® and Crestron RoomView® are registered trademarks of Crestron Electronics, Inc. in the United States and other countries. HDMI, the HDMI Logo, and High-Definition Multimedia Interface are trademarks or registered trademarks of HDMI Licensing LLC in the United States and other countries. HDBaseT™ and the HDBaseT Alliance logo are trademarks of the HDBaseT Alliance.
©2017 Hitachi America, Ltd. All Rights Reserved.



Hitachi America, Ltd.

Toll Free: 1.800.HITACHI • Email: dmd.info@hal.hitachi.com
Web: hitachi-america.us/projectors

