

SHARP®



With an eye popping **3000 ANSI lumens** this LCD projector can be used in a wide variety of presentation scenarios. Mount it on the ceiling for use in conference rooms and board rooms. Take it from room to room for collaborative work group sessions. Travel with it on the road, afterall, its light enough and durable.

Sharp's **Notevision P10** has wide compatability, versatility, and is an outstanding performer. With multiple inputs and outputs, this projector can create a true multimedia experience. Incorporate computer sources, video sources, and audio to mesmerize your audience and leave a lasting impression.

Just one of several projectors in Sharp's Conference Series, NotevisionP10 includes image resizing technology for compatibility with a wide range of resolutions, digital motion correction for crisp video, presentation tools for ease of use, digital keystone correction and auto sync technology for simple set up, and much more. You'll see, its more than you bargained for!

ADVANCED FEATURES

- * 3000 ANSI Lumens Brightness with 85% Uniformity (CCR)
- * Multiple Inputs for Computer, Standard and HD Video Applications
- * HDTV Compatible - 480I/480P/720P/1080I (4:3 & 16:9 aspect ratios)
- * Component Video Input
- * 3D Digital Uniformity
- * Superior Video Quality: *3D Y/C circuitry, digital comb filter, 3D noise reduction, Interlaced or Progressive scan, digital motion correction*
- * Advanced ImageACE Resizing - Supports Resolutions up to UXGA!
- * Digital Keystone Correction with Edge Smoothing
- * 1:1.3x Power Zoom/Focus Lens w/Optional Short & Long Throw Lenses
- * Advanced Compatibility - 230 MHz Dot Clock
- * "PresenterPAK" - Sharp Exclusive Feature Set

PROJECTION DISTANCES

Screen Diagonal	Screen Width	Screen Height	Minimum Distance	Maximum Distance
40"	32"	24"	4.7'	6.1'
60"	48"	36"	7.3'	9.6'
72"	58"	43"	8.6'	11.1'
84"	67"	50"	10.1'	13.2'
100"	80"	60"	12.0'	15.11'
150"	120"	90"	18.4'	23.6'
200"	160"	120"	24.3'	32.2'
300"	240"	180"	36.2'	47.0'

Approx. Min / Max Projection Distance from Screen to Front of Lens

Distributed by:

SPECIFICATIONS

Resolution	XGA (1024 x 768) / 700 Scan-doubled TV Lines
Panel Type	3 - 1.3" Polysilicon TFT LCD
H & V Frequency	fH 15-126 kHz / fV 43 - 200 Hz
Dot Clock	230 MHz
PC Compatibility	XGA (VGA to UXGA w/ ImageACE Resizing)
Mac Compatibility	1024 x 768 (up to 1280x1024 w/ ImageACE Resizing)
WS Compatibility	1024 x 768 (various modes w/ ImageACE Resizing)
Video System	NTSC/PAL/SECAM - Interlaced or Progressive Scan
HD Compatibility	480I/480P/720P/1080I - 4:3 & 16:9 Aspect Ratios
Resizing	Advanced ImageACE Resizing - up to UXGA
Brightness	3000 ANSI Lumens w/ 85% CCR
Contrast Ratio	250:1
Lens Type	1:1.3x Power Zoom and Focus
PC Control	RS-232C - 9 pin DIN
Remote Control	IR w/ Mouse Control, Laser Pointer
IR Carrier Frequency	38 kHz
Wired Remote	3.5 mm Minijack
Audio System	2 Watt Stereo
Lamp	200 Watt, UHP User-replaceable
Fan Noise	39 dB
Power Source	110-240V AC, 50/60Hz
Power Consumption	320 Watts
Presentation Tools	"PresenterPAK"
Dimensions	10.3" x 5.5" x 14.0"
Weight	16.8 lbs.
Limited Warranty	3 Years Parts/Labor & Sharp ER, Lamp 90 Days

INPUTS/OUTPUTS

- 2 - Computer / RGB / Component Inputs [(2)15pin HD, (1)5 BNC - selectable]
- 1 - Video Input [Composite (RCA) or S-Video (4 pin DIN)]
- 3 - Stereo Audio Inputs (1, RCA pair L/R; 2, 3.5mm Stereo Minijacks)
- 1 - Computer / RGB Output [15pin HD]
- 1 - Audio Output (3.5mm Stereo Minijack)
- 1 - RS-232C Serial Port (9pin DIN)
- 1 - Wired Remote Control Input (3.5mm Minijack)

INCLUDED ACCESSORIES

Backlit Wireless Remote with Mouse Control, 9' RGB Signal Cable, 9' Minijack Audio Cable, 12' Grounded AC Cord, 270° Wireless Mouse IR Receiver, PS/2 and USB Mouse Adapters, Sharp Advanced Presentation Software, 3 BNC/RCA Adapters, Quick Reference Cards, Operation Manuals, RS-232C Adapter

OPTIONAL ACCESSORIES

AN-P100BAG	Soft Sided Carry-on Bag (projector only)
AN-P100WCC	Hard Shell Carry Case w/wheels (projector only)
XG-NV6WB	Hard Sided Bag w/wheels (projector & PC)
AN-P100SC	"ATA" Shipping Case w/wheels (projector only)
AN-XGCM61	Ceiling Mounting Bracket
AN-EP101AP	Extension Tube for Ceiling Mount
AN-JT200P	Angle Mount Joint for Ceiling Mount
AN-W6EZ	Wide Angle Zoom Lens - 1.3 - 1.7:1 throw ratio
AN-T6EZ	Telephoto Zoom Lens - 2.5 - 3.2:1 throw ratio

Design and specifications are subject to change.
All trademarks are property of their respective holders.

SHARP ELECTRONICS CORPORATION
LCD Products Group, Sharp Plaza, Mahwah, NJ 07430-2135
Sales "Hotline" (201) 529-8731 / Fax Number (201) 529-9636
Corporate Headquarters (201) 529-8200 / Literature Faxback (201) 512-2380
E-mail: ProLCD@SharpSEC.com

www.SharpLCD.com • 1-888- GO SHARP

Printed in USA LC-02-185 6/00 Rev 3.0

