

**PRO-95**  
**0.65" DLP® Ultra Short Throw Laser Illuminated Projector**

The all-new Wolf Cinema PRO-95 ultra-short throw projector provides for long imaging life – with a minimum of ~20,000 hours of usage - via BluHD™ laser/phosphor illumination technologies. The PRO-95 is the perfect solution for corporate and business use, retail and digital signage, in home theaters, outdoor theaters, schools and churches - without the frequent lamp changes as required in traditional lamp-based projection systems. With our precision 0.25:1 lens, you can project a 120" diagonal image from just ~26" [66cm] away! Viewers can enjoy amazingly bright, sharp and colorful HD imaging from just about anywhere a projector/screen combo can be placed - the projector can be easily positioned on a table top, ceiling mounted or attached to the optional wall mounting bracket [as shown, accessory part number WC-PM-PRO85]. The wall mount incorporates an adjustable arm extension and mounting plate, and provides for a wide range of roll, pitch and yaw adjustment capabilities.



**WC-PM-PRO85**  
**Ultra-Short Wall Mounting System**  
**(Sold Separately)**

**Specifications:**

<b>Imaging Technology</b>	0.65" DarkChip3 1080p DLP® Technology by Texas Instruments
<b>Brightness</b>	4000 ANSI Lumens
<b>Contrast</b>	120,000:1
<b>Throw Factor/Offsets</b>	0.25:1, Fixed. Vertical Offset: 120%
<b>Keystone Correction</b>	±15° Vertical, ±15° Horizontal
<b>Illumination Life [hrs]</b>	BluHD™ Laser/Phosphor; 20,000 hours to 50% brightness
<b>Noise Level (Eco mode)</b>	30dB
<b>Audio</b>	16-Watt speaker [1]
<b>Computer Compatibility</b>	UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
<b>Video Compatibility</b>	PAL (B, D, G, H, I, M, N, 576i/p), NTSC (M, 4.43/3.58 MHz, 480i/p), SECAM (B, D, G, K, K1, L) HD (1080i, 720p, 1080p)
<b>Input Scanning Frequency</b>	H-sync. 15.3 - 91.1kHz; V-sync. 24 - 85Hz
<b>Video I/O</b>	HDMI 1.4a [2], VGA - YPbPr/RGB [2], VGA output [1, shared with VGA 2], Composite video input, Stereo 3.5mm
<b>Audio I/O</b>	Mini-RCA audio input [2], 3.5mm Mini-RCA audio-output, 3.5mm Mic Input
<b>Control, Other I/O</b>	12V Mini-RCA trigger, RS-232C D-sub 9 pin, RJ-45, USB-A [5V power], Mini-USB [service]
<b>Dimensions (W x H x D)</b>	15.1" x 4.85" x 12.2" (383 x 124 x 310mm)
<b>Weight</b>	12.3 lbs (5.6 kg)
<b>Operating Temperature</b>	41-104°F (5-40°C), 90% max humidity
<b>Voltage</b>	AC Input 100-240V, 50-60Hz, auto-switching
<b>Power Consumption</b>	320W Bright mode / 280W Eco mode (< 0.5W Standby)
<b>Supplied Accessories</b>	AC Power Cord, IR Remote Control, AAA Batteries [x 2], VGA Cable, User manual USB thumb drive

**Optional Accessories:**

<b>WC-PS-03</b>	ProScaler MK III Video Processor with E-VariScope™ Technology
<b>WC-PM-PRO85</b>	Custom Ultra-Short Wall Mount, Adjustable

*Features and specifications subject to change without notice.  
DLP is a registered trademark of Texas Instruments. VariScope and E-VariScope are trademarks of Wolf Cinema.*