

E-Vision 6900 WUXGA White

5,750 ANSI / 6,500 ISO Lumens | Contrast Ratio: 2,000:1 (Dynamic Black) 1,000:1 native | Part No:118-045

E-VISION 6900 SERIES DIGITAL PROJECTORS



THE VISIONARIES CHOICE

Colour System:

4-segment (RGBW) colour wheel for high brightness (as standard)

6-segment (RGCMBY) colour wheel for enhanced colour (optional extra)

Display Type:

1 x 0.67" DarkChip™ DMD™

DMD Specification:

1920 x 1200 pixels native.

Fast transit pixels for smooth greyscale and improved contrast.

Aspect Ratio:

16x10

Fill Factor

87%

Key Features

Video & Graphics Processing

- HDMI 1.4a for Side by Side, Frame Packing, Frame Sequential and Top Bottom 3D formats.
- Dual and Triple Flash Processing can be used to multiply the displayed frame rate for 24p 3D sources.
- Synchronisation of active glasses.
- 24p and 1080p native display.

Geometry Correction

- Horizontal & Vertical Keystone.
- Scaling for fixed aspect ratio screens.

HDBaseT® Interface

- Built in support for reception of uncompressed High Definition Video over standard CAT5e/6 LAN cable.
- Allows the projector to be placed up to 100m from the source with low cost cabling.

Colour Processing

- Powerful colour correction for accurate colour matching.

Projector Controller Software

- Intuitive user interface for network control.
- Simultaneous control of user-defined groups of projectors.
- At-a-glance monitoring of projector status.

Source Compatibility:

HDMI including Deep Color™ processing.

Graphics standards up to 1920 x 1200 resolution at 60Hz via HDMI, DVI-D, HDBaseT or VGA

Component Video (SD and HD) via RGBHV.

Inputs/Outputs

Video & Computer			Communication & Control		
Type	Connector	Qty	Type	Connector	Qty
DVI-D 1.0	DVI	1	3D Sync In	BNC	1
HDMI 1.4a	HDMI	2	3D Sync Out	BNC	1
VGA / Analog RGB	15-pin D-Sub	1	LAN	RJ45	1
Monitor Out	15-pin D-Sub	1	RS232	9-pin D Sub	1
Component Video	5 x BNC	1	Wired Remote	3.5mm Stereo Jack	1
HDBaseT (see LAN)	RJ45	1	12V Trigger	3.5mm Stereo Jack	1
			Service Port	USB Type B	1

NOTE: The LAN port is shared with HDBase-T.

3D Formats Supported	HDTV Formats Supported
Frame Packing	1080p (24Hz, 25Hz, 30Hz, 50Hz, 60Hz)
Frame Sequential	1080i (50Hz, 60Hz)
Side by Side (half)	720p (50, 60Hz)
Top and Bottom	

Computer Compatibility	Bandwidth
Up to 1920 x 1200	165 MHz on analog RGB 165 Megapixels per second on HDMI

Remote Control	Automation Control
Addressable IR Remote Control, wireless and wired. On-board keypad.	Crestron RoomView® Connected LAN RS232 AMX (Device Discovery) Served web page

Colour Temperature
5400 to 9300K

Lamp Type	Typical Lamp Life
2 x 300W	Normal Mode: 3000 hours Eco Mode : 4000 hours

Lenses			
Lens	Part No.	Focus Range	Lens Shift
0.38 :1 fixed	117-341	0.68m - 2.44m	none
0.76 :1 fixed	112-499	0.81m - 5.08m	none
0.75 - 0.93 :1 zoom	115-339	1.02m - 12.7m	Vert: 0.5 (U) 0.3 (D) frame, Hor: 0.1(L) 0.2 (R) frame
1.25 - 1.79 :1 zoom	112-500	1.33m - 11.73m	Vert: 0.5 (U) 0.3 (D) frame, Hor: 0.1(L) 0.2 (R) frame
1.73 - 2.27 :1 zoom	112-501	1.83m - 14.9m	Vert: 0.5 (U) 0.3 (D) frame, Hor: 0.1(L) 0.2 (R) frame
2.22 - 3.67 :1 zoom	112-502	2.36m - 24.2m	Vert: 0.5 (U) 0.3 (D) frame, Hor: 0.1(L) 0.2 (R) frame
3.58 - 5.38 :1 zoom	112-503	3.8m - 35.35m	Vert: 0.5 (U) 0.3 (D) frame, Hor: 0.1(L) 0.2 (R) frame
5.31 - 8.26 :1 zoom	112-504	5.59m - 54.8m	Vert: 0.5 (U) 0.3 (D) frame, Hor: 0.1(L) 0.2 (R) frame

Lens Mount
Motorised and programmable shift, zoom and focus. Intelligent Lens Memory with 10 user-definable preset positions (except UST lens).

Mechanical Mounting	Orientation
Front/Rear Table	Table Top or Inverted: Yes
Front/Rear Ceiling	Pointing Up: Yes
Adjustable Front/Rear Feet	Pointing Down: Yes
	Roll (Portrait): +/-10° from horizontal

Power Requirements	Power Consumption
100-240VAC 50/60Hz single phase	Typical 693W @ 220VAC in Normal mode Typical 554W @ 220VAC in ECO mode Typical 724W @ 110VAC in Normal mode Typical 574W @ 110VAC in ECO modeW

Thermal Dissipation	Fan Noise

Typical 2378 BTU/Hour @ 220VAC in Normal mode
Typical 1901 BTU/Hour @ 220VAC in ECO mode
Typical 2484 BTU/Hour @ 110VAC in Normal mode
Typical 1969 BTU/Hour @ 110VAC in ECO mode
BTU/Hour

Normal mode: 38 dBA max, 36 dBA typical
Eco mode: 32 dBA max, 30dBA typical

Operating/Storage Temperature

Operating: 5 to 40C (41 to 104F)
Operating: 40 to 45 C (104 to 113F) with reduced light output.
Storage: -20 to 60C (-4 to 140F)

Operating Humidity

10% to 85%, relative, non-condensing

Weight (Chassis Only)

20 kg
44.1 lb

Dimensions

L: 46.5cm W: 51.0cm H: 21.6cm
L: 18.3in W: 20.1in H: 8.5in

Safety & EMC Regulations

CE, CB, FCC Class B, UL / cUL, CCC, CECP, RoHS
IEC EN 62471-5 RG2 (with std lens)

**Dimensions included for reference only and are subject to change. Please download the full set of CAD files for this display for more accurate information.*

Downloads

[PDF CAD Drawings](#)

[User Guides](#)

[AUTOCAD Drawings](#)

[Important Information](#)

Specifications subject to change without notice. Digital Projection version: - ©2016 Digital Projection.
DLP®, Digital Light Processing™ and DMD are trademarks of Texas Instruments, Inc

DIGITAL PROJECTION, INC 55 CHASTAIN ROAD, SUITE 115 KENNESAW, GA. 30144
T: 770.420.1350 | F: 770.420.1360 | www.digitalprojection.com

DIGITAL PROJECTION, LTD GREENSIDE WAY, MIDDLETON MANCHESTER, UK. M24 1XX
T: +44.161.947.3300 | F: +44.161.684.7674 | www.digitalprojection.co.uk

DIGITAL PROJECTION, CHINA Rm A2006, ShaoYaoJu 101 North lane, Shi AO International Center, Chao Yang District, Beijing, 100029, PR CHINA
T: +86.10.58239771 | F: +86 10 58239770

DIGITAL PROJECTION, ASIA 16 NEW INDUSTRIAL ROAD, #02-10 HUDSON TECHNOCENTRE SINGAPORE 536204
T: +65.6284.1138 | F: +65.6284.1238