

PowerLite L500W WXGA 3LCD Laser Projector

Contact Us 800.463.7766

Mon-Fri 6am-8pm, Sat 7am-4pm PT



Robust, compact WXGA laser projector with 5,000 lumens.

The compact, affordable PowerLite L500W laser projector delivers powerful performance for education and business applications. Get bright, vivid images with 5,000 lumens color/white brightness¹. This robust projector also offers WXGA resolution for widescreen images. Featuring breakthrough laser technology, it delivers a laser light source of up to 20,000 hours². And, it offers virtually maintenance-free operation with no lamps. Plus, it features a Dynamic contrast ratio up to 2,500,000:1. It also features advanced installation features and enterprise-level wireless security support (module sold separately).

Model: V11H908020

OUR PRICE :

\$1,999.00



[Write a review](#)



Bright, vivid color
5,000 lumens color/white
brightness¹.

**Colorful, widescreen
images up to 280"**
WXGA resolution (1280 x 800)

**Breakthrough laser
technology**
features a laser light source of up
to 20,000 hours²; plus, Instant
ON/OFF

**Extraordinary sharpness
and detail**
up to 2,500,000:1 Dynamic
contrast ratio

**Optional wireless
networking with
enterprise-level security**
plus wireless content sharing with
Epson iProjection™³; wireless
module sold separately

**Virtually maintenance-
free operation**
no lamps

- **Versatile connectivity** — supports 2x HDMI®, VGA, RJ-45, stereo mini and more
- **Advanced installation features** — 360-degree flexibility and geometric correction tools such as horizontal and vertical keystone, arc correction, Quick Corner® and more
- **Constant Brightness Mode**⁴ — fine-tune the brightness setting to help maximize run time
- **Remote management and control tools** — compatible with Crestron®, AMX®, PJLink and more; offers easy access and maintenance

Eco Features

- RoHS compliant
- Recyclable product⁵
- Epson America, Inc. is a SmartWay™ Transport Partner⁶

Better Products for a Better Future™

For more information on Epson's environmental programs, go to www.epson.com/environment

IMPORTANT INFORMATION ABOUT USAGE ENVIRONMENTS ►

What's In The Box:

- PowerLite L500W Projector
- Power cord
- Computer cable (VGA)
- Remote control and batteries
- Quick setup poster
- Cable cover

Specifications Projector:

Projection System:

RGB Liquid Crystal Shutter Projection System

Projection Method:

Front, Front/Ceiling, Rear, Rear/Ceiling

LCD Screen:

0.59" (D8 with C²Fine™)

Driving Method:

Poly-silicon TFT Active Matrix

Pixel Number:

1,024,000 dots (1280 x 800) x 3

Color Brightness - Color Light Output:

5,000 lumens¹

White Brightness - White Light Output:

5,000 lumens¹

Aspect Ratio:

16:10

Resolution:

1280 x 800 (WXGA)

Throw Ratio Range:

1.38–2.24

Size - projected distance:

60" screen: 1.79–2.92 m

Keystone Correction:

Vertical: ±30 degrees; Horizontal: ±30 degrees

Contrast Ratio:

Up to 2,500,000:1

Color Processing:

10 bit

Color Reproduction:

Up to 1.07 billion colors

Light Source Life:

Normal: 20,000 hours; Quiet: 20,000 hours; Extended: 30,000 hours

Laser Type:

Laser Diode

Effective Scanning Frequency Range:

Pixel Clock:

Analog: 13.5–162 MHz (up to UXGA 60 Hz)

Digital: 13.5–162 MHz (up to UXGA 60 Hz)

Horizontal:

Analog: 15–92 kHz

Digital: 15–75 kHz

Vertical:

Analog: 50–85 Hz

Digital: 24/30/50/60 Hz

Projection Lens:

Type:

Optical Zoom (Manual)/Focus (Manual)

F-number:

1.5–1.7

Screen Size:

Zoom: Wide: 29"–280" [0.85–8.45 m]; Zoom: Tele: 29"–280" [1.40–13.71 m]

Focal Length:

18.2–29.2 mm

Zoom Ratio:

1–1.6

Lens Cover:

Lens cap (without string)

Projector Details:

Interfaces:

- 2x HDMI
- Analog: D-sub 15 pin
- 1x Control I/O: RS-232C D-sub 9 pin
- USB-I/O: Type A 1x; Type B 1x
- Wired LAN RJ45
- Wireless LAN Optional Accessory
- Audio in (stereo): 2x
- Audio out (stereo): 1x

Fan Noise:

Normal: 37 dB; ECO: 25 dB

Projector Dimensions:

Including feet:

17.32" x 11.97" x 5.35" (W x D x H)

Excluding feet:

17.32" x 11.97" x 4.73" (W x D x H)

Weight - with standard lens:

Approx. 16.3 lb/7.4 kg

Remote Control:

Operating Distance:

8 m

Operating Angle:

- Front: Right/Left: ± 60 degrees; Upper/Lower: +30 to -20 degrees
- Rear: Right/Left: ± 30 degrees; Upper/Lower: +50 to +10 degrees

Power:

Power Supply Voltage:

100 – 240 V $\pm 10\%$, 50/60 Hz AC

Power Consumption:

Normal: 337 W; Quiet: 254 W; Networked Standby 2.0 W; Energy Saving: 0.3 W
