

MX707

[Overview](#)[Specifications](#)[Q&A](#)[Downloads](#)[Video](#)[Contact Us](#)

All Specifications

Projection System

Projection System	DLP
DMD size	0.55"

Marketing

Main Marketing Series	Business Projector
Product Features	1.3X zoom, 3D,SmartEco, LAN control

Display

Native Resolution	XGA (1024x768)
Native Aspect Ratio	4:3
Brightness (ANSI lumens)	3500
Contrast Ratio (FOFO)	13000:1
Selectable Aspect Ratio	16:10,16:9,4:3,Auto,Real
Display Color	30-bit (1.07 billion colors)
Light Source	Lamp
Light Source Wattage	203W
Light Source Life	a. Normal 5000 hrs,b. ECO 10000 hrs,c. SmartEco 15000 hrs,d. LampSave 15000 hrs

Optical

Throw Ratio	1.51~1.97 (65"±3% @ 2m)
Zoom Ratio	1.3x
Lens	F=2.56~2.68, f=22.04~24.14mm
Projection Offset (Full-Height)	115%
Keystone Adjustment	1D, Vertical ± 40 degrees
ANSI Uniformity (Min.)	-45%
Clear Image Size	60"~300"
Image Size	30"~300"

Picture

Picture Modes	3D,Cinema,Dynamic,Presentation,sRGB,User 1,User 2
Color Wheel Segment (Lamp)	6 segment (RYWCBG)
Color Wheel Speed	2X (50Hz),2X (60Hz)

[TOP](#)

MX707	Overview	Specifications	Q&A	Downloads	Video	Contact Us
-------	----------	----------------	-----	-----------	-------	------------

Resolution Support	VGA(640 x 480) to WUXGA_RB(1920 x 1200) *RB=Reduced blanking
Horizontal Frequency	15K~102KHz
Vertical Scan Rate	23~120Hz
HDTV Compatibility	480i
Video Compatibility	NTSC,PAL,SECAM
3D Compatibility	Frame Packing,Frame Sequential,Side by Side,Top Bottom

I/O Interface

PC in (D-sub 15pin)	(x1)
Monitor out (D-sub 15pin)	(x1)
Composite Video in (RCA)	(x1)
S-Video in (Mini DIN 4pin)	(x1)
HDMI in	HDMI-1 (1.4b/HDCP1.4/MHL),HDMI-2 (1.4a/HDCP1.4)
LAN (RJ45)	(x1)
USB Type Mini B	USB Type Mini B-1(service/Page up&down)
RS232 in (DB-9pin)	(x1)

Audio

Speaker	(x1),10W
Audio out (3.5mm Mini Jack)	(x1),1
Audio in (3.5mm Mini Jack)	(x1),1

Environment

Power Supply	AC 100 to 240 V, 50/60 Hz
Typical Power Consumption (110V)	265W
Stand-by Power Consumption	<0.5W
Network Stand-by Power Consumption	<2W
Acoustic Noise (Typ./Eco.)(dB)	33/29dBA
Operating Temperature	0~40°C

Accessories

Remote Control w/ Battery	RCX014
Power Cord (by region)	x1 (1.8M)
VGA(D-sub 15pin) Cable	1 (1.5m)
User Manual CD	1 (24L)

TOP

MX707	Overview	Specifications	Q&A	Downloads	Video	Contact Us
-----------------------	--------------------------	--------------------------------	-------------------------	---------------------------	-----------------------	----------------------------

Quick Start Guide	T (T8L)
Warranty Card (by region)	Yes
Universal Ceiling Mount	(Optional), Yes, CMG2

OSD

OSD Language	30L
--------------	-----

Smart System

Dimension & Weight

Dimensions (WxHxD) (mm)	314.2 x116 x216.3
Net Weight (kg)	2.0

Optical

Throw Ratio	1.51~1.97
Zoom Ratio	1.3X
Lens Control	Fixed lens
Keystone Correction	Vertical: ± 40 degrees
Projection Size	60"~140"
Projection Offset	115% \pm 5%

Display

Projection System	DLP Single 0.55" XGA
DMD type	DC3 DMD chip
Resolution	1024x768 pixels
Brightness	3,500 ANSI Lumens
Contrast Ratio*	10,000:1
Display Color	1.07 Billion Colors
Aspect Ratio	Native 4:3 (5 aspect ratio selectable)
Light Source	Lamp
Light Source Life*	5000/10000/15000 hours(Normal/Eco/SmartEco mode)

Audio

Built-in Speaker	10W x 1
------------------	---------

Feature

MX707	Overview	Specifications	Q&A	Downloads	Video	Contact Us
-------	----------	-----------------------	-----	-----------	-------	------------

Lock

Connectivity

I/O Port

Audio in (Mini Jack) x 1
 Audio out (Mini Jack) x 1
 S-Video in (Mini DIN 4pin) x 1
 Composite Video in (RCA) x 1
 HDMI 2 x 1
 HDMI 1/MHL x 1
 Computer in (D-sub 15pin) x 1
 Monitor out (D-sub 15pin) x 1
 USB (Type Mini B) x 1
 RS232 x 1
 LAN x 1

Compatibility

Resolution Support

VGA(640 x 480) to UXGA(1600 x 1200)

Horizontal Frequency

15K ~ 102KHz

Vertical Scan Rate

23 ~ 120Hz

HDTV Compatibility

480i, 480p, 576i, 567p, 720p, 1080i, 1080p

Video Compatibility

NTSC, PAL, SECAM

Power

Power Consumption(Max/Normal/Eco)

Normal 265W

Standby Power Consumption

Normal < 0.5W. Network < 2W.

Dimension and Weight

Product Dimensions (WxHxD)

283 X 95 X 222mm

Product Weight

2 KG ± 100g

Operation Condition

Noise Level(Normal/Eco)

33/29 dBA

Operating Temperature

0° ~ 40°C

Accessories

Accessories (Standard)

Power Cord (1.8M)
 Remote control
 AAA Batteryx2
 VGA cable (1.5M)
 User Manual CD (24L)
 Quick Start Guide (18L)
 Warranty Card
 Spare Lamp Kit
 RS232 Cable
 3D Glasses

Accessories (Optional)

TOP