

Installation Projector SU765

Display

Projection System	DLP Single 0.67" WUXGA
--------------------------	-------------------------------

DMD type	DC3 DMD Chip
-----------------	---------------------

Resolution	1920x1200 pixels
-------------------	-------------------------

Brightness	5,500 ANSI Lumens
-------------------	--------------------------

Contrast Ratio*	10,000:1
------------------------	-----------------

Display Color	30 Bits (1,037,000,000 colors)
----------------------	---------------------------------------

Aspect Ratio	Native 16:10 (5 aspect ratio selectable)
---------------------	---

Light Source	Lamp
---------------------	-------------

Light Source Life*	3000/5000/6000 hours(Normal/Eco/SmartEco mode)
---------------------------	---

Optical

Throw Ratio **1.39~2.09**

Zoom Ratio **1.5X**

Lens Control **Fixed lens**

Lens Shift **Vertical 13%**

Keystone Correction **2D, Horizontal / Vertical \pm 30 degrees**

Projection Offset **108%**

Projection Size **30"~300"**

Audio

Built-in Speaker **5W x 1**

Security

Security Lock **Security Bar**

Feature	2D Keystone, HDMI/VGA Signal Power ON, LAN Control, Panel Key Lock, HDMI2.0 (4K compability)
----------------	---

Compatibility

Resolution Support	VGA(640 x 480) to UXGA(1600 x 1200)
---------------------------	--

Horizontal Frequency	15K ~ 102KHz
-----------------------------	---------------------

Vertical Scan Rate	23 ~ 120Hz
---------------------------	-------------------

HDTV Compatibility	480i, 480p, 576i, 567p, 720p, 1080i, 1080p
---------------------------	---

Video Compatibility	NTSC, PAL, SECAM
----------------------------	-------------------------

Power

Power Consumption(Max/Normal/Eco)	440W/420W/330W
--	-----------------------

Standby Power Consumption	Normal < 0.5W. Network < 2W.
----------------------------------	---

Power Supply	AC 100 to 240 V, 50/60 Hz
---------------------	----------------------------------

Dimension and Weight

**Product Dimensions
(WxHxD)** **359.8 x 120.8 x 259.0mm**

Product Weight **3.7 Kg**

Operation Condition

**Noise
Level(Normal/Eco)** **39/36 dB**

**Operating
Temperature** **0° ~ 40° C**

Accessories

**Accessories
(Standard)** **Power Cord (1.8M)
Remote control
AAA Batteryx2
User Manual CD
Quick Start Guide (18L)
Warranty Card**

**Accessories
(Optional)** **Carry Bag
Spare Lamp Kit
Wireless Dongle (QCast/WDC10)
RS232 Cable
3D Glasses**

Connectivity

I/O Port

USB Type-A x1
USB Type-B x1
HDMI 1 x1
HDMI 2 x1
Monitor out (D-sub 15pin) x1
Computer in (D-sub 15pin) x1
LAN x1
3D Sync Out x1
DC 12V Trigger (3.5mm Jack) x1
Audio out (mini jack) x1
Audio in (Mini Jack) x1
Speaker 5W x1
RS-232 x1
Audio L/R in (RCA) x1
Composite Video in (RCA) x1

OSD

On Screen Display Language

**Arabic/ Bulgarian/ Croatian/
Czech/ Danish/ Dutch/ English/
Finnish/ French/ German/ Greek/
Hindi/ Hungarian/ Italian/
Indonesian/ Japanese/ Korean/
Norwegian/ Polish/ Portuguese/
Romanian/ Russian/ Simplified
Chinese/ Spanish/ Swedish/
Turkish/ Thai/ Traditional Chinese
(28 Languages)**