

Lightweight and Compact

- Only 4.8 lbs.
- 2.5" x 9.0" x 10.5" (h x w x d)

Brilliant DLP Display

- 1,000 ANSI lumens
- Digital Light Processing™ (DLP) display technology

Outstanding Picture Clarity

- True XGA, 1024 x 768 resolution

Excellent Plug-and-Project Setup

- Auto tracking
- Auto source detect
- Auto positioning
- Digital Keystone Correction (DKC)

Full-Featured Data/Video Solution

- Precision optics
- Video playback
- HDTV (1080i) support
- Digital Video Interface (DVI) input
- Built-in zoom lens
- Built-in speaker



TDP-P3 Projector

*Work anywhere, anytime
— any way you want*

choose freedom™
TOSHIBA

TDP-P3 Projector

Toshiba's TDP-P3 projector shines light on a new level of presentation capabilities for today's mobile professional. Designed for travel, the ultraportable, 4.8 lbs. light TDP-P3 boasts advanced features and technology that enable unprecedented image quality along with ease of use.

True XGA resolution dynamically re-creates your computer or video display for the ultimate in accuracy and detail. Engineered for crisp image definition even with the room lights on, the 1,000 lumen TDP-P3 uses Digital Light Processing (DLP) display technology to liven up images with true color fidelity. Digital Video Interface (DVI) allows for standard analog or 100% digital connection to a computer. Other advanced features include Digital Keystone Correction (DKC), 1080i HDTV video support, a one-touch zoom lens and a wireless remote control that operates both the projector and the PC. Setup is literally "plug and project" and when the meeting's over, the TDP-P3 fits easily in the same bag with your portable computer.



Display

- Digital Light Processing (DLP) technology by Texas Instruments

Resolution

- True XGA, 1024 x 768

Data Compatibility

- XGA, SVGA, VGA and Macintosh®

Video Compatibility

- Full NTSC, NTSC 4.43, PAL and SECAM
- 1080i HDTV video support

Aspect Ratio

- 4:3

Contrast Ratio

- 400:1

Brightness

- 1,000 ANSI lumens (typical)

Projection Lens

- 1.25:1 manual zoom lens

Projection Angle

- 11°

Light Source

- 120-watt High-Pressure Mercury-Arc lamp

Lamp Life

- 1,000 hours (average minimum)

Data Connection

- VESA® mini D-sub 15-pin
- VESA M1-DA DVI digital/analog connector with USB

Image Configuration

- Plug-and-project auto synchronization
- Auto tracking
- Auto positioning
- Auto source detect
- Auto black/white level detect
- Digital Keystone Correction (DKC)

Audio

- 1-watt mono audio system with built-in speaker

Control

- On-board, hard-cap microswitch panel
- Wireless remote control

Dimensions (h x w x d)

- 2.5" x 9.0" x 10.5"
(6.35cm x 22.86cm x 26.67cm)

Weight

- 4.8 lbs. (2.2 kg)

Power Supply

- 100-240VAC at 50-60Hz and 200-240VAC at 50Hz

Power Consumption

- 160 watts

Warranty

- 2-year limited warranty on parts and labor
- 90-day warranty on projection lamp

Standard Accessories

- Deluxe carrying case
- Wireless remote control
- Cables for data, video and audio connections

TDP-P3 Projection Distance (Image Sizes)

Distance to Screen	Min. Diagonal Image Size	Max. Diagonal Image Size
4.9' (1.5 m)	2.5' (0.8 m)	3.2' (1.0 m)
8.0' (2.4 m)	4.1' (1.2 m)	5.2' (1.6 m)
12.0' (3.7 m)	6.1' (1.9 m)	7.8' (2.4 m)
16.0' (4.9 m)	8.1' (2.5 m)	10.4' (3.2 m)
20.0' (6.1 m)	10.2' (3.1 m)	12.9' (3.9 m)
30.0' (9.1 m)	15.2' (4.6 m)	19.4' (5.9 m)
100.0' (30.5 m)	50.8' (15.4m)	64.7' (19.7 m)