

ELECTRONIC PROJECTION SYSTEMS



3M™ Multimedia Projector MP8610

The Educators' Choice

Designed to help education and business professionals collaborate and communicate more effectively, the affordable 3M™ Multimedia Projector

MP8610 delivers **consistent brightness,**

image clarity and resolution from

classroom to classroom or business to

business. Control your computer from

anywhere in the room with the

VirtualMouse remote control. Crisp SVGA resolution and 500 ANSI lumens

of light provide **brilliant, uniform projection.** **Rich, powerful sound** is

ensured by two built-in 10-watt stereo

speakers. With its **easy-to-use** control panel

and universal power supply, the 3M

MP8610 will captivate and educate any

audience.



Make the meeting.



KEY FEATURES

- 500 ANSI lumens of on-screen brightness
- Single panel, active-matrix TFT LCD technology with 16.7 million colors at true SVGA (800 x 600) resolution
- Rugged and durable for portability from classroom to classroom or business to business
- VirtualMouse remote control
- RS-232 serial interface support for fixed installations
- Two 10-watt, built-in stereo speakers for superior sound quality
- Affordable, long-life, metal halide lamp
- Kensington® security slot for protection from theft (Kensington Microsaver needed)
- Optional object display camera for use in presentations and educational settings
- Quiet operation
- Ceiling mountable
- Universal power supply for use anywhere in the world

Six Presentation Tools:

- Reveal, blank, freeze, timer, magnification, pointer — all accessed by remote control

Computer Compatibility:

- PC-compatible — XGA, SVGA, VGA
- Apple® Macintosh® (II, LC, Quadra, Power Macintosh and PowerBook®)

Video Compatibility:

- NTSC, PAL, SECAM, NTSC 4.43, PALM, PALN

Accessories Included:

- RGB computer cable
- RCA™ video cable, S-VHS cable, RCA/3.5 mm stereo/audio cable
- Serial RS-232 and PS/2® mouse adapter
- Remote control
- Detachable power cords
- Multilingual operator's guide

3M™ Multimedia Projector MP8610

TECHNICAL SPECIFICATIONS

- LCD type: 6.4" active-matrix TFT
- Resolution: 800 (W) x 600 (H) pixels (SVGA)
- Brightness: 500 ANSI lumens
- Colors: 16.7 million (maximum)
- Contrast ratio: 200:1 ANSI
- Aspect ratio: 4:3
- Lens: Wide-angle F/5.6
- Screen size: 40" (minimum) to 300" (maximum) diagonal
- Horizontal scan: 14-75 kHz
- Vertical scan: 40-120 Hz
- Input terminals:
 - S-Video: (1) mini DIN 4-pin
 - Video: (1) RCA jack
 - Audio: (2) 3.5 mm stereo jack
 - RGB: (1) high density D-sub 15-pin
- Output terminals:
 - Mouse control and RS-232C: (1) D-sub 9-pin (male)
- Lamp type: user-replaceable 400-watt metal halide
- Lamp life: 1,500 hours
- Dimensions: 11" (28.0 cm) W x 7" (17.8 cm) H x 17.3" (44.0 cm) L
- Speakers: 2 x 10-watt (20 watts)
- Weight: 13.4 lbs (6 kg)
- Operating temperature: 32°F (0°C) to 95°F (35°C)
- Storage temperature: -4°F (-20°C) to 140°F (60°C)
- Power consumption: 500 watts (maximum)
- Power supply: 100-130V AC, 200-240V AC, 50/60Hz
- Regulatory approvals: FCC Part 15 Class A, CE, UL, TUVGS
- Order number: 78-9236-6432-6

Optional Accessories

- User replaceable lamp kit: 78-6970-8577-5
- Optional object display camera: 78-6969-8578-3
- MP8610 soft travel case: 78-6969-8579-1
- MP8610 shipping case: 78-6969-8580-9
- MP8610 ceiling mount: 78-6969-8581-7
- Ceiling mount extension cable kit: 78-6969-8582-5
- Macintosh cable set: DY-0205-1361-9
- Monitor splitter box: XX-0034-1736-5
- RGB cable extension: XX-0034-1131-9

1-800-328-1371

www.3M.com/meetings



3M Visual Systems Division

Building A145-5N-01
6801 River Place Blvd.
Austin, TX 78726-9000

3M Canada

P.O. Box 5757
London, Ontario, Canada
N6A 4T1

3M Mexico, S.A. de C.V.

Apartado Postal 14-139
Mexico, D.F. 07070
Mexico



Recycled paper,
40% pre-consumer,
10% post-consumer

Litho in U.S.A. © 3M 1998
78-6970-7811-7 (11820.0)LP

Specifications subject to change without notice.

Apple, Macintosh, Mac and PowerBook are registered trademarks of Apple Computer, Inc. PS/2 is a registered trademark of IBM Corp. RCA is a trademark of Radio Corporation of America. Kensington is a registered trademark of Kensington Technology Group.