

Specification

Display	Light Source	LED
	Resolution	1080P
	Brightness	450 ANSI Lumens
	Video Format	MP4、MKV、WMV、3GP、MPG、VOB、TP、
	Picture Format	TS、DAT、MOV、FLV
	Text Format	JPG、PNG、BMP、JPEG
		.txt

Projection	Focus	Auto
	Keystone	Auto
	Screen Alignment	Auto
	Obstacles Avoidance	Auto
	Throw Ratio	1.25:1
	Projection Size	40"-120" ³
	Distance	Min 3.63 ~ 10.89 ft ³

Audio	Speaker	JBL
	Audio	Dolby Audio
	Audio Format	MP3, AAC, LPCM, APE, FLAC, OGG, AMR

Battery	Video Playtime	2.5h ¹
	Music Playtime	18h ¹
	Charging Time	3.5h (Standby Mode), 5.5h (Power on)

Operating System	T2	Yaber OS
------------------	----	----------

	T2 Plus	Yaber OS + Google TV
Connectivity	Bluetooth	BT5.0
	Wi-Fi	Wi-Fi 6
	NFC Screencast	Yes
	Ports	USB 2.0 × 1, HDMI × 1, Audio Out × 1, RJ45 × 1
Measurements	Size	165 × 140 × 290mm / 6.5 × 5.51 × 11.42 inches ⁵
	Weight	2.5kg / 5.51 lbs ⁶
	Handle	Yes
What's Included	Projector T2	× 1
	Power Cord	× 1
	HDMI Cable	× 1
	Remote Control (IR)	× 1
	Quick Start Guide	× 1
	Lens Cover	× 1
	Brand Card	× 1
	FAQ	× 1 (Special for T2)
	TV Dongle	× 1 (Special for T2 Plus)
	TV Dongle Adaptor	× 1 (Special for T2 Plus)
	Remote Control (Bluetooth & IR)	× 1 (Special for T2 Plus)

1.The provided data is derived from laboratory test conditions. Actual performance and usage time may vary based on various factors, including but not limited to the working environment, ambient temperature, and intensity of usage.

2.Brightness (light output) will vary depending on usage conditions. White light output is measured in accordance with IEC 61947-1:2002 The nominal value represents the average value of mass production and is tested under ideal laboratory conditions in the performance mode/high power mode.

3.The throw distances above are estimations and may differ in actual usage scenarios. Adjustments required are based on your specific living space dimensions and conditions.

4.For handle stand functionality, it is recommended to keep the angle within 15°. Exceeding this angle may cause problems such as inability to perform keystone

correction, autofocus issues, and image distortion.

5.The actual size may vary based on configuration, manufacturing, and testing method.

6.The actual weight may vary based on configuration, manufacturing process, and testing method.

* Actual product features and specifications (including appearance, color, and size) and actual display aspects (including backgrounds, interface, and icons) may vary by country. Please consult the point of sale for further information.

* All performance data in the preceding pages are theoretical values obtained by Yaber internal laboratories through tests conducted under particular conditions. Refer to

the aforementioned product details for more information on the specific testing conditions. Actual performance may vary based on individual product configuration,

software versions, application conditions, and environmental factors. All data is subject to actual usage.

* Yaber makes every effort at the time of publication to ensure the accuracy of product information it provides. Due to subsequent changes involving product batches,

production, and supply factors, it may be necessary for Yaber to make changes and adjustments to text and images so that they match the performance, specifications,

indexes, and components of the actual product. Product information is subject to such changes and adjustments without notice.

* Operating temperature: 32°F to 100°F

* All parameters listed on this page are measured in an Yaber internal test environment for mass production. User experiences may vary in different settings, usage

conditions, software versions, etc. Please check the official Yaber website for detailed test standards and data.