



E-Vision 12000i 4K+

12,000 ISO / 10,800 ANSI Lumens | Contrast Ratio: 20,000:1 (Dynamic Black) | Part Number: 124-459

Key Specifications:

Colour System:	Laser Phosphor with Colorboost (Red Laser). Phosphor wheel: 2 x 7200rpm (120Hz) Colour wheel: 8 Segment RGBYRGBY 2 x 7200rpm (120Hz)
Display Type:	1 x 0.8" HEP DMD™ (High Efficiency Pixel)
DMD Specification:	1920 x 1200 pixels native display. (3840 x 2400 via 4-way pixel shift technology) Fast transit pixels for smooth greyscale and improved contrast.
Aspect Ratio:	16x10
Fill Factor	87%
Key Features:	Video & Graphics Processing • Nexus electronics platform • Support 3840 x 2160 display resolution • HDMI 2.0 • DisplayPort 1.2 • 10-bit colour processing (30-bits per pixel) 1,073,741,824 colours • Hue, Saturation and Gain colour management. • 24p and 1080p native display. • HDR support • Input source automatically detected • Selectable Dynamic Black • DICOM simulation mode • Optics engine sealed to IP6X Geometry Correction • Vertical & Horizontal Keystone correction • Four Corner adjustment • Rotation -100 to +100 with +/- 0.25° per step • Selectable aspect ratios: 5:4 / 4:3 / 16:10 / 16:9 / 1.88 / 2.35 / TheaterScope / Source / Unscaled

- Digital Zoom 0% ~ 100%
- Blanking control for custom input window sizing.
- Scaling for fixed aspect ratio screens. 16:10 / 16:9 / 4:3 / 2.35:1
- Custom warp

Edge Blending

- Correction for non-active pixels at the edge of the display.

HDBaseT® Interface

- Built in support for transmission of uncompressed High Definition Video over standard CAT5e/6 LAN cable.
- Allows the projector to be placed up to 100m from the source with low cost cabling.
- HDBaseT® Includes Ethernet 100BaseT and RS232/IR control.

Colour Processing

- Powerful seven point colour correction for accurate colour matching.

Projector LAN Control

- Free Digital Projection Projector Controller II software
- Intuitive user interface for network control.
- At-a-glance monitoring of projector status.
- Simultaneous control of user-defined groups of projectors.

Source Compatibility

12G-SDI, Supports a high data transfer rate of up to 12 gigabits per second (Gbps), enabling the transmission of uncompressed 4K UHD (Ultra High Definition) video signals with a single connector

Graphics standards up to WUXGA 1920 x 1200 - 120Hz RB, Up to WQXGA 2560 x 1600 60Hz RB (DisplayPort)

Video standards including HDTV 1080p - 60Hz and 4K+ (3840 x 2400) 60Hz

Support for colour gamuts up to P3

Inputs/Outputs

Video & Computer		
Type	Connector	Qty
HDMI 2.0b	HDMI	x 2
Display Port 1.2	DisplayPort	x 2
12G SDI IN	BNC	x 1
12G SDI OUT	BNC	x 1
HDBaseT	8P8C "RJ45"	x 1
Communication & Control		
Type	Connector	Qty
3D Sync In	BNC	1
3D Sync Out (loop through)	BNC	1
3D Sync Out for IR	BNC	1
LAN / Art-Net	EtherCON RJ45	1
HDBaseT/Ethernet/RS232/IR	RJ45	1

	Serial In RS-232C Serial Out RS-232C Wired Remote In Wired Remote Out 12V Trigger 12V 350mA USB Power out 5V/2A	9-pin D-Sub 9-pin D-Sub 3.5mm Stereo Jack 3.5mm Stereo Jack 3.5mm Stereo Jack USB Type A	1 1 1 1 1 1																																
3D Formats Supported																																			
HDTV Formats Supported	EDTV (480p, 576p), HDTV (720p, 1080i, 1080p), 4K+ (3840 x 2160), DCI 4K (4096 x 2400)																																		
Computer Compatibility	VGA, SVGA, XGA, SXGA, SXGA+, UXGA, WUXGA, WQXGA																																		
Bandwidth																																			
Remote Control	Infrared/Wired Remote Control Unit																																		
Automation Control	LAN - Webpage control TCP/UDP control RS-232 Alert Mail for Projector LAN Control-Crestron® Connected LAN Control-PJ Link Class 1 compatible LAN Control-AMX® Device Discovery Art-Net (DMX) control																																		
Colour Temperature	User selectable (3200K/ 5400K / 6500K / 7500K / 9300K / Native)																																		
Operation																																			
illumination Type	Laser Phosphor. ECO mode support (80% Brightness)																																		
Typical illumination Life	20,000 hours																																		
Lenses	<table><tr><th>Lens</th><th>Part No.</th><th>Optimised Focus Range*</th><th>Lens Shift (Frame)</th></tr><tr><td>0.31 - 0.33:1 zoom</td><td>124-318</td><td>0.38 - 3.01m</td><td>Vert: +/- 50% Hor: +/- 20%</td></tr><tr><td>0.55 - 0.75:1 zoom</td><td>124-319</td><td>0.69 - 6.58m</td><td>Vert: +/- 50% Hor: +/- 20%</td></tr><tr><td>0.74 - 1.08:1 zoom</td><td>124-320</td><td>0.75 - 12.19m</td><td>Vert: +/- 50% Hor: +/- 20%</td></tr><tr><td>1.05 - 1.41:1 zoom</td><td>124-321</td><td>1.06 - 18.94m</td><td>Vert: +/- 60% Hor: +/- 20%</td></tr><tr><td>1.4 - 2.11:1 zoom</td><td>124-322</td><td>1.47 - 27.86m</td><td>Vert: +/- 60% Hor: +/- 20%</td></tr><tr><td>2.1 - 4.0:1 zoom</td><td>124-323</td><td>2.24 - 54.19m</td><td>Vert: +/- 60% Hor: +/- 20%</td></tr><tr><td>3.9 - 7.0:1 zoom</td><td>124-446</td><td>4.3 - 90.57m</td><td>Vert: +/- 60% Hor: +/- 20%</td></tr></table> * Lens focal ranges above are the optimised distances but are likely to focus further, please contact your RSM for more details. Lens ratio tolerances: E-Vision Series: +/-3%. HighLite Series: +/- 5%. M-Vision Series: +/- 2%. Titan Series: +/-2%, INSIGHT Series: +/-2%,			Lens	Part No.	Optimised Focus Range*	Lens Shift (Frame)	0.31 - 0.33:1 zoom	124-318	0.38 - 3.01m	Vert: +/- 50% Hor: +/- 20%	0.55 - 0.75:1 zoom	124-319	0.69 - 6.58m	Vert: +/- 50% Hor: +/- 20%	0.74 - 1.08:1 zoom	124-320	0.75 - 12.19m	Vert: +/- 50% Hor: +/- 20%	1.05 - 1.41:1 zoom	124-321	1.06 - 18.94m	Vert: +/- 60% Hor: +/- 20%	1.4 - 2.11:1 zoom	124-322	1.47 - 27.86m	Vert: +/- 60% Hor: +/- 20%	2.1 - 4.0:1 zoom	124-323	2.24 - 54.19m	Vert: +/- 60% Hor: +/- 20%	3.9 - 7.0:1 zoom	124-446	4.3 - 90.57m	Vert: +/- 60% Hor: +/- 20%
Lens	Part No.	Optimised Focus Range*	Lens Shift (Frame)																																
0.31 - 0.33:1 zoom	124-318	0.38 - 3.01m	Vert: +/- 50% Hor: +/- 20%																																
0.55 - 0.75:1 zoom	124-319	0.69 - 6.58m	Vert: +/- 50% Hor: +/- 20%																																
0.74 - 1.08:1 zoom	124-320	0.75 - 12.19m	Vert: +/- 50% Hor: +/- 20%																																
1.05 - 1.41:1 zoom	124-321	1.06 - 18.94m	Vert: +/- 60% Hor: +/- 20%																																
1.4 - 2.11:1 zoom	124-322	1.47 - 27.86m	Vert: +/- 60% Hor: +/- 20%																																
2.1 - 4.0:1 zoom	124-323	2.24 - 54.19m	Vert: +/- 60% Hor: +/- 20%																																
3.9 - 7.0:1 zoom	124-446	4.3 - 90.57m	Vert: +/- 60% Hor: +/- 20%																																
Lens Mount	Centred lens for installation flexibility																																		

	Motorised and programmable shift, zoom and focus. Intelligent Lens Memory with 10 user-definable preset positions (except UST lens).			
Mechanical Mounting	Front/Rear Table Front/Rear Ceiling Adjustable Front/Rear Feet Ceiling Mount compatible chassis with 6 off M4*0.7 mounting holes available, Maximum screw length 16mm			
Orientation	Table Top or Inverted: Yes Pointing Up: Yes Pointing Down: Yes Roll (Portrait): Yes			
Power Requirements	100-240VAC 50/60Hz single phase			
Power Consumption	990W (max)			
Thermal Dissipation	TBD			
Fan Noise	Normal mode: 40 dBA typical Eco Mode: Max 39 dBA			
Operating/Storage Temperature:	Operating: 0 to 40 °C (32 to 104 °F) Force ECO over 35°C (95°F)			
Operating Humidity	90% (with maximum temperature of 35°C (95°F))			
Dimensions	L: 598mm x W: 500mm x H:218mm L: 23.54 inch x W: 19.68 inch x H: 8.58 inch			
Safety & EMC Regulations	TBD			
Accessories	<table><tr><td>Accessory</td><td>Part No.</td></tr></table>		Accessory	Part No.
	Accessory	Part No.		
<i>*Dimensions included for reference only and are subject to change. Please download the full set of CAD files for this display for more accurate information.</i>				
Downloads	PDF CAD Drawings AUTOCAD Drawings STEP / IGS Drawings			
User Guide				



DIGITAL PROJECTION, LTD



Unit 3, Aniseed Park, Broadgate,

Oldham, UK OL9 9XA



T: +44 (0)161 947 3300



www.digitalprojection.com



Specifications subject to change without notice.
 ©2024 Digital Projection. DLP®, Digital Light Processing™ and DMD are trademarks of Texas Instruments, Inc



DIGITAL PROJECTION, INC



55 Chastain Road, Suite 115 Kennesaw, GA.

30144



T: 770.420.1350 | F: 770.420.1360



www.digitalprojection.com



DIGITAL PROJECTION, CHINA



Rm A2301, Shaoyaoju 101 North Lane, Shi Ao

International Center, Chaoyang District, Beijing 100029,
PR China



T: +86.10.58239771 | F: +86 10 58239770

A brand of 