

LP920

InFocus® LP 920

The fixed installation projector



Specifications

- 2200 ANSI lumens
- Quiet - less than 37 dB
- Optical lens shift
- Case color matches most acoustical ceiling tiles
- True soft power
- Built-in digital/analog connectivity
- Flawless video quality
- Advanced 3 Poly-silicon LCD display with microlens array
- Manual zoom and focus lens
- Control using onboard key panel, LaserPro Remote and RS-232
- 3 additional lens options add versatility
- HDTV compatible

Display:	3 x 1.32" Poly-Silicon TFT LCD's with microlens array, Active-matrix
Brightness:	2200 lumens
Resolution:	True 1024 x 768 XGA, resizes VGA & SVGA , SXGA compression
Contrast Ratio:	350:1
Lens Shift:	0 - 12°
Projection Lens:	Multiple lens configurations available (w/ratio distance to image width) — Standard zoom (1.81:1 – 2.50:1) — Long Throw Zoom (2.50:1 – 4.31:1) — Wide Angle Zoom (1.37:1 – 1.62:1) — Ultra Wide Angle (.98:1)
Leveling Adjustment:	+/-3°
Audio:	2 x 5 watt built-in stereo speakers
Displayable Color	16.7 million colors
Palette:	2,359,296 pixels (1024 x 768 x 3)
Number of Pixels:	PC and Macintosh
Data Compatibility:	Manual zoom lens, focus (1:3:1 zoom, F = 1.8-2.3, F = 49-69 mm)
Projection Lens:	Front Projection, Rear/Ceiling Projection
Projection Methods:	Ultra High Efficiency (UHE) 220W (user replaceable), 2000 hours typical
Light Source:	Less than 37db
Acoustic Signature:	NTSC, NTSC 4.43, PAL, PAL M, PAL N, PAL 60, SECAM, HDTV (1080i)
Interface Standards:	RS-232c, USB-B, USB-A (through M1-D/A), CableWizard
Communication:	3x Audio In, 1 Audio Out, RGBHV, VESA, Cable Wizard, M1 D/A, Component Video, Composite Video, S-Video, Wired Remote, USB-B, RS-232c
Input Terminals:	On-board, hard-cap microswitch keypad , LaserPro Remote, RS-232c
Control:	16.5 w x 8.25 h x 19.5 d in the standard lens configuration
Dimensions:	25.5 lbs (11.5 kg) in the standard configuration
Weight:	English, French, German, Spanish, Chinese, and Japanese
Menu Language:	Base: Cool Gray #2, Accent: Cool Gray #4
Case Color:	100 - 120V, 200 - 240V @ 50 - 60 Hz
Power Supply:	100 - 120V~ 6A; 60Hz, 200-240V~ 3A; 50Hz
Power Consumption:	2 year
Warranty:	Power cord, LaserPro Remote
Ships Standard With:	Replacement Lamp, Shipping Case (ATA approved), Ceiling Mount Plate and Kit, Projector Cable Cover, 900 Series Wide Angle Zoom Lens, 900 Series Ultra Wide Angle Lens, 900 Series Long Throw Zoom Lens, M1 to VGA/USB-A (analog), M1 to DVI/USB-A (digital), Digital/Analog Interface Card, 1 year extended warranty
Optional Accessories:	Additional IOpen920 cables and remotes available; please visit www.infocus.com/store . The IOpen920 is compatible with all InFocus cables and remotes.