

Vista S3



When image is everything...

The Vista S3 represents an evolution in projection technology. Utilizing possibly the most advanced optical systems available today in conjunction with Christie's superior digital processing technology, the S3 promotes outstanding image performance.

At the heart of the S3 lies the very latest Digital Light Processing™ technology, a 3-chip DMD™ set with true SXGA resolution combines with a highly efficient 700W Xenon CERMAX® illumination system to deliver the sharpest, brightest and most faithfully reproduced images. The S3 also gives you the capability to input pixel formats with independent horizontal and vertical scaling control, this and the optional ADP (Advanced Digital Processing) module allows you to handle the most demanding projection requirements to place the perfect picture on your screen.

The S3 shares a common architecture with all other models in the Vista range. If your projection needs change, your S3 system can change to meet them. The S3 can be upgraded at only an incremental cost to deliver 5000 ANSI lumens of stunning SXGA resolution images.

This compact unit weighs in at just 40 kg and the projector's simple and functional design is both practical and unobtrusive, ensuring your audience's attention remains fixed firmly on your presentations. This powerful projection system is supported by a comprehensive selection of lenses, modules and accessories making it ideal for a wide range of fixed installation applications.

- 3000 ANSI lumens
- True SXGA resolution
- Pixel clock 160 MHz
- Vertical and Horizontal scaling
- LiteLOC™ light output control
- Modular architecture
- Superior lamp efficiency
- Inexpensive brightness upgrade path
- Compact design
- Advanced inverse telecine digital processing
- 6' to 40' diagonal image size
- Intuitive graphical user interface
- Superior image quality
- Xenon illumination system

APPLICATIONS

- | | |
|--|------------------------------------|
| • Boardrooms, executive briefing centers | • Corporate theaters |
| • Broadcast studios | • Auditoriums, arenas, churches |
| | • Casinos, theme parks and museums |


CHRISTIE
Project. Present. Perform.

Vista S3 • Specifications

Brightness

- 3000 ANSI lumens
- 90% brightness uniformity across the screen

Contrast Ratio (1.5-2.2:1 zoom lens)

- 350:1 ANSI, 400:1 full field

Resolution/Digital Processing

- 3 chip 0.9" DMD™, (Digital Micromirror Device) system
- True SXGA 1280 x 1024 chip resolution
- 13-bit user selectable gamma table
- More than 1 billion displayable colours

Dynamic Scaling

- Resizing capabilities to scale down from 1600x1200 and up from 640x480 to SXGA resolution
- Independent horizontal and vertical scaling adjustment for graphics and video inputs

HDTV/DTV Compatibility

- Full HDTV/DTV compatibility on analogue RGB/YpBPr inputs
- Accepts 480i, 480p, 576i, 576p, 720p, 1035i, and 1080i formats at all applicable frame/field rates
- Accepts 1080p at 24, 25 and 30 Hz frame rates
- Optional HDTV Serial Digital Input Module

Various Keypads

- Standard hand-held IR backlit remote keypad, front and rear infrared sensors
- Built-in backlit keypad
- Optional RS422 two-way remote controller with LCD display using 6-pin XLR connector with range of 600ft (183m)
- Optional wired backlit remote keypad with 3-pin XLR connector

Variable Lamp Power Supply/Light Output Control (LiteLOC™)

- "Auto Brightness" mode to maintain constant brightness over time
- "Lamp Conserve" mode to extend the lamp life
- "Max Brightness" mode for maximum light output

Power Requirements

- Line voltage 100V AC to 240 VAC +/- 10% @ 50/60 Hz
- Power consumption: 1150 W maximum
- Thermal dissipation: 3950 BTU/hr
- Operating current: 11.5A maximum (at 100 VAC)

Weight and Size

- 39.9kg (88lbs)
- 22.28"W x 30.1" L x 11.88" H (56.6cm W x 76.5cm L x 30.2cm H)

FEATURES



- The S3 offers the ability to input pixel formats with independent horizontal and vertical scaling control.



- The S3 offers an inexpensive brightness upgrade path.



- "Bayonet-style" lens insertion system and lens mount tilt adjustment.

Horizontal Frequency Range

- 15 to 120 kHz

Vertical Frequency Range

- 24 to 120 Hz

Field Interchangeable Optional Lenses

- Fixed short throw lens: 1.2:1
- Zoom lenses: 1.5-2.2:1, 2.2-4:1, and 4-7:1
- Up to 130% of vertical lens offset for off-axis projection
- Up to 80% of horizontal lens offset
- Compatibility with VistaGraphX lenses: 0.8:1, 2.5-4:1, 4-7:1 (adapter required)
- Screen size 1.8m - 12.2m (6ft - 40ft) diagonal

Lens Mount

- Manual horizontal and vertical lens offset, focus and zoom adjustments
- "Bayonet-style" lens insertion system
- Lens mount tilt adjustment
- Built-in light shutter

Inputs

- Built-in RGB/YUV/YpBPr inputs allowing separate H and V syncs, composite sync and sync-on green/luma (5 BNC connectors)
- Multi-standard Video Decoder Module (NTSC 3.58, NTSC 4.43, PAL, PAL 60, PAL M, PAL N, SECAM) with one composite video input (BNC and RCA connectors) and one S-video input (two BNC and 4-pin mini-DIN connectors)
- Built-in Audio Control Module with 4 stereo audio inputs and 1 stereo output (RCA connectors)
- Slot for an optional input module
- Full compatibility with third-party switchers

Control / Networking

- Third party control system and switcher compatibility
- Dual RS232 ports for computer control, with loop through for connection of multiple projectors
- Dual 6-pin XLR RS422 ports for connection of optional LCD two-way controllers and loop-through to multiple projectors up to 600ft (183m)

Diagnostics

- Built-in LCD diagnostic display indicates operational status and error messages
- Power and Status LED
- Full diagnostics through RS232 9-pin D connector

Graphical User Interface

- Auto Set-up feature
- "Direct Access" intuitive user interface for complete projector control in 5 world languages
- On screen user movable menus to fit different image aspect ratios (4:3, 5:4, 16:9, etc.)
- On screen help menus
- 100 channel memories
- Auto power feature

Lamp Specification/Colour Temperature

- 700W CERMAX® Xenon illumination system
- Pre-aligned lamp module
- Constant colour temperature over the lamp life
- Colour temperature adjustment range: 32000K to 93000K
- User replaceable lamp within 5 minutes
- Typical lifetime: 1000 hours

Standard Accessories

- IR remote keypad with batteries
- User manual with warranty card
- 2.44m (8ft) line cord

Optional Accessories

- Serial Digital Input (SMPTE 259M/CCIR 601) with loop-through feature
- Digital HDTV Input module (with loop-through feature) compatible with all known HDTV formats
- DVI/DFP Input module
- 10-bit ADP (Advanced Digital Processing) module
- Wired remote keypad
- Motorized lens mount upgrade
- RS422 two-way remote LCD controller
- Replacement lamp module
- Remote infrared sensor
- Service manual
- Librarian communication software
- Transit case

Regulatory Approvals

- CSA, UL and European safety approvals
- North American and European EMV/EMC approvals

Warranty

- One year parts and labour
- Accessories: One year

Head Offices

USA
10550 Camden Drive
Cypress, CA 90630
PH: +714-236-8610
FX: +714-503-3385
Toll free: (800) 407-7727 (NA only)
sales-us@christiedigital.com

CANADA
809 Wellington Street North
Kitchener, Ontario N2G 4Y7
PH: +519-744-8005
FX: +519-749-3136
Toll free: (800) 265-2171 (NA only)
sales-canada@christiedigital.com

Branch Offices

UNITED KINGDOM
PH: +44 118 977 8000
FX: +44 118 977 8100
sales-europe@christiedigital.com

SINGAPORE
PH: +65 6877-8737
FX: +65 6877-8747
sales-singapore@christiedigital.com

FRANCE
PH: +33 (0) 1 47 48 28 07
FX: +33 (0) 1 47 48 26 06
Mobile: +33 (0) 6 76 47 43 62
sales-france@christiedigital.com

GERMANY
PH: +49 2161 664540
FX: +49 2161 664546
sales-europe@christiedigital.com

CHINA
PH: +86 21 6278 7708
FX: +86 21 6278 7707
sales-china@christiedigital.com

