Onboard I/O Ports

Audio/Video Inputs

- DB Connector
- HDMI (Digital Connector Component, HDTV)
- Mini DIN Connector (S-Video)
- RCA Composite Connector (Video)
- Audio Mini Jack (DVI)
- Audio Mini Jack (S-Video/Video)
- Audio Mini Jack (15-PIN D-Sub)

Audio/Video Output

- Audio Mini Jack

Communications

- RS-232
- +12V (Motor Screen Trigger)

Remote Control

On-Screen Display

- Multi-language Operation
- Projector Management
- Image Control
- Audio Control

Display	DLP® Technology by Texas Instruments
Resolution	Native XGA (1024 x 768), SVGA (800 x 600) compression
Video Compatibility	1080i (1400i/p), 720p/p, 576p/p, 1080i/p PAL, SECAM, M-NTSC, NTSC4.43
Computer Compatibility	IBM PC and Compatibles, Apple Macintosh, Mac, MAC PDB Series, Fujitsu PR Series, and VESA Standards SXGA, XGA, SVGA, VGA (resizable)
Aspect Ratio	4:3 Native, 16:9 Compatible (1024 x 576)
Contrast Ratio (Typical)	1000:1
Displayable Colors	16.7 Million Colors
Brightness (Typical)	1,000 ANSI Lumens
Projection Lens	F=2.46 ~ 2.65, f = 20.8 ~ 24.0 mm, 1.1:1.2 Manual Zoom and Manual Focus
Projection Screen Size	28" (0.62m) ~ 300" (7.7m) Diagonal
Projection Distance	5.0' (1.5m) ~ 32.8' (10.0m)
Horizontal Scan	15 ~ 100 kHz
Vertical Refresh Scan	43 ~ 120 Hz
Lamp Type	200 W User Replaceable UHP Lamp
Lamp Life (Typical)	2,000 Hours
Keystone Correction	+/- 15 Degrees
Audio	2 Stereo Speakers (Can offer 3 watts output)
Weight	6.6 lbs (2.9 kgs)
Dimensions (W/D/H)	10.6 (D) x 3.3 (H) inches (27.7 x 8.5 x 26.9 cms)
Remote Control	Remote Control
Power Supply	AC Input 100-240V, 50/60 Hz
Power Consumption	320 Watts
Operation Temperature	5°C ~ 40°C / 41°F ~ 104°F
Noise Level (Typical)	30 dB in Normal Operation
Uniformity	90%
Audio/Video Inputs	DB Connector HDMI (Video Connector (Component, HDTV)) Mini DIN Connector (S-Video) RCA Composite Connector (Video) Audio Mini Jack (DVI) Audio Mini Jack (S-Video/Video) Audio Mini Jack (15-PIN D-Sub)
Audio/Video Output	Audio Mini Jack
Communications	RS-232, +12V Relay (Screen Trigger)
Warranty	Three (3) years Limited Warranty Parts and Labor; 90 Days on Lamps
Standard Accessories	Lens Cover, Connector Cover, AC Power Cord, 15-Pin D-Sub to HDTV Component Cable, S/V to VGA cable, 12-Pin DIN Signal Cable, S-Video Signal Cable, Composite Video Cable Mini Phone Jack to Stereo RCA Audio Cable, RS-232 Cable, Wireless Remote Control, AA Size Batteries x 2, Soft Transit Carrying Case, User Manual (Print and CD) + Quick Start Card, Warranty card
Optional Accessories	Ceiling Mount Kit w/ Mid Cable, 30cm DVI Signal (DVI to DVI Cable (LONG Optional short throw lenses (.55:1, .70:1) and long throw lenses (1.2:1) are available through Optoma (www.optomausa.com))

Available From:

Optoma www.optomausa.com

©2007 Optoma Technology Inc. Specifications are subject to change without notice. All brands or product names are trademarks or registered trademarks of their respective companies. DLP® and BrilliantColor™ are registered trademarks of Texas Instruments Inc.

Optoma

Home Theater Projectors