

# HITACHI

Inspire the Next

# CP-S370W



- 2,200 ANSI lumens
- Native SVGA resolution
- 7 lbs
- 2 RGB inputs and RGB output
- Vertical keystone correction
- HDTV theater ready
- FCC class B
- Multiple video inputs (composite component and S-video)
- Reverse image function for ceiling mount
- Whisper mode 34dB
- 16:9 mode
- Manual zoom/manual focus
- Color temperature and gamma correction
- Digital zoom and image freeze function
- Comes with carry case
- Kensington security slot

## SPECIFICATIONS

<b>Model name</b>	<b>CP-S370W</b>		
Liquid crystal panel structure	0.9" polysilicon active-matrix TFT x 3		
Number of pixels	480,000 pixels (H 800 x V 600)		
Resolution	800 x 600 color pixels		
Colors	16.7 million colors		
Aspect ratio	Native 4:3/16:9 compatible		
Lens	Manual zoom 1:1.3 (F1.74 - 2.08)		
Throw ratio (distance:width)	1.94 ~ 2.57 : 1		
Lamp	200W UHB		
Expected lamp life	2,000 hours		
Brightness	2,200 ANSI lumens (1,760 ANSI lumens in whisper mode)		
Contrast ratio	350 : 1		
Speakers	1W x 2		
Power supply	AC100-120V/AC220-240V 50/60Hz		
Power consumption	310W		
Operating temperature	0° ~ 35°C (32° ~ 95° F)		
Input signals	RGB	VGA, SVGA, XGA/SXGA (COMPRESSED), MAC13", MAC16"	
	Composite video	NTSC, NTSC4.43, PAL, PAL-M, PAL-N, PAL 60, SECAM, S-video	
	Component video	480i, 575i, 480p, 1,080i, 720p	
Acoustic noise level	40dB (34dB in whisper mode)		
H sync	15kHz ~ 80kHz		
V sync	50Hz ~ 120Hz		
Vertical keystone correction	Digital keystone +/- 15°		
Horizontal keystone correction	-		
Approvals	UL, C-UL, FCC Class-B, CE, TUV		
Input/Output terminals	RGB input	Analog RGB	15-pin D-sub connector x 2
		Audio	Stereo mini jack x 2
	Audio output	Analog RGB	Stereo mini jack x 1
	Video input	S-video	Mini DIN 4-pin connector x 1
		Composite video	RCA jack x 1
	Component video	RCA jack x 3	
	Audio	RCA jack x 2 (L/R)	
	Control terminals		15-pin D-sub connector x 1
	Compatible controls		USB connector (USB mouse) x 1
			PS/2, ADB Serial
			RS-232C (Serial)
Chassis	Dimensions	11.7" x 3.0" x 9" (W x H x D)	
	Weight	7 lbs.	
	Supplied accessories	Card type wireless remote, PS/2 mouse cable, batteries (AA), power cord (U.S., UK, Euro), RCA component cable, RGB cable, multiple language operator/safety manual, handle strip and carrying case.	
Replacement parts	Lamp	CPX370 LAMP (Part #: DT00431)	
	Remote control	Card type remote (Part #: HL01444)	



Screen Size 4.3		Throw distance	
Diagonal*	Width*	Min*	Max*
40	32	62	82
60	48	94	123
80	64	127	164
100	80	160	205
120	96	192	246
150	120	241	308
200	160	323	411

Throw ratio: 1.94 ~ 2.57:1 (distance:width)

\*: Measured in inches

### CP-S370 Dimensions (incl.protruding part)

