



- 1,700 ANSI lumens
- Native SVGA resolution
- 6 lbs
- 2 RGB inputs and RGB output
- Component/composite/S-video inputs
- HDTV theater ready
- FCC Class B
- 16:9 mode
- Vertical & horizontal keystone correction
- "My screen" (user programmable start-up)
- Reverse image function for ceiling mount
- Wireless remote controller with laser pointer
- Color correction
- Whisper mode 34dB
- Comes with carry case
- Digital zoom (x4)
- Freeze function
- Manual zoom & manual focus
- Kensington security slot
- Wide-angle lens

SPECIFICATIONS

Model name		CP-S317W
Liquid crystal panel structure		0.7" polysilicon active-matrix TFT x 3
Number of pixels		480,000 pixels
Resolution		800 x 600 color pixels
Colors		16.7 million colors
Aspect ratio		Native 4:3/16:9 compatible
Lens		F1.7 - 1.9 manual zoom 1:1.2 manual focus
Throw ratio (distance:width)		1.47 ~ 1.79 : 1
Lamp		150W UHB (130W in whisper mode)
Brightness		1,700 ANSI lumens (1,360 ANSI lumens in whisper mode)
Expected lamp life		2,000 hours
Contrast ratio		400 : 1
Speakers		1W x 1
Power supply		AC100-120V/AC220-240V 50/60Hz
Power consumption		240W
Operating temperature		32°F ~ 95°F
Input signals	RGB	VGA, SVGA, XGA/SXGA/UXGA (COMPRESSED), MAC13", MAC16"
	Composite video	NTSC, NTSC4.43, PAL, SECAM, PAL-M, PAL-N, PAL60
	Component video	480i, 575i, 480p, 1,080i, 720p
Acoustic noise level		39dB (34dB in whisper mode)
H sync		15kHz ~ 91kHz
V sync		50Hz ~ 120Hz
Vertical keystone correction		Digital keystone +/- 15°
Horizontal keystone correction		Digital keystone +/- 5°
Approvals		UL, C-UL, FCC Class B
Input/Output terminals	RGB input	Analog RGB
	RGB output	RGB
	Video input	S-video
		Composite video
		Component video
	Audio	RCA jack x 2 (L/R)
Chassis	Control terminals	15-pin D-sub connector x 1
		USB connector (USB mouse) x 1
	Compatible controls	PS/2, ADB serial, RS-232C (serial)
	Dimensions	11.6" x 3.0" x 9.1" (W x H x D)
	Weight	6 lbs.
Replacement parts	Supplied accessories	Wireless remote control with laser pointer, batteries (AA), RGB cables, RCA video/audio cable, power cord (US, UK, Euro), operator/safety manual, carrying case
	Lamp	CPS317 LAMP (Part #: DT00511)
	Wireless remote	Wireless remote (Part #: HL01891)



Screen Size 4.3		Throw distance	
Diagonal*	Width*	Min*	Max*
40	32	47	55
60	48	71	87
80	64	95	114
100	80	118	142
120	96	142	173
150	120	181	217
200	160	240	287

Throw ratio: 1.47 ~ 1.79:1 (distance:width)

*: Measured in inches

CP-S317/CP-X327 Dimensions (incl.protruding part)

