


L713V

LUXEON L713V Digital LCD Multimedia Projector

>>

L713V



- LCD Projection technology
- Impressive brightness at 1300 ANSI lumens
- Native SVGA (800x600) performance, XGA compatibility
- Long lamp life up to 2000 hours
- Ultra-Portable at 7.2lbs.
- Distortion-free, 15' degree digital keystone correction
- 3 years standard warranty (Extended warranty available)


L713V



The LUXEON L713V, SVGA multi-media projector offers the best value with its light weight 7.2lbs in ultra portable class. With 1300 Lumens in brightness and maximum resolution at 1024x768 XGA, it delivers unbelievable image quality. Remote control with mouse through USB port as well as digital key stone correction make demanding user satisfied with both its performance and value.



Input/Output Terminals



Adjustable Zoom and Focus Ring



1-866-4-LUXEON

WWW.LUXEONUSA.COM

LUXEON is a trademark of LUXEON USA Corp. All other trademarks are used with permission or are for identification purpose only and are property of their respective companies.
©2002 LUXEON USA Corp. All rights reserved.



Laser Type: Class II
Wavelength: 645nm
Output: 1mW

SPECIFICATIONS

Display Technology	Three 0.9" Poly-Silicon LCD	
Number of Pixels	1,440,000; 800 x 600 x 3	
Resolution	SVGA 800 x 600 (native), XGA 1024 X 768 (compressed)	
Color Reproduction	16.7 million True Color (24 bit)	
Contrast Ratio	250:1 (full on/off)	
Brightness	1300 ANSI Lumens (typical)	
Lamp (Life)	130W SHL Ultra Compact (2000 hours)	
Lens	Manual zoom (1:1.3) and manual focus	
Screen Size (diagonal)	28.6 in. ~ 252.4 in. (0.73m ~ 6.41m)	
Projection Distance	4.9 ft. ~ 32.8 ft. (1.5m ~ 10.0m)	
Digital Keystone Correction	+/- 15 degree	
Aspect Ratio	4:3 and 16:9	
RGB Input Signal	Signal	0.7Vpp/75 Ohms
	Sync.	Separate and composite TTL Level
	Horizontal Frequency	30 - 70KHz
Compatibility	Vertical Frequency	56-85 Hz
	RGB Analog	VESA "1024x768 @ 85 Hz VESA " 800x600 @ 85 Hz VESA "640x480 @ 85Hz SVGA, VGA, Macintosh, Power Mac
	Video	NTSC/NTSC 4.43, PAL B/D/G/H/I/G/L/N/M, SECAM B/D/G/H/K/L, RGBHV (480i, 480p, 720p)
Input/Output Terminals	RGB in	D-sub HD 15-pin x1
	RGB out	D-sub HD 15-pin x1
	S-Video in	Mini DIN 4-pin x1
	Video (Composite) in	RCA jack x1
	Audio in	1/8 Stereo mini jack x2
	USB out	Type B receptacle x1
OSD Controls	Contrast, Brightness, Keystone, Volume (Audio), Horizontal Position, Vertical Position, Tracking, Frequency, Color, Tint, Video AGC (Automatic Gain Control), Digital Zoom, Display Mode, Projection Mode (Front, Rear, Ceiling, Rear Ceiling), OSD Language (English, Chinese, French, German, Italian, Spanish, Portuguese), OSD Position, Auto Power Off Timeout, Auto Image On/Off, Factory Recall, Status, Color Manager	
Remote Control Features	Wireless remote with mouse function, power, digital zoom, keystone, source select, auto image, volume, mute, blank, freeze and full OSD control	
Sound Output	3W mono	
Installation Options	Front, Front Ceiling, rear, rear ceiling	
Security Lock	Kensington MicroSaver Security System	
Dimension (w x h x d)	12.8 in x 3.6 in. x 9.8 in. (325mm x 92mm x250mm)	
Power Supply	Input: 100~240V AC, 60/50Hz, universal, PFC included	
Power Consumption	On: < 250W; Standby: <20W	
Audio Noise Level	<36 dB (normal room condition)	
Safety & Regulatory Compliance	FCC-A, UL, C-UL, CE, TUV	
Environmental Conditions	Operating Temperature	32°F to 95°F (0°C to 35°C)
	Operating Humidity	10 to 95% (no condensation)
Supplied Accessories	Remote Control w/2AA batteries, soft carrying case, lens cap, power cord, analog RGB 15-pin mini D-sub cable, S-video cable, composite video cable, stereo mini-jack cable, RCA audio/stereo mini-jack cable, USB cable, Mac adapter	
Optional Accessories	Replacement Lamp unit, ceiling mount kit, hard carrying/shipping case	
Warranty	Standard 3 year limited warranty, first year replacement, 90-day lamp warranty, extended warranty available	

*Specification subject to change without prior notice.

