

Simple, versatile presentation support

Advanced OHP features allow the presenter to integrate a diverse array of documents and solid objects into the presentation. Simple control of these features allows for the presenter to efficiently add flair and professionalism to any presentation.



■ Document rotation and zoom function

A4 size

rotation

Allows you to rotate documents vertically, horizontally or a full 180 degrees.

zoom

Provides up to 6.25X zoom.

■ Keystone correction

Vertical and horizontal image correction (horizontal $\pm 10^\circ$, vertical $\pm 15^\circ$) make it possible to project images from an indirect angle.

■ Stores up to eight documents in memory

The MP-50E stores up to eight documents in its built-in memory.

MP-50E Specifications

Panel Type	1.0-inch TFT LCD x 3 pieces, aspect ratio 4:3	
Resolution	XGA (1,024 x 768)	
PC Compatibility	VGA to UXGA	
Projection Lens	Manual zoom (1 – 1.25 times)	
Light Source	260W super-high-pressure mercury lamp	
Screen Size	Min. 32 inches – Max. 300 inches (projection distance 1.4m – 13.9m)	
Color Reproducibility	Full color (16.77 million colors)	
Light Output/Center to Edge	3,000 ANSI lumens	
Sound Output	1W x 1W stereo speakers	
Compatible Scanning Frequency	Horizontal	21 – 80KHz
	Vertical	50 – 85Hz
Keystone Correction	Adjustable horizontal $\pm 10^\circ$, vertical $\pm 15^\circ$	
Analog RGB Input/Output	Input Terminal (Image)	Mini D-sub 15 pins x 2
	Output Terminal (Image)	Mini D-sub 15 pins x 1
	Input Terminal (Sound)	Stereo mini-jack x 2
	Output Terminal (Sound)	Stereo mini-jack x 1
Video Input/Output	Input Signal Type	NTSC, PAL, SECAM
	Input Terminal (Image)	RCA pin x 1, S-Video terminal (Mini DIN 4 pins x 1)
	Input Terminal (Sound)	RCA pin (L/R) x 1
Operational Environment	Temperature 0 – 35°C, humidity 20 – 80% (no condensation)	
Input Power	100-120 VAC/220-240 VAC	
Power Consumption	390W	
External Dimensions	400(W) x 315(D) x 145(H)mm excluding projected section	
Weight	7.3kg (approx. 16.1 lbs.)	
Standard Accessories	Power cable (3m), Personal computer interface cable, (2m, Mini D-sub 15 pins), Remote controller, Lens cover, Instruction manual, Batteries (AA x 2),	
Document Camera	1/2-inch color CCD 2,000,000 pixels	
	Zoom	6.25X zoom
	Resolution	760 TV lines (horizontal resolution)

Note: Design and specifications are subject to change without notice.



NIPPON AVIONICS CO.,LTD.

Overseas Department

20-1, Nishi-Shinbashi 3-chome, Minato-ku Tokyo 105-0003, Japan

Phone: 81-3-5401-7386 Fax: 81-3-5401-7344

URL <http://www.avio.co.jp/>

Printed in Japan

420-175-E 0303-150-KLR1