



- 2,200 ANSI lumens
- Native XGA resolution
- Contrast ratio 400:1
- 2 RGB inputs and RGB output
- Component/composite/S-video inputs
- Manual zoom/manual focus
- HDTV theater ready
- 7 lbs
- FCC class B
- Whisper mode 34dB
- Digital keystone correction
- Remote control with laser pointer

#### Forget-Me-Not Features

- 16:9 mode
- Kensington security slot
- Reverse image function for ceiling mount
- Color temperature and gamma correction
- Digital zoom (x4) and image freeze function

## SPECIFICATIONS

<b>Model name</b>	CP-X385W/WT			
Liquid crystal panel structure	0.9" polysilicon active-matrix TFT x 3			
Number of pixels	786,432 pixels (H1,024 x V768)			
Resolution	1,024 x 768 color pixels			
Colors	16.7 million colors			
Aspect ratio	Native 4:3/16:9 compatible			
Lens	Manual zoom 1:1.3 (F1.7 - 2.1)			
Throw ratio (distance:width)	2.0 ~ 2.57 : 1			
Lamp	200W UHB			
Expected lamp life	Approx. 2,000 hours			
Brightness	2,200 ANSI lumens (1,760 ANSI lumens in whisper mode)			
Contrast ratio	400 : 1			
Speakers	1W x 2			
Power supply	AC100-120V/AC220-240V 50/60Hz			
Power consumption	310W			
Operating temperature	0° ~ 35°C (32° ~ 95° F)			
Input signals	RGB	VGA, SVGA, XGA, SXGA/LUXGA (COMPRESSED), MAC13", MAC16"		
	Composite video	NTSC, NTSC4.43, PAL, PAL-M, PAL-N, PAL 60, SECAM		
	Component video	480i, 575i, 480p, 1,080i, 720p		
Acoustic noise level	40dB (34dB in whisper mode)			
H sync	15kHz ~ 91kHz			
V sync	50Hz ~ 120Hz			
Vertical keystone correction	Digital keystone +/- 15°			
Horizontal keystone correction	Digital keystone +/- 5°			
Approvals	UL, C-UL, FCC Class-B, CE, TUV			
Input/Output terminals	RGB input	Analog RGB	15-pin D-sub connector x 2	
		Audio	Stereo mini jack x 2	
	Audio output	Analog RGB	3.5 stereo mini jack	
	Video input	S-video		Mini DIN 4-pin connector x 1
		Composite video		RCA jack x 1
		Component video		RCA jack x 3
Audio			RCA jack x 2 (L/R)	
Control terminals	15-pin D-sub connector x 1			
Compatible controls	USB connector (USB mouse) x 1			
	PS/2, ADB, Serial RS-232C (Serial)			
Chassis	Dimensions	11.7" x 3.0" x 8.98" (W x H x D)		
	Weight	7 lbs.		
	Supplied accessories	Remote control with laser pointer, batteries (AA), PS/2 mouse cable, power cord, RGB cable, RCA video/audio cable, multiple language operator/safety manual, handle strip and soft case		
Replacement parts	Lamp	CPX380LAMP (Part #: DT00431)		
	Remote control	(Part #: HL01794)		



Screen Size 4.3		Throw distance	
Diagonal*	Width*	Min*	Max*
40	32	62	82
60	48	94	123
80	64	127	164
100	80	160	205
120	96	192	246
150	120	241	308
200	160	323	411

Throw ratio: 2.0 ~ 2.57:1 (distance:width)

\*: Measured in inches

**CP-X385 Dimensions**  
(incl.protruding part)

