

SLM R10 Executive



PRODUCT SPECIFICATIONS**SLM R10 EXECUTIVE**

Lichtuitvoer	10000 ANSI lumens
Digital MicroMirror Device™	three S-XGA DMDs (1280 x 1024)
Helderheidsuniformiteit	Brightness uniformity: >90% for the total screen
Resolutie	1280 x 1024 (native) 1600 x 1200 (max)
Lamp	2.2 kW Xenon illumination system Typical lifetime: 500 hours Max. lifetime: 1000 hours
Contrastverhouding	> 800:1 (High Contrast Mode: >1600 : 1)
Schermbreedte (min./max.)	5m -15m / 6 ft -50 ft
Compatibiliteit	■ All video sources in Composite, S-VHS, Component or RGB formats or serial digital format ■ All currently proposed HDTV, extended and improved television standards ■ Most Macintosh computers ■ Computers and electronic workstations with a resolution up to 1600 x 1200 pixels ■ Two digital input slots allow direct digital interfacing with current and future digital inputs
Lenzen	Fixed focal length lenses are available with a throw ratio of 0.8:1 (very short throw ratio, specially designed for rear screen on-axis projection) or 1.2:1 (long throw). Motorized Zoom Lenses with a throw distance of 1.6-2.0,2.0-2.8,2.8-5.0,5.0-8.0 times the screen width
Ingangen	2 x multifunctional 5-Cables input (high bandwidth) for the connection of: -RGB analog signals with standard sync (BNC) or tri-level sync, sync on green or separate sync -Standard video signals -S-VHS signals 2 x DVI in + 1 x DVI out SDI loop-through (Serial Digital Input) Video input
Optioneel	SDI loop-through (Serial Digital Input) HD-SDI loop-through (High Definition Serial Digital Input)
Communicatie	1 x D9 connector for RS232 or RS422 loop-through 1 x D9 connector for peripherals 1 x 3-pin male XLR connector for wired remote network connection
Geluidsniveau	< 56 dBA
Energieverbruik	2750 W
Wisselstroom	220 V (tolerance 200 V -240 V)
Veiligheidsvoorschriften	Compliant with UL1950 and IEC950
Netwerkverbinding	Optional
Kenmerken	· Picture-in-picture · Seamless source switching with effects
Afmetingen (B x L x H)	529 x 795 x 429 mm (20.8 x 31.3 x 16.9 inch)
Lensverschuiving	TLD Lenses Motorized V shift: -20% +100% Motorized H shift: max. 65% (L+R) For specific details per lens type: see lens product pages
Naadloos schakelen	Standard
ScenergiX	Standard
Verzegelde DLP™-kern	Not available
Gewicht	45 kg (99lbs)

Last updated: 24 Feb 2021Technical specifications are subject to change without prior notice. Please check www.barco.com for the latest information.