



- 1,100 ANSI lumens
- Native SVGA resolution
- 5 lbs
- RGB/component/composite/S-video inputs
- HDTV theater ready
- Short throw lens
- Manual zoom & manual focus
- Color temperature and gamma correction
- Reverse image function for ceiling mount
- Kensington security slot
- Vertical keystone correction
- Slide lens cover
- 16:9 mode
- Digital zoom & freeze function
- Comes with carry case
- Whisper mode 32dB

SPECIFICATIONS

Model name		CP-S225WT
Liquid crystal panel structure		0.7" polysilicon active-matrix TFT x 3
Number of pixels		480, 000 pixels (H800 x V600)
Resolution		800 x 600 color pixels
Colors		16.7 million colors
Aspect ratio		Native 4:3/16:9 compatible
Lens		Manual zoom 1:1.2 (F2.0 - 2.3)
Throw ratio (distance:width)		1.16 ~ 1.46 : 1
Lamp		150W UHB
Brightness		1,100 ANSI lumens
Expected lamp life		2,000 hours
Contrast ratio		300 : 1
Speakers		1W x 1
Power supply		AC90-132V/AC220-240V 50/60Hz
Power consumption		240W
Operating temperature		0 ~ 35°C (32° ~ 95°F)
Input signals	RGB	VGA, SVGA, XGA/SXGA (COMPRESSED), MAC13", MAC16"
	Composite video	NTSC, NTSC4.43, PAL, PAL-M, PAL-N, SECAM, PAL60, S-video
	Component video	480i, 625i, 480p, 1,080i, 720p
Acoustic noise level		36dB (32dB in whisper mode)
H sync		15kHz ~ 78kHz
V sync		50Hz ~ 120Hz
Vertical keystone correction		Digital keystone +/- 10°
Horizontal keystone correction		-
Approvals		UL, C-UL, FCC Class B, CE, TUV
Input/Output terminals	RGB input	D-sub 15-pin connector x 1
	Audio	Stereo mini jack x 1
	Video input	Mini DIN 4-pin input connector x 1
	S-video Composite video Component video Audio	RCA jack x 1 RCA jack x 3 RCA jack x 2 (L/R)
	Control terminals	D-sub 15-pin connector x 1
	Compatible controls	RS-232C (Serial) -
Chassis	Dimensions	10.9" x 2.4" x 8.3" (W x H x D)
	Weight	5 lbs.
	Supplied accessories	Card type remote control, batteries (AA), power cord (U.S., UK, Euro), RGB cable, RCA component cable, multiple language operator/safety manual, handle strip and carrying case.
Replacement parts	Lamp	CPS225 LAMP (Part #: DT00401)
	Remote control	Card type remote (Part #: HL01444) Mouse kit (Part #: RMU101) Optional



Screen Size 4.3		Throw distance	
Diagonal*	Width*	Min*	Max*
40	32	37	46
60	48	57	69
80	64	77	93
100	80	98	116
120	96	116	139
150	120	145	174
200	160	194	233

Throw ratio: 1.16 ~ 1.46:1 (distance:width)

*: Measured in inches

CP-S225/CP-X275 Dimensions (incl.protruding part)

