

28 dB

3.0 kg

XGA

2000 : 1

2600 ANSI lumen



projectiondesign evo

The evo has been designed specifically for business users, and offers the best possible performance for the meeting room or the distinctive board room. DLP™ (Digital Light Processing) technology yields superb performance with high brightness and contrast, and true colours. Combined with small size and an extreme attention to lowering operating noise, the evo is the ultimate meeting room projector, with qualities unheard of in its class.

designed for ease of use

High attention to detail and focusing on ease of use has resulted in a very distinct projector that is as attractive in design as it is in performance. Evolved from an internationally recognized and award winning design, the evo is finished in an eye catching Ice Blue magnesium cabinet. Ensuring the best possible durability and longevity, and lowering the total cost of ownership. Using the evo simply means turn it on and connect. Everything else is automatic. It cannot be easier.

investment for the future

The projectiondesign evo connects to everything in the office with its' extensive connectivity, and makes a long lasting investment that will never go out of style. It will be an integral part of the office environment for many years, and will never fail to perform in front of your audience.

The choice of a lifetime. projectiondesign evo.



**Award for
Design Excellence**
Awarded by the
Norwegian Design Council



**Designed and
manufactured
in Norway**



28 dB

3.0 kg

XGA

2000 : 1

2600 ANSI lumen



diagonal image size	distance	
	cm / inches	min
152 / 60	268	340
203 / 80	358	455
254 / 100	447	569
304 / 120	536	683

technical specifications

projector **evo**
XGA DLP™ digital projector (101-0028-06)

resolution 1 024 x 768

brightness 2 600 ANSI lumens

contrast ratio 2 000 : 1 (on / off)

computer video pc / mac, 640 x 480 - 1400 x 1050
1080i, 720p, pal, ntsc, secam

projection lens 1.3x manual zoom lens

throw ratio 2.20 - 2.80 : 1 distance : width

image size 0.7 - 5.7 m (2.5 - 18 ft) diagonal

lens offset +9 % of image height

focusing distance 1.5 - 10 m (5 - 33 ft)

lamp 250 w uhp™, 2 000 hours (typical)

computer inputs 1x dvi (digital rgb)
2x vga (analog rgb)

video inputs 3x rca (component)
1x 4-pin mini din (s-video)
1x rca composite video

video out 1x vga (analog rgb)

audio line out 1x 3.5 mm stereo mini jack

speakers 2x 1 w stereo

supplied cables vga cable
dvi-d cable
usb cable
a/v cable

supplied accessories ceiling mount cable cover
infrared remote control
soft carrying case

operating noise level 28 dB (typical)

dimensions 244 x 278 x 88 mm (9.6 x 10.9 x 3.5 in) dwh

weight 3.0 kg / 6.5 lbs

power requirements 100 - 240 vac, 50/60 Hz, +/- 10 %
350 w power consumption

conformances CE, CSA "C/US", FCC Class A

warranty 2 years, 90 days or 500 hours on lamp



601-0031-00 All brands and trade names are the property of their respective owners. Specifications subject to change without prior notice. All values are typical and may vary. Patent pending on lamp and cooling system.