

ASK Proxima M1 (DP1200x) Projector

Technical and Functional Specifications

Compatibility

Computer	Analog PC, Macintosh®, XGA. Intelligent resizing for SXGA, SVGA, VGA
Video	Full NTSC, PAL, SECAM through S-video input with adaptor, S-video EDTV, HDTV (1080i, 720p, 576p, 480p) through M1 input
H-sync range	15 - 100 kHz
V-sync range	43.5 - 130 Hz

Inputs & Outputs

M1D	Computer
3.5mm	Audio in
S-Video	Video
Audible Noise	36 dB

Display

Type	DLP™ by Texas Instruments®: 0.7" XGA 12° DMD DDR
Resolution	XGA / 1024 x 768
Contrast Ratio	2000:1 full on/full off
Aspect Ratio	4:3, 16:9
Focusing Distance	5' / 1.5 m to 32.8' / 10 m (Note that image remains in focus at longer distances. However, the brightness level drops as the throw distance increases.)
Keystone Correction	Digital, up to +/- 7.5° for both data and video
Lamp	120-Watt UHP (2,000 hours life)
Brightness	1,000 ANSI lumens
Modes	Front and rear
Projection Lens (standard zoom)	F/2.8-3.1, 25.8-30mm focal length
Projection Ratio	1.8:1 - 2.1:1 (distance/width)
Image offset	112% (+/-5%)
Zoom Ratio	1.16:1

General

Conformances	FCC A (US/Canada), S-JQA (Japan), PSE (Japan), CCC (China), IRAM (Argentina), GOST (Russia), UL & cUL (US/Canada), TUV GS (Germany), NOM (Mexico), MIC (Korea), C-Tick (Australia)
Menu Languages	English, Spanish, French, German, Japanese, Korean, Portuguese, Italian, Norwegian, Russian, Chinese Simple, Chinese Traditional
Operating Temperature	5° - 40° C at sea level (0 - 10,000') ; 41° - 104° F
Power Supply	100V - 240V at 50 - 60 Hz
Power Consumption	150 watts
Dimensions	2.05 in (H) x 3.69 in (L) x 9.75 in (W) 5.21 cm (H) x 9.37 cm (L) x 24.77 cm (W)
Weight	1.98 lbs/.9 kg
Warranty	2 years part and labor, 1 year accessories
Lamp Warranty	90 days or 500 hours, whichever comes first