

Vision Model 40

D L P P R O J E C T O R

- 1280 x 720 Widescreen Native 16:9 Resolution HD-2+ DMD™ Display Device
- Integrated Video Processing With 3:2 Pulldown
- 950 ANSI Lumens/1600:1 Contrast Ratio
- Multiple Aspect Ratios with IntelliWide™ Mode
- HDTV Ready
- DVI-I Input with HDCP
- 9-Point White Balance System for Excellent Gray Scale Tracking
- Discrete IR and RS-232 Control
- "Cat's Eye" Optical System for Enhanced Contrast and Black Levels
- Two Lens Options with Variable Throw Distances for Versatile Installation Convenience



VISION
SERIES

Vidikron
A RUNCO INTERNATIONAL COMPANY

Vision Model 40

DLP PROJECTOR

The world-class Vidikron Vision™ Model 40 represents the pinnacle in high performance video projection using the latest HD-2+, 16:9 widescreen DLP™ technology. The Model 40's advanced engineering innovations, features and picture quality qualify it as the centerpiece of state-of-the-art home theater installations.

The Model 40's 950 ANSI lumens of light output and 1600:1 contrast ratio make it a superb choice for home theaters with recommended screen requirements all the way up to 96 inches wide. The internal video processing with 3:2 film detection circuitry and full HDTV compatibility (with outboard tuner/decoder or satellite receiver) make the Model 40 capable of projecting any video source with stunning results.

The Model 40's multiple aspect ratio control includes Vidikron's IntelliWide™ mode, offering the ability to view standard video formats in widescreen without loss of image quality. Advanced digital keystone correction and discrete IR or RS-232 control facilitate custom installations seamlessly, while discrete source and aspect ratio selection accommodate automation control systems.

The Vision Model 40 offers a variable throw distance of 1.38:1 to 1.63:1, while an optional lens provides a longer variable throw distance of 1.83:1 to 2.40:1. Both lenses feature a 'cat's eye' optical system that enhances contrast and optimizes black level performance. In addition, a unique 9-point white balance system accounts for superb gray scale tracking, enabling the Model 40 to offer stellar images with crisp detail and deeply saturated colors.

The high performance Model 40 offers all of the quality expected of a Vidikron product, packaged in an aesthetically pleasing chassis with a very modest footprint.

Specifications for Vision Model 40:

Projection Type:	Digital Light Processing™ (DLP™), Single HD-2+ DMD™ Chip	Estimated Lamp Life:	2000 hours @ 6500° Kelvin
Native Resolution:	1280 x 720 (16:9)	Inputs:	(1) Composite Video, (1) S-video, (1) RGB/Component (via BNC), (1) RCA Component Video, (1) DVI-I w/ HDCP, (1) RS-232
Aspect Ratio:	4:3, Letterbox, 16:9 Anamorphic, IntelliWide™	Memories:	21 memories
Video Standards:	NTSC, PAL	12V Output:	Max .250 Amp, active when the projector is on
DTV Compatibility:	480p, 720p, 1080i	Power Requirements:	100 – 240V AC, 320W
Scan Frequency:	Horizontal: 15 – 80KHz Vertical: 50 – 100Hz	Operating Environment:	40° – 95° F, (5° – 35° C)
Picture Size:	Recommended Width: 72 – 96 in. Maximum Width: 200 in. (16:9 screen)	Dimensions (w/o feet):	Width: 15 3/4 in. (400.00 mm) Depth: 11 in. (280 mm) Height: 4 7/8 in. (125.41 mm), with feet 5 1/4 in. (131.5 mm) Weight: 17.5 lbs. (7.8 kg) (includes lens)
Throw Distance:	Standard Zoom: 1.38 – 1.63	Regulatory Approvals:	UL, FCC Class B, CE, C-Tick
(Factor x Screen Width):	Optional Zoom: 1.83 – 2.40	Limited Warranty:	Projector: (2) Two year parts and labor from the date of delivery to the end user. Lamp Warranty: (6) six months or 1000 hours.
Light output:	<u>CSMS* Specifications:</u> Home Theater Calibration: 480 ANSI Lumens; 17.9 Foot-Lamberts (fL); 950 ANSI Lumens		
Contrast Ratio:	CSMS* Contrast Ratio: 148:1; 1600:1 ANSI		
Lamp:	210 W		

All specifications subject to change without notice. Optional ceiling bracket available.
* Cinema Standards Measurement System. See www.vidikron.com for more details.

Vidikron
2900 Faber Street, Union City, CA 94587
510-324-5900 Fax 510-324-5905
www.vidikron.com

© 2004 Vidikron, a Runco International Company. All rights reserved. Vision is a trademark of Vidikron.
Digital Light Processing, DLP and DMD are trademarks of Texas Instruments.

