

# Dell Micro-portable Projectors 2200MP, 3300MP and 4100MP



## Dell | Projectors

**Great things come in small packages,  
and they keep getting better.**

Whether for business, education or personal use, Dell™ projectors offer great performance at an affordable price. They are packed with high-end technology and include the extras as standard, so you have everything you need to get up and running, right out of the box – custom-fitted hard-shell carrying case, remote control and data/video cables.

### Deliver bright, clear images

Dell projectors use advanced DLP™ (Digital Light Processing™) technology from Texas Instruments to achieve great picture quality in a small and light form factor. They combine consistent brightness and high contrast ratios to produce clear, sharp video and text images. Built-in digital keystone correction and zoom help you adjust the projector for optimal viewing for almost any situation. Dell offers a choice of native resolutions so you can select the projector to match your requirements and budget.

### Outstanding ease of use

Dell Projectors are extremely easy to use. With support for a wide range of input video sources and television and video standards, you get great presentation flexibility. The projectors feature automatic synchronisation so the projector will detect the type of input and change its settings accordingly. This plug-and-play technology makes the projectors compatible with most computers, including Dell Latitude™ and Inspiron™ notebooks – just follow the simple Quick Set Up guide and you're ready to go.

### Excellent mobility features

Dell projectors are small and light – they weigh less and are more portable than many notebook computers. They're built for durability, with a sturdy magnesium casing. The included carrying case makes travelling easy. With desktop or ceiling mount capability and front and rear projection, you can use these projectors just about anywhere.

### Perfect for work and entertainment

Dell projectors have enough performance features to be your workhorse during the week, but at the weekend these units can take home entertainment to the next level as an excellent complement to your home theatre system for watching movies, sporting events, viewing photos or even playing video games.

### Great value is a given – it's from Dell!

Like all Dell products, Dell projectors maximise price-for-performance value. They are affordably priced and backed by Dell service and support. Valuable extras, such as a carrying case and remote control, are included at no extra charge.



Dell 2200MP Projector



Dell 3300MP Projector



Dell 4100MP Projector

Presentations made easy. Easy as **DELL™**

Visit [www.euro.dell.com](http://www.euro.dell.com) for more information.



# Dell Micro-portable Projectors 2200MP, 3300MP and 4100MP



<b>Model Name</b>
<b>Projection Technology</b>
<b>Brightness</b>
<b>Native Resolution</b>
<b>Max. Sync Resolution</b>
<b>Contrast Ratio</b>
<b>Displayable Colours</b>
<b>Image Adjustment</b>
<b>Projection Lens</b>
<b>Zoom</b>
<b>Memory Card Reader</b>
<b>Keystone Correction</b>
<b>Projection Screen Size</b>
<b>Projection Distance</b>
<b>Video Compatibility</b>
<b>Horizontal Frequency</b>
<b>Vertical Frequency</b>
<b>Internal Loudspeaker</b>
<b>Bulb Type</b>
<b>Bulb Lifetime</b>
<b>Power Supply</b>
<b>Power Consumption</b>
<b>Power Saver Shutdown</b>
<b>I/O Connectors</b>
<b>Power</b>
<b>Computer Input</b>
<b>Monitor Loop-through</b>
<b>Video Input</b>
<b>Audio Input</b>
<b>Control Input/Output</b>
<b>Environmental</b>
<b>Operating Temperature</b>
<b>Operating Humidity</b>
<b>Storage Temperature</b>
<b>Storage Humidity</b>
<b>Flexible orientation</b>
<b>Included Accessories</b>
<b>Optional Accessories</b>
<b>Weight</b>
<b>Dimensions (h x w x d)</b>
<b>Warranty</b>

4100MP	3300MP	2200MP
Single chip DLP™ DDR technology	Single chip DLP DDR technology	Single chip DLP DDR technology
2200 ANSI Lumens (max) <sup>3</sup>	1500 ANSI Lumens (max) <sup>2</sup>	1200 ANSI Lumens (max) <sup>1</sup>
XGA (1024 X 768)	XGA (1024 x 768)	SVGA (800 x 600)
UXGA (1600 x 1200)	SXGA+ (1400 x 1050)	SXGA+ (1400 x 1050)
2000:1 (Full On/Full Off)	1700:1 (Full On/Full Off)	1700:1 (Full On/Full Off)
16.7 million	16.7 million	16.7 million
Zoom, focus and horizontal and auto vertical keystone controls	Zoom, focus and auto vertical keystone controls	Zoom, focus and keystone controls
F/2.43-2.66, f=28.0-33.6mm	F/2.43-2.65, f=28.04-33.59mm	F/2.4-2.7, f=19.7-23.6mm
1.2x manual zoom	1.2x manual zoom	1.2x manual zoom
Optional 6-in-1 reader	Optional 6-in-1 reader	None
±16° adjustment	±16° adjustment	±16° adjustment
24.4-292.5" (0.6-7.4m diagonal)	24.4-292.5" (0.6-7.4m diagonal)	28-337" (0.7-8.6m) diagonal
1.2m – 12m	1.2m – 12m	1.2m-12m
NTSC, NTSC 4.43, PAL, PAL-M, PAL-N, SECAM and HDTV (480i/P, 576i/P, 720P and 1080i) Composite Video and S-Video capability	NTSC, NTSC 4.43, PAL, PAL-M, PAL-N, SECAM, HDTV (480i/P, 576i/P, 720P and 1080i) Composite Video and S-Video capability	NTSC, NTSC 4.43, PAL, PAL-M, PAL-N, SECAM, HDTV (480i/P, 576i/P, 720P and 1080i) Composite Video and S-Video capability
15kHz-100kHz	15kHz-80kHz	15kHz-70kHz
43Hz-120Hz	50Hz-85Hz	43Hz-85Hz
Two 2-watt speakers	One 2-watt speaker	One 2-watt speaker
250-watt, user-replaceable UHP lamp	180-watt, user-replaceable P-VIP lamp	200-watt, user-replaceable P-VIP lamp
1500 hours (up to 3000 hours in Eco-mode)	3000 hours (up to 5000 hours in Eco-Mode)	2000 hours (up to 2500 hours in Eco-Mode)
Universal 90-240V AC 50-60 Hz	Universal 100-240V AC 50-60 Hz	Universal 100-240V AC, 50-60Hz
310W at full power	224W at normal operation	250W at normal operation
Yes	Yes	Yes
AC power input socket	AC power input socket	AC power input socket
One M1-DA for analogue/digital/HDTV; one D-sub 15-pin for analogue/HDTV input	One M1-DA for analogue/digital/HDTV	15-pin D-sub for analogue RGB/component, HDTV
One 15-pin D-sub	One 15-pin D-sub	One 15-pin D-sub
One composite video (RCA); one S-Video and one 3-pin component for HDTV	One composite video (RCA); one S-Video and one M1-DA for component HDTV	One composite video RCA and one S-Video
One 3.5mm phone jack for line audio input	One 3.5mm phone jack for line audio input	One 3.5mm phone jack for line audio input
One DC jack 12 volt @ 200mA output, relay control. One mini-DIN RS-232 input	One mini-DIN RS-232 input	None
5°C – 35°C (41°F to 95°F)	5°C – 35°C (41°F to 95°F)	5°C to 35°C
80% maximum	80% maximum	80% maximum
-20°C to 60°C (4°F to 140°F)	-20°C to 60°C (4°F to 140°F)	-20°C to 60°C
80% maximum	80% maximum	80% maximum
Desktop or ceiling mountable and rear or front projection	Desktop or ceiling mountable and rear or front projection	Desktop or ceiling mountable and rear or front projection
Carrying case, wireless remote with laser pointer, M1-DA to D-sub/USB cable, S-Video cable, RCA audio composite video cable, composite video cable, composite cable, miniphone jack, power cord, quick start guide and user manual	Carrying case, wireless remote with laser pointer, M1-DA to D-sub/USB cable, S-Video cable, RCA audio composite video cable, composite video cable, composite cable, miniphone jack, power cord, quick start guide and user manual	Carrying case, wireless remote control, VGA cable (D-sub to D-sub), component video, S-video cable, USB cable, composite video cable, RCA to audio, mini-pin, power cord, quick start guide and user manual
Ceiling mount kit, Replacement bulb	Ceiling mount kit, Replacement bulb	Ceiling mount kit, Replacement bulb
2.95kg	1.81kg	2.1kg
302 x 251 x 114mm	245 x 211 x 83.5mm	85mm x 266mm x 216mm
Two years (90 days on bulb)	Two years (90 days on bulb)	One year (90 days on bulb)

Pricing, specifications, availability and terms may change without notice. Dell's Terms and Conditions of Sales and Service apply and are available on request and at [www.euro.dell.com](http://www.euro.dell.com). DLP and Digital Light Processing are trademarks of Texas Instruments, Incorporated. Dell, the Dell logo, Latitude and Inspiron are trademarks of Dell Computer Corporation. 1. Based on ANSI/NAPM IT7.228-1997 tests of 73 units, September 2003, with average ANSI Lumens 1118. Bulb brightness degrades with usage. Dell recommends replacing your bulb after 2000 hours of usage. 2. Based on ANSI/NAPM IT7.228-1997 tests of 15 units, January 2004, with average ANSI Lumens 1523. Bulb brightness degrades with usage. Dell recommends replacing your bulb after 3000 hours of usage (up to 5000 hours in Eco-mode). 3. Based on ANSI/NAPM IT7.228-1997 tests of 35 units, November 2003, with average ANSI Lumens 2144. Bulb brightness degrades with usage. Dell recommends replacing your bulb after 1500 hours of usage. © 2004 Dell Computer Corporation. All rights reserved. Reproduction in any manner whatsoever without the express written permission of Dell Computer Corporation is strictly forbidden.

EU865/25March2004

Presentations made easy. Easy as 

Visit [www.euro.dell.com](http://www.euro.dell.com) for more information.