

U5

U5-SERIES

PLUS



VALUE. PERFORMANCE. CHOICE.

THE U5 SERIES IS EVERYTHING A PRESENTER NEEDS FROM A DIGITAL PROJECTOR. FEATURES LIKE A SHORT-FOCUS ZOOM LENS, HDTV COMPATIBILITY AND UP TO 3,000 LUMENS ARE AVAILABLE IN THIS COMPACT 4-POUND PACKAGE. LIKE ALL PLUS PROJECTORS, THE U5'S ARE EASY TO USE AND CONNECT TO VIRTUALLY ANY VIDEO SOURCE.

THE U5'S ARE IDEAL FOR PRESENTERS ON THE GO, BOARDROOM USE OR CLASSROOM USE. AND WITH PASSWORD-PROTECTED THEFT PREVENTION, YOU'LL HAVE PEACE-OF-MIND WHEREVER A PLUS PROJECTOR IS NEEDED.

Up to 3,000 ANSI lumens corner-to-corner brightness

Only 4 pounds

Eco-mode lets you increase lamp life by 30%

Digital zoom instantly targets and enlarges the fine print at the touch of a button

Connects to virtually any computer or video source

Models featuring short-focus zoom lenses allow for flexible big-screen presentations in cramped quarters

Anti-theft security

RS-232 Support

HDTV Compatible



PLUS Vision Corp.

9610 SW SUNSHINE CT.
SUITE 800
BEAVERTON, OR 97005
866-427-8855 • 503-748-8700
www.plus-america.com

U5

U5-SERIES

Remote for U5-111/112



PLUS

Remote for U5-132/232/332

Specifications	U5-111/U5-112	U5-132/U5-232/U5-332	
Resolution	SVGA, 800 x 600 pixels	XGA, 1024 x 768 pixels	
RGB Signal	SVGA (true)	XGA (true)	
	XGA (compressed)	SXGA (compressed)	
	VGA (expansion/true)	SVGA/VGA (expansion/true)	
Brightness	1600 Lumens	2000 Lumens	
Bright Mode		3000 Lumens (U5-232)	
Contrast Ratio	2000:1 (Full on/off)	2000:1 (Full on/off)	
Aspect Ratio	4:3, supports 16:9	4:3, supports 16:9	
Projection Lens	F=2.6, f=19 mm (U5-111)	F=2.6-2.9, f=18.4-22 mm (U5-132/232)	
	Manual Focus (U5-111)	1:1.2 Manual Zoom/Focus	
	F=2.6-2.9, f=20-24 mm (U5-112)	F2.4-2.6, f=26.5-31.8mm (U5-332)	
	1:1.2 Manual Zoom/Focus (U5-112)		
Digital Keystone Correction	20 degrees	20 degrees	
Digital Zoom	2x	2x	
Light Resource	280-watt lamp, 2,000 hrs.	280-watt lamp, 2,000 hrs.	
	3,000 hrs. in Eco-mode	3,000 hrs. in Eco-mode	
RS-232 Control		9-pin D-sub input terminal	
Color Palette	16.7 million colors	16.7 million colors	
Projection Positions	Front/rear, table/ceiling	Front/rear, table/ceiling	
Projection Distance	3.9-34.7 ft. / 1.2-10.6 m (U5-111)	3.9-26.2 ft / 1.2-8.0 m (U5-132/232)	
	3.9-36.4 ft. / 1.2-11.1 m (U5-112)	3.9-37.7 ft. / 1.2-11.5 m (U5-332)	
Image Size	34"-300" diagonal (U5-111)	38"-300" diagonal (U5-132/232)	
	28"-300" diagonal (U5-112)	27"-300" diagonal (U5-332)	
Video Signal	NTSC3.58, NTSC4.43, PAL, PAL-M,	NTSC3.58, NTSC4.43, PAL, PAL-M,	
	PAL-N, PAL60, SECAM,	PAL-N, PAL60, SECAM,	
	YCbCr (NTSC, PAL),	YCbCr (NTSC, PAL),	
	YPbPr (480p, 720p, 1080i)	YPbPr (480p, 720p, 1080i)	
	Built-in Line Doubler	Built-in Line Doubler	
Audio	Mono 0.8 watt	Mono 0.8 watt	
Dimensions Excluding Lens and Stand:		U5-132/232	U5-332
Height	2.3 in./60 mm	2.3 in./60 mm	-
Width	8.5 in./216 mm	8.5 in./216 mm	-
Length	9.5 in./240 mm	9.9 in./252 mm	10.2 in./260 mm
Weight	4.1 lb./1.9 kg	4.4 lb./2.0 kg	4.6 lb./2.1 kg



Presentation Screens

Choose from a variety of portable presentation screens from PLUS. They will save the day in any presentation environment.



Replacement Bulbs

PLUS offers a wide array of replacement bulbs so you can carry a spare anywhere.



Elmo HX-3000 Visualizer

Allowing you to present 3D objects or documents via PLUS projectors.

Included Accessories:

- Wireless remote control (U5-111/112)
- Wireless remote control w/mouse control (U5-132/232/332)
- Power cable (6 ft./1.8 m)
- VGA cable (mini D-sub 15 pin) (6.5 ft./2 m)
- S-video cable (6.5 ft./2 m)
- Video Cable, RCA (6.5 ft./2 m)
- 3.5 mm mini plug audio cable (6.5 ft./2 m)
- 3.5 mm stereo plug to RCA
- USB cable, Mini-B - Type A (6.5ft./2 m) (U5-132/232/332)
- Soft carrying case
- User's manual

Optional Accessories:

- ATA shipping cases
- VGA cables (9-12 ft./2.7-3.6 m)
- 15-pin to RCA component cable (10 ft./3 m)
- Zen Z2 Remote RF Wireless USB Mouse
- Ceiling mount kit



PLUS Vision Corp.

9610 SW SUNSHINE CT.
 SUITE 800
 BEAVERTON, OR 97005
 866-427-8855 • 503-748-8700
 www.plus-america.com