

A cost-effective solution that doesn't sacrifice quality



## IBM E400 projector



**NEW!**

*The IBM E400 projector includes a carrying case and remote control with integrated laser pointer.*

### Highlights

- **Small size and weight eases travel from the office to home or elsewhere**
- **Good image quality and value-added features provide professional presentation capabilities with entry-level affordability**
- **Auto-sensing technology lets you plug-in and project from your IBM ThinkPad notebook, enabling you to start presentations with minimal delay**

### Travel light to the office, home and on the road

Boasting one of the lowest weights among entry-level projectors, the IBM E400 projector is easy to carry between home and office. Take advantage of professional image reproduction as well as built-in HDTV compatibility (requires HDTV source).

### Leverage good image quality and professional features—in an affordable package

The IBM E400 projector gives you affordable options for projecting a professional image. The IBM E400 projector provides high quality images and brightness through Digital Light Processing (DLP) technology.

### Plug in and project from your ThinkPad notebook

Get the convenience you require for on-the-go media needs with auto-sensing technology. The IBM E400 projector automatically senses the video signal on your IBM ThinkPad® notebook, so you can just plug in and project with minimal delay.

### Rest easy with one of the industry's most competitive warranties

Rest easy with a 3-year limited warranty<sup>1</sup> on your projector from IBM as well as a 3-month limited warranty on the lamp. You'll also enjoy access to IBM worldwide<sup>2</sup> service and support. Our long lamp life and industry-leading warranty and service combine to deliver exceptional total cost of ownership. With other projectors, you could pay extra to get the service and support that come standard with IBM. For example, if an E400 projector under warranty needs a warranty-related repair, a replacement projector can be shipped to you quickly and easily. Get the peace of mind to keep your focus on your presentation—not on your projector.

For important warranty information, see page 2.

Call **1 888 SHOP IBM** or go to **ibm.com** (U.S.) or **ibm.ca** (Canada) to buy direct, locate an IBM reseller or for more information.

**For more information**

To learn more about the IBM E400, visit  
**ibm.com/us/accessories/projectors** (U.S.)  
**ibm.ca/accessories/projectors** (Canada)



© Copyright IBM Corporation 2004

Produced in the United States of America  
 04-04  
 All Rights Reserved

<b>IBM E400 projector specifications</b>	
<b>Projector:</b>	E400
<b>Part number</b>	0038A04
<b>Weight</b>	2.1kg/ 4.6 lb
<b>Dimensions</b>	97x280x205mm/3.82x11.02x8.0"
<b>Display technology</b>	DLP; single-chip 0.55" DMD
<b>Native resolution</b>	SVGA (800X600)
<b>Lumens/Brightness</b>	1300 ANSI lumens
<b>Contrast ratio</b>	1500:1 Full on/ Full off
<b>Computer compatibility</b>	VGA, SVGA, XGA
<b>Video connectors</b>	DVI-I, S-Video, Composite video
<b>Video compatibility</b>	NTSC, PAL, SECAM, SDTV (480i), EDTV (480p), HDTV (720p, 1080i)
<b>Keystone correction</b>	+/- 15 degrees
<b>Zoom</b>	1.16:1 manual zoom
<b>Audio connector</b>	3.5mm mini-jack
<b>Speakers</b>	1 x 1 Watt Mono
<b>Limited warranty<sup>1</sup></b>	3 years
<b>Control Features:</b>	Keypad, Infra-red remote with laser pointer, USB mouse
<b>Projection</b>	Front, rear, ceiling
<b>Keylock</b>	Yes
<b>Elevator foot</b>	Yes
<b>Leveling foot</b>	Yes
<b>Lamp:</b>	
<b>Part number</b>	73P2775
<b>Power</b>	200w P-VIP
<b>Life<sup>3</sup> (hrs)</b>	2000
<b>Limited warranty<sup>1</sup></b>	90 days

- <sup>1</sup> Telephone support may be subject to additional charges. For onsite labor, IBM will attempt to diagnose and resolve the problem remotely before sending a technician. Bulb covered by a separate 90-day limited warranty.
- <sup>2</sup> International Warranty Service is available in any country in which this product is sold and serviced. Service delivery methods and parts availability vary by country, may be different from that in the country of purchase, and are subject to change without notice. Fees and restrictions may apply in some countries.
- <sup>3</sup> Lamp life is a measure of brightness degradation only, and is not a specification for the time it takes a lamp to fail and cease light output. Lamp life is defined as the time it takes for more than 50 percent of a lamp sample population to have brightness decrease by approximately 50 percent of the rated lumens for the specified lamp. For example, if the defined life of your lamp is 2,000 hours and its brightness is rated at 1100 lumens, then there is a 50-percent chance that over 2,000 hours of run time, your lamp will have decreased its brightness by 50 percent to approximately 550 lumens.

IBM reserves the right to change specifications or other product information without notice. This publication could include technical inaccuracies or typographical errors. References herein to IBM products and services do not imply that IBM intends to make them available in other countries. IBM PROVIDES THIS PUBLICATION "AS IS," WITHOUT WARRANTY OR CONDITION OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OR CONDITIONS OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SOME JURISDICTIONS DO NOT ALLOW DISCLAIMER OF EXPRESS OR IMPLIED WARRANTIES IN CERTAIN TRANSACTIONS; THEREFORE, THIS DISCLAIMER MAY NOT APPLY TO YOU.

IBM, the IBM logo and ThinkPad are trademarks of IBM Corporation in the United States, other countries, or both.

Other company, product and service names may be trademarks or service marks of others.

Not all Accessories by IBM products are made in the United States. Country of origin data is available from your IBM marketing representative or reseller.

**Projection distances and viewing sizes for IBM E400 projector**

Distance to screen	Diagonal screen size	Image width	Image height
1.5m/4.92'	1.10m/43.3"	0.88m/2.88'	0.66m/2.16'
2.0m/6.56'	1.47m/57.8"	1.17m/3.83'	0.88m/2.88'
2.4m/7.87'	1.76m/69.3"	1.4m/4.59'	1.1m/3.6'
2.8m/9.18'	2.06m/81.1"	1.64m/5.38'	1.23m/4.03'
3.2m/10.5'	2.35m/92.5"	1.87m/6.13'	1.41m/4.62'
3.6m/11.81'	2.65m/104.3"	2.11m/6.92'	1.58m/5.18'
4.0m/13.12'	2.94m/115.7"	2.34m/7.67'	1.76m/5.77'
4.4m/14.4'	3.23m/127.2"	2.57m/8.43'	1.94m/6.36'

