



### cineo3+ - High Definition digital eCinema projector

The cineo3+ has been designed to meet the requirements of emerging e-cinema applications. With High Definition DLP™ technology, the cineo3+ offers the best possible reliability and image quality.

Film-like image quality is ensured by using the Emmy-winning DLP™ technology known from DLP Cinema™ projectors. With superb brightness, contrast and colour fidelity, the cineo3+ is well suited even for larger cinema screens.


Designed for reliability, the cineo3+ has numerous features to allow failsafe operation. The patented DuArch™ illumination architecture allows Hot Swap of lamps while in operation, keeping the image on screen. In addition, the cineo3+ features dual colour wheels, dual illumination optimizers, and dual illumination irises. For monitoring, a backlit LCD status panel is available for immediate and configurable status overview and events logging, as well as complete control and asset management over TCP/IP from any remote computer, using standard tools.

Installation flexibility is ensured with a wide range of projection lenses, covering every need from 0.88 – 7.70 : 1. All lenses are user replaceable during operation and can be shifted ±110% vertically and ±90% horizontally.



### Main Features

- New! Updated with higher power 300W lamps for higher brightness and impact
- Dual Lamp architecture for failsafe operation
- RealColor colour management suite
- Hot Swap lamps for user replacement during operation
- High brightness and contrast – user configurable
- High Definition DLP™ technology, >100.000 hours life time
- Wide range of projection lenses, user replaceable
- Vertical and horizontal lens shift for flexible installation
- REC 709 colour space compliant for colour accuracy
- Scope and wide formats available
- Secure DVI interface to film server with HDCP anti-piracy protocol
- Custom input configurations using patented XPort™ technology
- Backlit LCD status monitoring
- TCP/IP asset management




HIGH PERFORMANCE PROJECTORS™



## technical specifications

cineo3+	
projector	HDTV DLP™ digital projector
display	<p>technology single chip LVDS DLP™ technology with DarkChip3™</p> <p>concept sealed, all-glass optical design</p> <p>resolution 1280 x 720 HDTV resolution</p> <p>brightness user configurable; up to 4200 ANSI lumens</p> <p>contrast user configurable; up to 7500 : 1</p> <p>aspect ratio 16 : 9 native, scope and widescreen</p> <p>colours 16.8 million displayable</p> <p>latency ~ 1 input frame with graphics</p>
compatibility	<p>computer compatibility RGBHV, RGBS, RGsB</p> <p>horizontal scan 15 - 150 kHz</p> <p>vertical scan 48 - 190 Hz</p> <p>video compatibility HDTV (1080i, 720p, 576i/p, 480i/p) NTSC, NTSC4.43, PAL, PAL-M, PAL-N, SECAM</p> <p>bandwidth 205 MHz analog RGB, 165 MHz digital RGB</p>
lenses	<p>lens operation motorized zoom/focus/shift for all lenses</p> <p>IRIS control motorized IRIS control for F/2.1 - 6.1 for all lenses</p>



- ultra wide angle 0.88:1 fixed focal (on axis only)
- wide angle 1.30:1 fixed focal
- wide angle zoom 1.45 - 1.85 : 1
- standard zoom 1.85 - 2.75 : 1
- tele zoom 2.75 - 4.35 : 1
- long tele zoom 4.35 - 7.70 : 1

optics	
lens shift	+/- 110% vertical, +/- 90% horizontal
lamps	300W UHP™ x2
lamp power control	250 - 300W in 5W increments
lamp life	6000 hours (max) in eco lamp relay mode 1700 hours (typ) in full power mode

inputs / outputs	
computer inputs	1x 15 pin HDDSUB (analog RGB) 1x DVI HDCP (secure digital RGB) 1x BNC x5 (analog RGB or YUV)
video inputs	3x RCA (YUV) x 4-pin Mini DIN (Y/C) 1x RCA (C)
audio inputs	2x 3.5 mm Stereo Mini Jack Audio (all ch.)
communications	2x RS232 9-pin DSUB (control) in/out 1x RJ-45 TCP/IP (LAN)
computer output	1x USB (firmware upgrade)
audio output	1x 15 pin HDDSUB (analog) monitor 1x 3.5 mm Stereo Mini Jack

general	
operating noise level (typ)	30 dB (A) at 20°C/ 68°F, sea level
dimensions (dwh)	376 x 510 x 223 mm / 14.8 x 20.0 x 8.8 in
weight (w/o lens)	12.7 kg / 27.8 lbs + lens
power requirements	90 - 260 VAC, 50/60 Hz 900 W power consumption
conformances	CE, FCC Class A, CSA(C/US),
colours	metallic grey, silver



Designed and manufactured in Norway by:  
 projectiondesign as  
 Habornveien 53  
 N-1630 Gamle Fredrikstad  
 Norway  
 +47 69 30 45 50  
 sales@projectiondesign.com  
 www.projectiondesign.com

Distributed by: