



C175 & C185

Create your own opportunity



Powerful & versatile

The new ASK Proxima C175 and C185 are designed to help you get your ideas across as clearly as possible. These innovative projectors provide the power you need, and thanks to the reliability of DLP® technology, you'll be worry-free. Once you see what an impact these projectors make on your meeting, you'll never want to present without one. With the C175 or C185 in your office you'll give your ideas the biggest, brightest and clearest platform possible.

Outstanding performance

The C175 or C185 looks and acts like a high-end projector, but comes at a very affordable price. It's the perfect way to make your presentations shine without breaking the bank. The compact design enables easy installation and makes it a snap to move from meeting to meeting.

Now you're connected

Say hello to the end of connection hassles. Multiple inputs on the C175 or C185 provide seamless integration into your existing IT infrastructure. With network and RS232 connections, multiple computer inputs, S-Video and more, you'll be confident that your meeting room will be compatible with your projector.

Make it easy on yourself

With a quick, simple set up and an intuitive user interface, the C175 or C185 allows anyone to give an impressive presentation. Exceptional brightness provided by the 2,000 plus max ANSI lumens, paired with the latest DLP® display chipset, provide awe-inspiring images. Instant feedback from the intuitive LED panel facilitates easy troubleshooting while the low operating volume lets the projection speak for itself.



The easy to use keypad and instant-feedback LED display make running the show trouble-free. You'll have easy-access to the features you need at the touch of a button.

Additional Features

- Serial interface, computer and A/V inputs make IT integration easy.
- The latest DLP® display chipset provides the most reliable images imaginable.
- Sleek, compact design provides maximum mobility.
- Quiet operating volume of <35 dBA lets the presentation do the talking.
- Instant feedback LED interface takes the trouble out of troubleshooting.

TECHNICAL SPECIFICATIONS*

Native Resolution	• XGA 1024 x 768
Display Technology	• DLP® by Texas Instruments™: 0.7" XGA DDR DMD
Input Sources	• 2 Computer (DVI-M1 and VESA); 2 Video (S-Video 4-pin mini DIN and Composite RCA); 1 Audio (stereo RCA); 1 Serial Interface (RJ45)
Output Sources	• Monitor Out (VESA); Stereo Audio (3.5 mm)
Computer Compatibility	• VGA, SVGA, XGA, SXGA, SXGA+, Macintosh®
Video Compatibility	• SDTV (NTSC, PAL, SECAM, 480i, 576i), ED/HDTV (480p, 576p, 720p, 1080i)
Brightness	• C175: 2000 max ANSI lumens • C185: 2500 max ANSI lumens
Contrast Ratio	• 1000:1
Number of Colors	• 16.7 million
Projection Distance	• 4.92'-33' (1.5-10 m)
Brightness Uniformity	• -30%
H-Synch Range	• 15.625-85 kHz
V-Synch Range	• 48-85 Hz
Dot Clock	• 13.5 MHz-140 MHz
Digital Keystone Correction	• +30/-25 degrees vertical correction; video/data
Projection Lens	• Zoom lens with manual focus and manual zoom adjustment
Zoom Ratio	• 1.2:1
Throw Ratio (distance/image width)	• 1.83:1-2.27:1
Minimum Projection Distance	• 4.92' (1.5 m)
Image Offset Ratio %	• 115%
Aspect Ratio	• 4:3 (native) and 16:9
Image Size (diagonal)	• 32" (82.5 cm) to greater than 264" (670 cm)
Projection Methods	• Front, ceiling, rear, rear ceiling
Audio	• 3.0 Watt
Control	• Projector keypad, IR remote control, USB via M1-D/A, RS232 serial via RJ45
Lamp	• 200W SHP / 2000 hour user replaceable
Product Dimensions	• 2.93" H x 10.36" W x 8.57" L (7.44 cm H x 26.31 cm W x 21.77 cm L)
Product Weight	• 5.2 lbs (2.36 kg)
Product Color	• Black with Silver
Shipping Weight	• 16 lbs (7.2 kg)
Shipping Dimensions	• 8" H x 20" L x 15" W (20.32 cm H x 50.86 cm W x 38.10 cm L)
Power Consumption	• 260W
Power Supply	• 90-265 VAC at 50/60 Hz
Operating Temperature	• 10-35 °C at sea level to 7500' (2286 m), 50-95 °F
Ships with	• Computer cable (with tie wrap), power cable (with tie wrap), carry case, lens cap, remote control, user guide, detailed reference guide, CD
Menu Languages	• English, German, French, Italian, Spanish, Swedish, Portuguese, Russian, Chinese (simplified)
Audible Noise	• 35dbA in Low Power Mode
Approvals	• UL and c-UL (US/Canada), FCC-A (US/Canada), CE (CE member countries), GOST (Russia), TUV GS (Germany), CCC (China), IRAM (Argentina), NOM (Mexico), C-Tick (Australia)
Lamp Warranty	• 6 months
Product Warranty	• 2 year parts and labor
Accessory Warranty	• 90 day/1 year

* Actual lamp life may vary based on the ambient environment. Conditions that may affect lamp life include temperature, altitude or rapidly switching the projector on and off.

+ ASK Proxima reserves the right to alter product offerings and specifications at any time without notice.

++ Product warranty may vary per region.



SHIPS STANDARD WITH:

- Lens cap
- Computer Cable
- Power Cord
- SCART Adapter (EMEA Only)
- Projector System CD includes: multi-language User Guide, Quick Start Card, URL/service information/accessories after market
- User Guide (printed version)
- Quick Start Card (printed version)

OPTIONAL ACCESSORIES

- Ceiling Mount
- Projection Screens
- Performance Cables for digital and HDTV
- Cable Adapters
- Advanced Remote Control

SERIOUS COMMITMENT

ASK Proxima's dedication to quality and customer satisfaction is reflected in service options that will bring you a greater return on your investment. ASK Proxima projectors come with a standard two-year limited factory warranty, including parts and labor, a 90-day or one-year accessory warranty, and a six-month lamp replacement warranty. Our customer support offers you premium service and convenience, whatever your needs.

For service program details in your region, please visit: www.infocus.com/service/service_offerings

ASK Proxima

www.askproxima.com

InFocus Corporate Headquarters: 27700B SW Parkway Avenue
Wilsonville, Oregon 97070-9215, USA • Phone: (1) 503-685-8888
(1) 800-294-6400 • Fax: (1) 503-685-8887

In Europe: InFocus International BV • Strawinskylaan 585 • 1077 XX Amsterdam
The Netherlands • Phone: (31) 20 5792000 • Fax: (31) 20 5792999
Freephone: 008000 4636287 (008000 INFOCUS)

In Asia: 19 Tanglin Road • 7th Floor
Singapore 247909 • Telephone: (65) 6334-9005 • Fax: (65) 6333-4525