

# PDG-DSU20N

SVGA Ultraportable Multimedia Projector



## ULTRA-COMPACT, FULLY PORTABLE SVGA DESIGN

Not much larger than a laptop PC, the PDG-DSU20N weighs less than 5.5 pounds and delivers true SVGA picture quality in a versatile, go-anywhere system.

## HIGH BRIGHTNESS AND CONTRAST

A brightness level of 2000 ANSI Lumens and a contrast ratio of 2000:1 make this projector a winner in its category. It's all the quality DLP® technology has become known for.

## F2.51-2.69 ZOOM LENS

Comes with its own 1:1.1 zoom lens, which can throw a crisp, bright 100" diagonal image. That's just one size. This lens is adjustable up to a 300-inch diagonal screen size.

## AUTO INPUT SEARCH

This special feature searches, finds and displays incoming source material automatically.

## SPECIAL FEATURES

Component input, quiet fan operation and versatile go anywhere capability make this a truly portable projector. Also may be ceiling or inverse mounted for enhanced versatility.

**SANYO**

PRESENTATION TECHNOLOGIES

21605 Plummer Street  
Chatsworth, CA 91311  
Ph: 888-337-1215 (toll-free)  
Fax 818.717.2719  
www.sanyoldc.com

## Specifications

Resolution	SVGA (800 x 600)
Brightness	2000 ANSI Lumens
Uniformity	80% (corner to center)
Panel System	0.55" DMD x 1
Number of Pixels	480,000(800 x 600)
Contrast Ratio	2000:1
Image Size (diagonal)	30" – 300"
Aspect Ratio	4:3
Throw Distance	3.9' – 39.4'
Zoom/Focus	Manual
Zoom Ratio	1:1.1
Up/Down Ratio	13.3:-1
Digital Keystone Correction	Vertical: +/- 15° MAX
Projection Lens	F2.51-2.69 / f0.86"-0.95"
Lens Throw Ratio	1.95-2.15:1
Projection Lamp	180W UHP
Scanning Frequency	H Sync: 31-79kHz, V Sync: 50-85Hz
Dot Clock	25-135MHz
Color System	PAL/PAL-M/PAL-N/SECAM/NTSC/NTSC4.43
Computer Compatibility	SXGA, XGA, SVGA, VGA
Sound Output	One-piece, 2-watt Mono
Voltage	100-240V AC (auto Voltage) ; 50/60 Hz
BTU Rating	785/682 (Normal/Eco)
dB Rating	35dB / 32dB (Normal/Eco)
Power Consumption	230W / 200W (Normal/Eco)
Dimensions (WxHxD)	10.7" x 3.7" x 8.8" (Including Adjustable Feet & Lens Part)
Net Weight	5.5lbs
User Maintenance	replace lamp assembly
PC Input Terminals	D-Sub15 x 1
Video Input Terminals	Composite Video (RCA x 1) • S-Video (Mini-DIN 4-pin) • Audio (mini-jack : common) • Computer/Component In (Dsub 15x1)
Control Terminals	• USB (Type B)
Included Accessories	Wireless remote • CR2025 batteries • Owner's Manual • VGA Cable • Lens Cap with strap • AC power supply code
Optional Accessories	• POA-CA-COMPVGA – Component- VGA conversion Cable • 610 337 1764 – Replacement Lamp • POA-CACVCL2 - Soft Carrying Bag
Service Port	None
Warranty	Three years parts and labor; 90 days original lamp; Quick Repair Program under warranty

Because its products are subject to continuous improvement, SANYO reserves the right to modify product design and specifications without notice and without incurring any obligations.



INPUT / OUTPUT TERMINAL



REMOTE CONTROL



DLP® and the DLP logo are registered trademarks of Texas Instruments.