

Dell M409WX

At a Glance

- **High Brightness** - Leave the lights on with maximum projector brightness of 2000 ANSI Lumens.
- **1280 x 800 WXGA Resolution** - Deliver native 16:10 widescreen format in high-quality WXGA resolution. Auto sync up to 1600 x 1200 UXGA.
- **2000:1 Contrast Ratio (Full On / Full Off)** - The 2000:1 (typical) contrast ratio offers deep, rich colours, sharp image quality and easy-to-read text.
- **DLP® and BrilliantColor™ Technology** - With 16.7 million vibrant colours, the M409WX produces precise, life-like images and superior colour performance. The magic is in the mirrors.
- **39 Feet (12 Meter) Maximum Screen Projection** - From a 39 feet distance (12 meters), the M409WX makes a really big impression.
- **Up to 5000 Hours Lamp¹ Life** - Reduce cost and maintenance with lamp life up to 5000 hours in quiet-running eco mode.
- **Ultra-Portable 2.6 lbs** - At only 2.6 lbs (1.18 kg), this lightweight projector is ready for the road.
- **Customizable Start-up Logo** - Build brand awareness by adding your customized company logo to the start-up.
- **Quick Shut Down Feature** - Designed to shut down in 10 seconds (prior settings required).



Ultra-Mobile, Widescreen Projection



At only 2.6 lbs, this portable projector easily goes wherever business takes you. Quickly connect to widescreen laptops and deliver big multi-media presentations in a high-quality 16:10 viewing format. The M409WX offers maximum brightness of 2000 Lumens for effective, lights-on performance.

DLP® and BrilliantColor™ Technology

Thanks to multi-colour processing and BrilliantColor technology, the M409WX offers superior colour performance, image accuracy and picture reliability. DLP projectors produce wonderfully vivid colour quality. The magic is in the mirrors.

Versatile Connectivity

You'll be well-connected with the M409WX. Ideal for the highly mobile professional, this versatile projector offers extensive connectivity options – including HDMI, VGA, S-Video and composite video connections. And with flexible rear and front projection using a translucent screen, the

M409WX shines in most setting.

Immediate Road Ready Operation

Open the box and then open your eyes to brilliant, widescreen performance. The M409WX is shipped with everything you need to take your show on the road – including projector, soft carrying case, full-featured remote control, power cord, batteries and VGA connection cable.

Brightness:

2000 ANSI Lumens (maximum)

Contrast Ratio:

2000:1 typical (Full on / Full off)

Resolution:

1280 x 800 (WXGA); autosync up to 1600 x 1200 (UXGA) maximum

Uniformity:

80% typical (Japan Standard - JBMA)

Projection Lens:

F-Stop: F/2.44 ~ 2.58

Focal length, f=21.8~23.8 mm with 1.1x manual zoom lens

Image Size:

76.1 cm to 913.0 cm (27.3" to 359.4")

Projection Distance:

1.0 m to 12.0 m (3.3 ft to 39.4 ft)

Lamp Life¹ Cycle:

3000 hours (typical); 5000 hours (eco mode)

Lamp Type:

165 watt user-replaceable lamp

Audio:

1 speaker, 1 watt RMS (Mono)

Security:

Kensington[®] security port (cable lock sold separately) Password Protection

Connectivity:

Integrated Video and Audio Ports

VGA

S-Video

Composite Video

Component via VGA

HDMI

Audio-In

Audio-Out

Video Compatibility

High Definition Multimedia Interface (HDMI)

Component Video via VGA

S-Video

Composite Video

Keystone Correction Direction:

Vertical

Vertical Keystone Correction:

+40/-35°

Horizontal Keystone Correction:

Not available

Colour:

Black

Dimensions (W x D x H):

7.25 cm (2.85") x 15.5 cm (6.10") x 20.5 cm (8.07")

Weight:

1.18 kg (2.6 lbs)

Power:

Universal 90-264 V AC 50-60 Hz with PFC input

Power Consumption Operational:

212 watts (typical); 168 watts (eco mode)

Compliance and Standards:

FCC, CE, VCCI, UL, cUL, Nemko-GS, ICES-003, MIC, C-Tick, CCC, PSB, NOM, SABS, eK

Temperature Range Operating:

5° C to 35° C (41° F to 95° F)

Temperature Range Non-operating:

0° C to 60° C (32° F to 140° F)

Humidity:

80% (maximum)

Humidity Range Non-operating:

Storage: 90% (maximum)

Sound Emission:

38 dB(A) Full-on mode; 32 dB(A) eco mode

What's in the Box:

1.8 m power cord (3.0 m in Americas)

1.8 m VGA cable (VGA to VGA)

Carrying case

Remote control

AAA Batteries (2)

CD User's guide and documentation

¹ **DISCLAIMER :** The actual operating life span of a projector lamp will vary according to operating conditions and usage patterns. Usage of a projector in stressful conditions which may include dusty environments, under high temperatures and abrupt powering-off may result in a lamp's shortened operating life span or possibly lamp failure. The lamp life specified for Dell's projectors refers to the typical time under non-stressful operating conditions for more than 50% of a sampling population to reduce to approximately 50% of the lamp's rated brightness level. It is not the measure of time a lamp will cease light output.