



Designer Styling – Big Screen Impact

Small and stylish, the EP720 will deliver life-like presentations and movies up to 300". Great colours, really impressive brightness and easy to use both in the office and at home; with computers, games consoles and DVD players.

- 2200 lumens to highlight the finest detail in ambient light conditions
- Designer styling and compact at 2kg; as versatile on the move as it is when installed
- Optoma Colour Enhancement Technology and 2000:1 contrast gives exceptional colour to create crystal clear presentations and video
- Optoma 10 Year Colour Guarantee*
- Comprehensive PC, Video, DVD and games consoles connectivity includes: VGA, Component & SCART capabilities
- Native SVGA and zoom lens for sharp, detailed images and movies
- DLP® Filter-free design for zero maintenance No routine servicing


Easy to use:

- Fully featured remote control with mouse control
- 5 preset picture modes to adjust the settings to match a variety of different applications
- 15 second start-up and cool down time to reduce both time and money in energy use
- Quick keystone correction

- Express start-up & cool down
- Built in speaker for multi media use
- Long Lamp Life 3000 hours standard

Optoma Colour Enhancement Technology maximises colour accuracy for deeper saturated colours

Optoma guarantees colour quality will remain as new for 10 years*



Optoma Colour Enhancement Technology



EP720 Remote Control

- Remote Mouse
- Vertical Keystone Correction
- Volume Control
- Brightness Adjustment
- Contrast Adjustment
- AV Mute
- Direct Input Source Selection

EP720 Connections

- VGA In Component & SCART via adaptor
- Composite
- 10 S-Video
- 11 Audio In
- 12 USB (Remote Mouse)



Specifications

Native Resolution SVGA 800 x 600 Compressed Resolution SX6A (1280 x 1024) Brightness 2000/1500L (BRIGHT/STD mode) Contrast 2000:1 Noise Level 30dB Lamp Life 3000/2000 (STD/BRIGHT mode)** Display Technology Single 0.55" SVGA type X DMD chip DLP® Technology by Texas Instruments Weight / Dimensions (W x D x H) 2 kg / 259 x 188 x 71.5mm Remote Control Full Function Remote Mouse and Direct Source selecting INPUTS: 15 Pin D-Sub VGA (SCART & Component via adaptor) S-Video 4 Pin Mini Din Composite RCA 3.5mm Stereo Jack USB (remote mouse) Audio 1 x TW Speaker Aspect Ratio 4:3 Native, 16:9 Compatible Keystone Correction ± 18 Degrees Vertical On Screen Display 16 Languages: English, German, French, Italian, Spanish, Portuguese, Polish, Dutch, Russian, Finnish, Swedish, Greek, Norwegian/Danish, Hungarian, Czech & Arabic Video Compatibility PAL SECAM 576i/p, NTSC 486i/p, DT 720p/1080i Uniformity 85% Displayable Colours F-2.41 - 2.55, f=21.79 - 23.99mm, 1.1x Manual Focus Throw Ratio 1.95 ~ 2.15:1 (EP720
Brightness 2000/1500L (BRIGHT/STD mode)	Native Resolution	SVGA 800 x 600
Contrast Noise Level 30dB Lamp Life 3000/2000 (STD/BRIGHT mode)*** Display Technology Single 0.55" SVGA type X DMD chip DLP® Technology by Texas Instruments Weight / Dimensions (W x D x H) Remote Control Full Function Remote Mouse and Direct Source selecting INPUTS: 15 Pin D-Sub VGA (SCART & Component via adaptor) S-Video 4 Pin Mini Din Composite RCA 3.5mm Stereo Jack USB (remote mouse) Audio 1 x 1W Speaker Aspect Ratio 4:3 Native, 16:9 Compatible Keystone Correction ± 18 Degrees Vertical On Screen Display 16 Languages: English, German, French, Italian, Spanish, Portuguese, Polish, Dutch, Russian, Finnish, Swedish, Greek, Norwegian/Danish, Hungarian, Czech & Arabic Video Compatibility PAL SECAM 576i/p, NTSC 480i/p, HD 720p/1080i Uniformity 85% Displayable Colours 16.7 Million Projection Lens F=2.41 ~ 2.55, 1=21.79 ~ 23.99mm, 1.1x Manual Focus Throw Ratio 1.95 ~ 2.15:1 (Projection Distance:Image Width) Projection Distance 1.2 - 12m Image Size 0.70 - 7.70m (27.49" - 303.12") Diagonal 4:3 Horizontal Scan Rate 43 - 85Hz Power Consumption 260W Maximum < 10W Standby mode Operating Conditions Operating: 5 - 40 C, 80% Humidity (Max), 3000m Altitude (Max) Security One Kensington Lock Port, Password Protection Standard Accessories Lens Cover, AC Power Cord, VGA Cable, USB Cable, Full Function Remote, Batteries x 2, Quick Start Guide, CD User Manual, Warranty, WEEE Card Compliant Lamp Warranty Warranty may vary by country. Please see www.optomaeurope.com or ask your local supplier for details	Compressed Resolution	SXGA (1280 x 1024)
Noise Level 30dB Lamp Life 3000/2000 (STD/BRIGHT mode)** Display Technology Single 0.55" SVGA type X DMD chip DLP® Technology by Texas Instruments Weight / Dimensions (W x D x H) 2 kg / 259 x 188 x 71.5mm Remote Control Full Function Remote Mouse and Direct Source selecting INPUTS: 15 Pin D-Sub VGA (SCART & Component via adaptor) S-Video 4 Pin Mini Din Composite RCA 3.5mm Stereo Jack USB (remote mouse) Audio 1 x 1W Speaker Aspect Ratio 4:3 Native, 16:9 Compatible Keystone Correction ± 18 Degrees Vertical On Screen Display 16 Languages: English, German, French, Italian, Spanish, Portuguese, Polish, Dutch, Russian, Finnish, Swedish, Greek, Norwegian/Danish, Hungarian, Czech & Arabic Video Compatibility PAL SECAM 576i/p, NTSC 480i/p, HD 720p/1080i Uniformity 85% Displayable Colours 16.7 Million Projection Lens F=2.41 ~ 2.55, 1=21.79 ~ 23.99mm, 1.1x Manual Focus Throw Ratio 1.95 ~ 2.15:1 (Projection Distance-Image Width) Projection Distance 1.2 - 12m Image Size 0.70 - 7.70m (27.49" - 303.12") Diagonal 4:3 Horizontal Scan Rate 43 - 85Hz Power Supply 100-240V, 50-60Hz with PFC Power Supply Power Consumption 260W Maximum < 10W Standby mode Operating Conditions Operating: 5 - 40 C, 80% Humidity (Max), 3000m Altitude (Max) Security One Kensington Lock Port, Password Protection Standard Accessories Lens Cover, AC Power Cond, VGA Cable, USB Cable, Full Function Remote, Batteries x 2, Quick Start Guide, CD User Manual, Warranty, WEEE Card RoHS Compliant Lamp Warranty Warranty wary by country. Please see www.optomaeurope.com or ask your local supplier for details	Brightness	2000/1500L (BRIGHT/STD mode)
Lamp Life Display Technology Single 0.55" SVGA type X DMD chip DLP® Technology by Texas Instruments Weight / Dimensions (W x D x H) Remote Control Full Function Remote Mouse and Direct Source selecting INPUTS: 15 Pin D-Sub VGA (SCART & Component via adaptor) S-Video 4 Pin Mini Din Composite RCA 3.5mm Stereo Jack USB (remote mouse) Audio 1 x 1W Speaker Aspect Ratio 4:3 Native, 16:9 Compatible Keystone Correction 16 Languages: English, German, French, Italian, Spanish, Portuguese, Polish, Dutch, Russian, Finnish, Swedish, Greek, Norwegian/Danish, Hungarian, Czech & Arabic Video Compatibility PAL SECAM 576i/p, NTSC 480i/p, HD 720p/1080i Uniformity 85% Displayable Colours 16.7 Million Projection Lens F=2.41 ~ 2.55, f=21.79 ~ 23.99mm, 1.1x Manual Focus Throw Ratio 1.95 ~ 2.15:1 (Projection Distance:Image Width) Projection Distance 1.2 - 12m Image Size 0.70 - 7.70m (27.49" - 303.12") Diagonal 4:3 Horizontal Scan Rate Vertical Scan Rate 43 - 85Hz Power Supply 100-240V, 50-60Hz with PFC Power Supply Power Consumption Operating: 5 - 40 C, 80% Humidity (Max), 3000m Altitude (Max) Security One Kensington Lock Port, Password Protection Lens Cover, AC Power Cord, VGA Cable, USB Cable, Full Function Remote, Batteries x 2, Quick Start Guide, CD User Manual, Warranty, WEEE Card RoHS Compilant Lamp Warranty Warranty may vary by country. Please see www.optomaeurope.com or ask your local supplier for details	Contrast	2000:1
Display Technology Single 0.55" SVGA type X DMD chip DLP® Technology by Texas Instruments Weight / Dimensions (W x D x H) Remote Control Full Function Remote Mouse and Direct Source selecting INPUTS: 15 Pin D-Sub V6A (SCART & Component via adaptor) S-Video 4 Pin Mini Din Composite RCA 3.5mm Stereo Jack USB (remote mouse) Audio 1 x 1W Speaker Aspect Ratio 4:3 Native, 16:9 Compatible Keystone Correction 1 8 Degrees Vertical On Screen Display 16 Languages: English, German, French, Italian, Spanish, Portuguese, Polish, Dutch, Russian, Finnish, Swedish, Greek, Norwegian/Danish, Hungarian, Czech & Arabic Video Compatibility PAL SECAM 576i/p, NTSC 480i/p, HD 720p/1080i Uniformity 85% Displayable Colours 16.7 Million Projection Lens F=2.41 ~ 2.55, f=21.79 ~ 23.99mm, 1.1x Manual Focus Throw Ratio 1.95 ~ 2.15:1 (Projection Distance:Image Width) Projection Distance 1.2 - 12m Image Size 0.70 - 7.70m (27.49" - 303.12") Diagonal 4:3 Horizontal Scan Rate 43 - 85Hz Power Supply 100-240V, 50-60Hz with PFC Power Supply Power Consumption 260W Maximum < 10W Standby mode Operating Conditions Operating: 5 - 40 C, 80% Hurniadity (Max), 3000m Altitude (Max) Security One Kensington Lock Port, Password Protection Standard Accessories Lens Cover, AC Power Cord, VGA Cable, USB Cable, Full Function Remote, Batteries x 2, Quick Start Guide, CD User Manual, Warranty, WEEE Card RoHS Compilant Lamp Warranty Warranty may vary by country. Please see www.optomaeurope.com or ask your local supplier for details	Noise Level	30dB
Weight / Dimensions (W x D x H) 2 kg / 259 x 188 x 71.5mm Remote Control Full Function Remote Mouse and Direct Source selecting INPUTS: 15 Pin D-Sub VGA (SCART & Component via adaptor) S-Video 4 Pin Mini Din Composite RCA 3.5mm Stereo Jack USB (remote mouse) Audio 1 x 1W Speaker Aspect Ratio 4:3 Native, 16:9 Compatible Keystone Correction ± 18 Degrees Vertical On Screen Display 16 Languages: English, German, French, Italian, Spanish, Portuguese, Polish, Dutch, Russian, Finnish, Swedish, Greek, Norwegian/Danish, Hungarian, Czech & Arabic Video Compatibility PAL SECAM 576i/p, NTSC 480i/p, HD 720p/1080i Uniformity 85% Displayable Colours 16:7 Million Projection Lens F=2.41 ~ 2.55, f=21.79 ~ 23.99mm, 1.1x Manual Focus Throw Ratio 1.95 ~ 2.15:1 (Projection Distance:Image Width) Projection Distance 1.2 - 12m Image Size 0.70 - 7.70m (27.49" - 303.12") Diagonal 4:3 Horizontal Scan Rate 43 - 85Hz Power Supply 100-240V, 50-60Hz with PFC Power Supply Power Consumption 260W Maximum < 10W Standby mode Operating Conditions Operating: 5 - 40 C, 80% Humidity (Max), 3000m Altitude (Max) Security One Kensington Lock Port, Password Protection Standard Accessories Lens Cover, AC Power Cord, VGA Cable, USB Cable, Full Function Remote, Batteries x 2, Quick Start Guide, CD User Manual, Warranty, WEEE Card RoHS Compliant Lamp Warranty 6 months or 1000 hours - whichever is soonest Warranty Warranty may vary by country. Please see www.optomaeurope.com or ask your local supplier for details	Lamp Life	3000/2000 (STD/BRIGHT mode)**
Remote Control Full Function Remote Mouse and Direct Source selecting INPUTS: 15 Pin D-Sub VGA (SCART & Component via adaptor) S-Video 4 Pin Mini Din Composite RCA 3.5mm Stereo Jack USB (remote mouse) Audio 1 x 1W Speaker Aspect Ratio 4:3 Native, 16:9 Compatible Keystone Correction 1 El Degrees Vertical On Screen Display 16 Languages: English, German, French, Italian, Spanish, Portuguese, Polish, Dutch, Russian, Finnish, Swedish, Greek, Norwegian/Danish, Hungarian, Czech & Arabic Video Compatibility PAL SECAM 576i/p, NTSC 480i/p, HD 720p/1080i Uniformity 85% Displayable Colours 16:7 Million F=2.41 ~ 2.55, f=21.79 ~ 23.99mm, 1.1x Manual Focus Throw Ratio 1.95 ~ 2.15:1 (Projection Distance:Image Width) Projection Distance 1.2 - 12m Image Size 0.70 - 7.70m (27.49" - 303.12") Diagonal 4:3 Horizontal Scan Rate 15 - 100kHz Vertical Scan Rate 43 - 85Hz Power Supply 100-240V, 50-60Hz with PFC Power Supply Power Consumption 260W Maximum < 10W Standby mode Operating: 5 - 40 C, 80% Humidity (Max), 3000m Altitude (Max) Security One Kensington Lock Port, Password Protection Standard Accessories Lens Cover, AC Power Cord, VGA Cable, USB Cable, Full Function Remote, Batteries x 2, Quick Start Guide, CD User Manual, Warranty, WEEE Card RoHS Compliant Lamp Warranty Warranty warranty of teals Source Supplier for details	Display Technology	Single 0.55" SVGA type X DMD chip DLP® Technology by Texas Instruments
INPUTS: 15 Pin D-Sub VGA (SCART & Component via adaptor) S-Video 4 Pin Mini Din Composite RCA 3.5mm Stereo Jack USB (remote mouse) Audio 1 x 1W Speaker Aspect Ratio 4:3 Native, 16:9 Compatible Keystone Correction 1 £ 18 Degrees Vertical On Screen Display 16 Languages: English, German, French, Italian, Spanish, Portuguese, Polish, Dutch, Russian, Finnish, Swedish, Greek, Norwegian/Danish, Hungarian, Czech & Arabic Video Compatibility PAL SECAM 576i/p, NTSC 480i/p, HD 720p/1080i Uniformity 85% Displayable Colours 16.7 Million Projection Lens F=2.41 ~ 2.55, f=21.79 ~ 23.99mm, 1.1x Manual Focus Throw Ratio 1.95 ~ 2.15:1 (Projection Distance:Image Width) Projection Distance 1.2 - 12m Image Size 0.70 - 7.70m (27.49" - 303.12") Diagonal 4:3 Horizontal Scan Rate 15 - 100kHz Vertical Scan Rate 43 - 85Hz Power Supply 100-240V, 50-60Hz with PFC Power Supply Power Consumption Operating Conditions Operating: 5 - 40 C, 80% Humidity (Max), 3000m Altitude (Max) Standard Accessories Lens Cover, AC Power Cord, VGA Cable, USB Cable, Full Function Remote, Batteries x 2, Quick Start Guide, CD User Manual, Warranty, WEEE Card RoHS Compliant Lamp Warranty Warranty may vary by country. Please see www.optomaeurope.com or ask your local supplier for details	Weight / Dimensions (W x D x H)	2 kg / 259 x 188 x 71.5mm
S-Video 4 Pin Mini Din Composite RCA 3.5mm Stereo Jack USB (remote mouse) Audio 1 x 1W Speaker Aspect Ratio 4:3 Native, 16:9 Compatible Keystone Correction ± 18 Degrees Vertical On Screen Display 16 Languages: English, German, French, Italian, Spanish, Portuguese, Polish, Dutch, Russian, Finnish, Swedish, Greek, Norwegian/Danish, Hungarian, Czech & Arabic Video Compatibility PAL SECAM 576i/p, NTSC 480i/p, HD 720p/1080i Uniformity 85% Displayable Colours 16.7 Million Projection Lens F=2.41 ~ 2.55, f=21.79 ~ 23.99mm, 1.1x Manual Focus Throw Ratio 1.95 ~ 2.15:1 (Projection Distance:Image Width) Projection Distance 1.2 - 12m Image Size 0.70 - 7.70m (27.49" - 303.12") Diagonal 4:3 Horizontal Scan Rate 43 - 85Hz Power Supply 100-240V, 50-60Hz with PFC Power Supply Power Consumption Operating Conditions Operating: 5 - 40 C, 80% Humidity (Max), 3000m Altitude (Max) Security One Kensington Lock Port, Password Protection Standard Accessories Lens Cover, AC Power Cord, VGA Cable, USB Cable, Full Function Remote, Batteries x 2, Quick Start Guide, CD User Manual, Warranty, WEEE Card RoHS Compliant Lamp Warranty Warranty may vary by country. Please see www.optomaeurope.com or ask your local supplier for details	Remote Control	Full Function Remote Mouse and Direct Source selecting
Composite RCA 3.5mm Stereo Jack USB (remote mouse) Audio 1 x 1W Speaker Aspect Ratio 4:3 Native, 16:9 Compatible Keystone Correction ± 18 Degrees Vertical On Screen Display 16 Languages: English, German, French, Italian, Spanish, Portuguese, Polish, Dutch, Russian, Finnish, Swedish, Greek, Norwegian/Danish, Hungarian, Czech & Arabic Video Compatibility PAL SECAM 576i/p, NTSC 480i/p, HD 720p/1080i Uniformity 85% Displayable Colours 16.7 Million Projection Lens F=2.41 ~ 2.55, f=21.79 ~ 23.99mm, 1.1x Manual Focus Throw Ratio 1.95 ~ 2.15:1 (Projection Distance:Image Width) Projection Distance 1.2 - 12m Image Size 0.70 - 7.70m (27.49" - 303.12") Diagonal 4:3 Horizontal Scan Rate 43 - 85Hz Power Supply 100-240V, 50-60Hz with PFC Power Supply Power Consumption 260W Maximum < 10W Standby mode Operating Conditions Operating: 5 - 40 C, 80% Humidity (Max), 3000m Altitude (Max) Security One Kensington Lock Port, Password Protection Standard Accessories Lens Cover, AC Power Cord, VGA Cable, USB Cable, Full Function Remote, Batteries x 2, Quick Start Guide, CD User Manual, Warranty, WEEE Card RoHS Compliant Lamp Warranty Warranty may vary by country. Please see www.optomaeurope.com or ask your local supplier for details	INPUTS:	15 Pin D-Sub VGA (SCART & Component via adaptor)
3.5mm Stereo Jack USB (remote mouse) Audio 1 x 1W Speaker Aspect Ratio 4:3 Native, 16:9 Compatible Keystone Correction ± 18 Degrees Vertical On Screen Display 16 Languages: English, German, French, Italian, Spanish, Portuguese, Polish, Dutch, Russian, Finnish, Swedish, Greek, Norwegian/Danish, Hungarian, Czech & Arabic Video Compatibility PAL SECAM 576i/p, NTSC 480i/p, HD 720p/1080i Uniformity 85% Displayable Colours 16.7 Million Projection Lens F=2.41 ~ 2.55, f=21.79 ~ 23.99mm, 1.1x Manual Focus Throw Ratio 1.95 ~ 2.15:1 (Projection Distance:Image Width) Projection Distance 1.2 - 12m Image Size 0.70 - 7.70m (27.49" - 303.12") Diagonal 4:3 Horizontal Scan Rate 43 - 85Hz Power Supply 100-240V, 50-60Hz with PFC Power Supply Power Consumption 260W Maximum ~ 10W Standby mode Operating Conditions Operating: 5 - 40 C, 80% Humidity (Max), 3000m Altitude (Max) Security One Kensington Lock Port, Password Protection Standard Accessories Lens Cover, AC Power Cord, VGA Cable, USB Cable, Full Function Remote, Batteries x 2, Quick Start Guide, CD User Manual, Warranty, WEEE Card RoHS Compliant Lamp Warranty Warranty may vary by country. Please see www.optomaeurope.com or ask your local supplier for details		S-Video 4 Pin Mini Din
Audio Aspect Ratio Aspect Ratio Aspect Ratio Aspect Ratio 4:3 Native, 16:9 Compatible Evystone Correction b 16 Languages: English, German, French, Italian, Spanish, Portuguese, Polish, Dutch, Russian, Finnish, Swedish, Greek, Norwegian/Danish, Hungarian, Czech & Arabic Video Compatibility PAL SECAM 576i/p, NTSC 480i/p, HD 720p/1080i Uniformity 85% Displayable Colours 16.7 Million Projection Lens F=2.41 ~ 2.55, f=21.79 ~ 23.99mm, 1.1x Manual Focus Throw Ratio 1.95 ~ 2.15:1 (Projection Distance:Image Width) Projection Distance 1.2 - 12m Image Size 0.70 - 7.70m (27.49" - 303.12") Diagonal 4:3 Horizontal Scan Rate 15 - 100kHz Vertical Scan Rate 43 - 85Hz Power Supply 100-240V, 50-60Hz with PFC Power Supply Power Consumption Qperating Conditions Operating: 5 - 40 C, 80% Humidity (Max), 3000m Altitude (Max) Security One Kensington Lock Port, Password Protection Standard Accessories Lens Cover, AC Power Cord, VGA Cable, USB Cable, Full Function Remote, Batteries x 2, Quick Start Guide, CD User Manual, Warranty, WEEE Card RoHS Compliant Lamp Warranty Warranty may vary by country. Please see www.optomaeurope.com or ask your local supplier for details		Composite RCA
Audio 1 x 1W Speaker Aspect Ratio 4:3 Native, 16:9 Compatible ± 18 Degrees Vertical On Screen Display 16 Languages: English, German, French, Italian, Spanish, Portuguese, Polish, Dutch, Russian, Finnish, Swedish, Greek, Norwegian/Danish, Hungarian, Czech & Arabic Video Compatibility PAL SECAM 576i/p, NTSC 480i/p, HD 720p/1080i Uniformity 85% Displayable Colours F=2.41 ~ 2.55, f=21.79 ~ 23.99mm, 1.1x Manual Focus Throw Ratio 1.95 ~ 2.15:1 (Projection Distance:Image Width) Projection Distance 1.2 - 12m Image Size 0.70 - 7.70m (27.49" - 303.12") Diagonal 4:3 Horizontal Scan Rate 43 - 85Hz Power Supply 100-240V, 50-60Hz with PFC Power Supply Power Consumption 260W Maximum < 10W Standby mode Operating Conditions Operating: 5 - 40 C, 80% Humidity (Max), 3000m Altitude (Max) Security One Kensington Lock Port, Password Protection Standard Accessories Lens Cover, AC Power Cord, VGA Cable, USB Cable, Full Function Remote, Batteries x 2, Quick Start Guide, CD User Manual, Warranty, WEEE Card RoHS Compliant Lamp Warranty Warranty may vary by country. Please see www.optomaeurope.com or ask your local supplier for details		3.5mm Stereo Jack
Aspect Ratio 4:3 Native, 16:9 Compatible Evystone Correction 16 Languages: English, German, French, Italian, Spanish, Portuguese, Polish, Dutch, Russian, Finnish, Swedish, Greek, Norwegian/Danish, Hungarian, Czech & Arabic Video Compatibility PAL SECAM 576i/p, NTSC 480i/p, HD 720p/1080i Uniformity 85% Displayable Colours F=2.41 ~ 2.55, f=21.79 ~ 23.99mm, 1.1x Manual Focus Throw Ratio 1.95 ~ 2.15:1 (Projection Distance:Image Width) Projection Distance 1.2 - 12m Image Size 0.70 - 7.70m (27.49" - 303.12") Diagonal 4:3 Horizontal Scan Rate 15 - 100kHz Vertical Scan Rate 43 - 85Hz Power Supply Power Consumption 260W Maximum < 10W Standby mode Operating Conditions Operating: 5 - 40 C, 80% Humidity (Max), 3000m Altitude (Max) Security One Kensington Lock Port, Password Protection Standard Accessories Lens Cover, AC Power Cord, VGA Cable, USB Cable, Full Function Remote, Batteries x 2, Quick Start Guide, CD User Manual, Warranty, WEEE Card RoHS Compliant Lamp Warranty Warranty may vary by country. Please see www.optomaeurope.com or ask your local supplier for details		USB (remote mouse)
Keystone Correction ± 18 Degrees Vertical 0n Screen Display 16 Languages: English, German, French, Italian, Spanish, Portuguese, Polish, Dutch, Russian, Finnish, Swedish, Greek, Norwegian/Danish, Hungarian, Czech & Arabic Video Compatibility PAL SECAM 576i/p, NTSC 480i/p, HD 720p/1080i Uniformity 85% Displayable Colours 16.7 Million Projection Lens F=2.41 ~ 2.55, f=21.79 ~ 23.99mm, 1.1x Manual Focus Throw Ratio 1.95 ~ 2.15:1 (Projection Distance:Image Width) Projection Distance 1.2 - 12m Image Size 0.70 - 7.70m (27.49" - 303.12") Diagonal 4:3 Horizontal Scan Rate 15 - 100kHz Vertical Scan Rate 43 - 85Hz Power Supply Power Consumption 260W Maximum < 10W Standby mode Operating Conditions Operating: 5 - 40 C, 80% Humidity (Max), 3000m Altitude (Max) Security One Kensington Lock Port, Password Protection Standard Accessories Lens Cover, AC Power Cord, VGA Cable, USB Cable, Full Function Remote, Batteries x 2, Quick Start Guide, CD User Manual, Warranty, WEEE Card ROHS Compliant Lamp Warranty Warranty may vary by country. Please see www.optomaeurope.com or ask your local supplier for details	Audio	1 x 1W Speaker
On Screen Display 16 Languages: English, German, French, Italian, Spanish, Portuguese, Polish, Dutch, Russian, Finnish, Swedish, Greek, Norwegian/Danish, Hungarian, Czech & Arabic Video Compatibility PAL SECAM 576i/p, NTSC 480i/p, HD 720p/1080i Uniformity 85% Displayable Colours 16.7 Million Projection Lens F=2.41 ~ 2.55, f=21.79 ~ 23.99mm, 1.1x Manual Focus Throw Ratio 1.95 ~ 2.15:1 (Projection Distance:Image Width) Projection Distance 1.2 - 12m Image Size 0.70 - 7.70m (27.49" - 303.12") Diagonal 4:3 Horizontal Scan Rate 15 - 100kHz Vertical Scan Rate 43 - 85Hz Power Supply 100-240V, 50-60Hz with PFC Power Supply Power Consumption 260W Maximum < 10W Standby mode Operating Conditions Operating: 5 - 40 C, 80% Humidity (Max), 3000m Altitude (Max) Security One Kensington Lock Port, Password Protection Standard Accessories Lens Cover, AC Power Cord, VGA Cable, USB Cable, Full Function Remote, Batteries x 2, Quick Start Guide, CD User Manual, Warranty, WEEE Card RoHS Compliant Lamp Warranty Warranty may vary by country. Please see www.optomaeurope.com or ask your local supplier for details	Aspect Ratio	4:3 Native, 16:9 Compatible
Dutch, Russian, Finnish, Swedish, Greek, Norwegian/Danish, Hungarian, Czech & Arabic Video Compatibility PAL SECAM 576i/p, NTSC 480i/p, HD 720p/1080i Uniformity 85% Displayable Colours 16.7 Million Projection Lens F=2.41 ~ 2.55, f=21.79 ~ 23.99mm, 1.1x Manual Focus Throw Ratio 1.95 ~ 2.15:1 (Projection Distance:Image Width) Projection Distance 1.2 - 12m Image Size 0.70 - 7.70m (27.49" - 303.12") Diagonal 4:3 Horizontal Scan Rate 15 - 100kHz Vertical Scan Rate 43 - 85Hz Power Supply 100-240V, 50-60Hz with PFC Power Supply Power Consumption 260W Maximum < 10W Standby mode Operating Conditions Operating: 5 - 40 C, 80% Humidity (Max), 3000m Altitude (Max) Security One Kensington Lock Port, Password Protection Standard Accessories Lens Cover, AC Power Cord, VGA Cable, USB Cable, Full Function Remote, Batteries x 2, Quick Start Guide, CD User Manual, Warranty, WEEE Card RoHS Compliant Lamp Warranty Warranty may vary by country. Please see www.optomaeurope.com or ask your local supplier for details	Keystone Correction	± 18 Degrees Vertical
Arabic Video Compatibility PAL SECAM 576i/p, NTSC 480i/p, HD 720p/1080i Uniformity 85% Displayable Colours 16.7 Million Projection Lens F=2.41 ~ 2.55, f=21.79 ~ 23.99mm, 1.1x Manual Focus Throw Ratio 1.95 ~ 2.15:1 (Projection Distance:Image Width) Projection Distance 1.2 - 12m Image Size 0.70 - 7.70m (27.49" - 303.12") Diagonal 4:3 Horizontal Scan Rate 15 - 100kHz Vertical Scan Rate 43 - 85Hz Power Supply 100-240V, 50-60Hz with PFC Power Supply Power Consumption 260W Maximum < 10W Standby mode Operating Conditions Operating: 5 - 40 C, 80% Humidity (Max), 3000m Altitude (Max) Security One Kensington Lock Port, Password Protection Standard Accessories Lens Cover, AC Power Cord, VGA Cable, USB Cable, Full Function Remote, Batteries x 2, Quick Start Guide, CD User Manual, Warranty, WEEE Card RoHS Compliant Lamp Warranty Warranty may vary by country. Please see www.optomaeurope.com or ask your local supplier for details	On Screen Display	16 Languages: English, German, French, Italian, Spanish, Portuguese, Polish,
Video Compatibility PAL SECAM 576i/p, NTSC 480i/p, HD 720p/1080i Uniformity 85% Displayable Colours 16.7 Million Projection Lens F=2.41 ~ 2.55, f=21.79 ~ 23.99mm, 1.1x Manual Focus Throw Ratio 1.95 ~ 2.15:1 (Projection Distance:Image Width) Projection Distance 1.2 - 12m Image Size 0.70 - 7.70m (27.49" - 303.12") Diagonal 4:3 Horizontal Scan Rate 15 - 100kHz Vertical Scan Rate 43 - 85Hz Power Supply 100-240V, 50-60Hz with PFC Power Supply Power Consumption 260W Maximum < 10W Standby mode Operating Conditions Operating: 5 - 40 C, 80% Humidity (Max), 3000m Altitude (Max) Security One Kensington Lock Port, Password Protection Standard Accessories Lens Cover, AC Power Cord, VGA Cable, USB Cable, Full Function Remote, Batteries x 2, Quick Start Guide, CD User Manual, Warranty, WEEE Card RoHS Compliant Lamp Warranty Warranty may vary by country. Please see www.optomaeurope.com or ask your local supplier for details		Dutch, Russian, Finnish, Swedish, Greek, Norwegian/Danish, Hungarian, Czech &
Uniformity 85% Displayable Colours 16.7 Million Projection Lens F=2.41 ~ 2.55, f=21.79 ~ 23.99mm, 1.1x Manual Focus Throw Ratio 1.95 ~ 2.15:1 (Projection Distance:Image Width) Projection Distance 1.2 - 12m Image Size 0.70 - 7.70m (27.49" - 303.12") Diagonal 4:3 Horizontal Scan Rate 15 - 100kHz Vertical Scan Rate 43 - 85Hz Power Supply 100-240V, 50-60Hz with PFC Power Supply Power Consumption 260W Maximum < 10W Standby mode Operating Conditions Operating: 5 - 40 C, 80% Humidity (Max), 3000m Altitude (Max) Security One Kensington Lock Port, Password Protection Standard Accessories Lens Cover, AC Power Cord, VGA Cable, USB Cable, Full Function Remote, Batteries x 2, Quick Start Guide, CD User Manual, Warranty, WEEE Card RoHS Compliant Lamp Warranty G months or 1000 hours - whichever is soonest Warranty Warranty may vary by country. Please see www.optomaeurope.com or ask your local supplier for details		Arabic
Displayable Colours Projection Lens F=2.41 ~ 2.55, f=21.79 ~ 23.99mm, 1.1x Manual Focus Throw Ratio 1.95 ~ 2.15:1 (Projection Distance:Image Width) Projection Distance 1.2 - 12m Image Size 0.70 - 7.70m (27.49" - 303.12") Diagonal 4:3 Horizontal Scan Rate 15 - 100kHz Vertical Scan Rate 43 - 85Hz Power Supply 100-240V, 50-60Hz with PFC Power Supply Power Consumption 260W Maximum < 10W Standby mode Operating Conditions Operating: 5 - 40 C, 80% Humidity (Max), 3000m Altitude (Max) Security One Kensington Lock Port, Password Protection Standard Accessories Lens Cover, AC Power Cord, VGA Cable, USB Cable, Full Function Remote, Batteries x 2, Quick Start Guide, CD User Manual, Warranty, WEEE Card RoHS Compliant Lamp Warranty Warranty may vary by country. Please see www.optomaeurope.com or ask your local supplier for details	Video Compatibility	PAL SECAM 576i/p, NTSC 480i/p, HD 720p/1080i
Projection Lens F=2.41 ~ 2.55, f=21.79 ~ 23.99mm, 1.1x Manual Focus Throw Ratio 1.95 ~ 2.15:1 (Projection Distance:Image Width) Projection Distance 1.2 - 12m Image Size 0.70 - 7.70m (27.49" - 303.12") Diagonal 4:3 Horizontal Scan Rate 15 - 100kHz Vertical Scan Rate 43 - 85Hz Power Supply 100-240V, 50-60Hz with PFC Power Supply Power Consumption 260W Maximum < 10W Standby mode Operating Conditions Operating: 5 - 40 C, 80% Humidity (Max), 3000m Altitude (Max) Security One Kensington Lock Port, Password Protection Standard Accessories Lens Cover, AC Power Cord, VGA Cable, USB Cable, Full Function Remote, Batteries x 2, Quick Start Guide, CD User Manual, Warranty, WEEE Card RoHS Compliant Lamp Warranty G months or 1000 hours - whichever is soonest Warranty Warranty may vary by country. Please see www.optomaeurope.com or ask your local supplier for details	Uniformity	85%
Throw Ratio 1.95 ~ 2.15:1 (Projection Distance:Image Width) Projection Distance 1.2 - 12m Image Size 0.70 - 7.70m (27.49" - 303.12") Diagonal 4:3 Horizontal Scan Rate 15 - 100kHz Vertical Scan Rate 43 - 85Hz Power Supply 100-240V, 50-60Hz with PFC Power Supply Power Consumption 260W Maximum < 10W Standby mode Operating Conditions Operating: 5 - 40 C, 80% Humidity (Max), 3000m Altitude (Max) Security One Kensington Lock Port, Password Protection Standard Accessories Lens Cover, AC Power Cord, VGA Cable, USB Cable, Full Function Remote, Batteries x 2, Quick Start Guide, CD User Manual, Warranty, WEEE Card RoHS Compliant G months or 1000 hours - whichever is soonest Warranty Warranty may vary by country. Please see www.optomaeurope.com or ask your local supplier for details	Displayable Colours	16.7 Million
Projection Distance Image Size 0.70 - 7.70m (27.49" - 303.12") Diagonal 4:3 Horizontal Scan Rate 15 - 100kHz Vertical Scan Rate 43 - 85Hz Power Supply 100-240V, 50-60Hz with PFC Power Supply Power Consumption 260W Maximum < 10W Standby mode Operating Conditions Operating: 5 - 40 C, 80% Humidity (Max), 3000m Altitude (Max) Security One Kensington Lock Port, Password Protection Standard Accessories Lens Cover, AC Power Cord, VGA Cable, USB Cable, Full Function Remote, Batteries x 2, Quick Start Guide, CD User Manual, Warranty, WEEE Card RoHS Compliant Lamp Warranty 6 months or 1000 hours - whichever is soonest Warranty Warranty may vary by country. Please see www.optomaeurope.com or ask your local supplier for details	Projection Lens	F=2.41 ~ 2.55, f=21.79 ~ 23.99mm, 1.1x Manual Focus
Image Size 0.70 - 7.70m (27.49" - 303.12") Diagonal 4:3 Horizontal Scan Rate 15 - 100kHz Vertical Scan Rate 43 - 85Hz Power Supply 100-240V, 50-60Hz with PFC Power Supply Power Consumption 260W Maximum < 10W Standby mode Operating Conditions Operating: 5 - 40 C, 80% Humidity (Max), 3000m Altitude (Max) Security One Kensington Lock Port, Password Protection Standard Accessories Lens Cover, AC Power Cord, VGA Cable, USB Cable, Full Function Remote, Batteries x 2, Quick Start Guide, CD User Manual, Warranty, WEEE Card RoHS Compliant Lamp Warranty G months or 1000 hours - whichever is soonest Warranty Warranty may vary by country. Please see www.optomaeurope.com or ask your local supplier for details	Throw Ratio	1.95 ~ 2.15:1 (Projection Distance:Image Width)
Horizontal Scan Rate Vertical Scan Rate 43 - 85Hz Power Supply 100-240V, 50-60Hz with PFC Power Supply Power Consumption 260W Maximum < 10W Standby mode Operating Conditions Operating: 5 - 40 C, 80% Humidity (Max), 3000m Altitude (Max) Security One Kensington Lock Port, Password Protection Standard Accessories Lens Cover, AC Power Cord, VGA Cable, USB Cable, Full Function Remote, Batteries x 2, Quick Start Guide, CD User Manual, Warranty, WEEE Card RoHS Compliant Lamp Warranty G months or 1000 hours - whichever is soonest Warranty Warranty may vary by country. Please see www.optomaeurope.com or ask your local supplier for details	Projection Distance	1.2 - 12m
Vertical Scan Rate 43 - 85Hz Power Supply 100-240V, 50-60Hz with PFC Power Supply Power Consumption 260W Maximum < 10W Standby mode Operating Conditions Operating: 5 - 40 C, 80% Humidity (Max), 3000m Altitude (Max) Security One Kensington Lock Port, Password Protection Standard Accessories Lens Cover, AC Power Cord, VGA Cable, USB Cable, Full Function Remote, Batteries x 2, Quick Start Guide, CD User Manual, Warranty, WEEE Card RoHS Compliant Lamp Warranty 6 months or 1000 hours - whichever is soonest Warranty wary by country. Please see www.optomaeurope.com or ask your local supplier for details	Image Size	0.70 - 7.70m (27.49" - 303.12") Diagonal 4:3
Power Supply Power Consumption 260W Maximum < 10W Standby mode Operating Conditions Operating: 5 - 40 C, 80% Humidity (Max), 3000m Altitude (Max) Security One Kensington Lock Port, Password Protection Standard Accessories Lens Cover, AC Power Cord, VGA Cable, USB Cable, Full Function Remote, Batteries x 2, Quick Start Guide, CD User Manual, Warranty, WEEE Card RoHS Compliant Lamp Warranty 6 months or 1000 hours - whichever is soonest Warranty Warranty may vary by country. Please see www.optomaeurope.com or ask your local supplier for details	Horizontal Scan Rate	15 - 100kHz
Power Consumption 260W Maximum < 10W Standby mode Operating Conditions Operating: 5 - 40 C, 80% Humidity (Max), 3000m Altitude (Max) Security One Kensington Lock Port, Password Protection Standard Accessories Lens Cover, AC Power Cord, VGA Cable, USB Cable, Full Function Remote, Batteries x 2, Quick Start Guide, CD User Manual, Warranty, WEEE Card RoHS Compliant Lamp Warranty 6 months or 1000 hours - whichever is soonest Warranty wary by country. Please see www.optomaeurope.com or ask your local supplier for details	Vertical Scan Rate	43 - 85Hz
Operating Conditions Operating: 5 - 40 C, 80% Humidity (Max), 3000m Altitude (Max) Security One Kensington Lock Port, Password Protection Standard Accessories Lens Cover, AC Power Cord, VGA Cable, USB Cable, Full Function Remote, Batteries x 2, Quick Start Guide, CD User Manual, Warranty, WEEE Card RoHS Compliant Lamp Warranty 6 months or 1000 hours - whichever is soonest Warranty Warranty may vary by country. Please see www.optomaeurope.com or ask your local supplier for details	Power Supply	100-240V, 50-60Hz with PFC Power Supply
Security One Kensington Lock Port, Password Protection Lens Cover, AC Power Cord, VGA Cable, USB Cable, Full Function Remote, Batteries x 2, Quick Start Guide, CD User Manual, Warranty, WEEE Card RoHS Compliant Lamp Warranty 6 months or 1000 hours - whichever is soonest Warranty Warranty may vary by country. Please see www.optomaeurope.com or ask your local supplier for details	Power Consumption	260W Maximum < 10W Standby mode
Standard Accessories Lens Cover, AC Power Cord, VGA Cable, USB Cable, Full Function Remote, Batteries x 2, Quick Start Guide, CD User Manual, Warranty, WEEE Card RoHS Compliant Lamp Warranty 6 months or 1000 hours - whichever is soonest Warranty Warranty may vary by country. Please see www.optomaeurope.com or ask your local supplier for details	Operating Conditions	Operating: 5 - 40 C, 80% Humidity (Max), 3000m Altitude (Max)
ies x 2, Quick Start Guide, CD User Manual, Warranty, WEEE Card RoHS Compliant Lamp Warranty 6 months or 1000 hours - whichever is soonest Warranty Warranty may vary by country. Please see www.optomaeurope.com or ask your local supplier for details	Security	One Kensington Lock Port, Password Protection
RoHS Compliant Lamp Warranty 6 months or 1000 hours - whichever is soonest Warranty Warranty may vary by country. Please see www.optomaeurope.com or ask your local supplier for details	Standard Accessories	Lens Cover, AC Power Cord, VGA Cable, USB Cable, Full Function Remote, Batter-
Lamp Warranty 6 months or 1000 hours - whichever is soonest Warranty Warranty may vary by country. Please see www.optomaeurope.com or ask your local supplier for details		ies x 2, Quick Start Guide, CD User Manual, Warranty, WEEE Card
Warranty may vary by country. Please see www.optomaeurope.com or ask your local supplier for details	RoHS	Compliant
local supplier for details	Lamp Warranty	6 months or 1000 hours - whichever is soonest
	Warranty	Warranty may vary by country. Please see www.optomaeurope.com or ask your
Colour Guarantee 10 Years		local supplier for details
	Colour Guarantee	10 Years

EP720 Projection Distance 1.2 - 12m (16:10 Aspect Ratio)									
Projection Distance (m)	Max. Horizontal Image size (m)	Min. Horizontal Image size (m)	Max. Screen Height (m)	Min. Screen Height (m)	Max. Diagonal Image Size (m)	Max. Diagonal Image Size (Inch)	Max. Image Offset (m)		
1.20	0.80	0.67	0.50	0.42	0.94	37.14	0.14		
2.00	1.33	1.11	0.83	0.69	1.57	61.90	0.23		
2.50	1.67	1.39	1.04	0.87	1.97	77.38	0.29		
3.00	2.00	1.67	1.25	1.04	2.36	92.85	0.35		
4.00	2.67	2.22	1.67	1.39	3.14	123.81	0.47		
5.00	3.33	2.78	2.08	1.74	3.93	154.76	0.58		
6.00	4.00	3.33	2.50	2.08	4.72	185.71	0.70		
7.00	4.67	3.89	2.92	2.43	5.50	216.66	0.82		
8.00	5.33	4.44	3.33	2.78	6.29	247.61	0.93		
9.00	6.00	5.00	3.75	3.13	7.08	278.56	1.05		
10.00	6.67	5.56	4.17	3.47	7.86	309.51	1.17		
11.00	7.33	6.11	4.58	3.82	8.65	340.47	1.28		
12.00	8.00	6.67	5.00	4.17	9.43	371.42	1.40		

EP720 is capable of 16:9 & 4:3 aspect ratio projection. When projecting a 16:9 & 4:3 image the image sizes, screen height and offset information will differ to that of above

Optoma recommends Panoview screens

Panoview www.panoview.eu

Optoma Europe Ltd.

42 Caxton Way, Watford Business Park, Watford, Hertfordshire, UK. WD18 8QZ