

# PLC-XW57

XGA Ultraportable Multimedia Projector



### ULTRACOMPACT, EASY QUICK POWER OFF AND GO

The compact and lightweight body (13.0" x 3.2" x 9.3" and 6.4lbs.) offers great portability. After your presentation, no need to wait for the projector to cool down. You can disconnect the power cord right after your presentation. The best choice for your business presentation.

### D-SUB15 INPUT AND MONITOR OUT

The PLC-XW57 offers excellent flexibility via 2 D-Sub 15 input and 1 output (common) terminal. Using an optional adapter cable, the D-Sub 15 input can even accept component video signals. The D-Sub 15 output terminal can be used with monitor output for greater flexibility.

### DIGITAL KEYSTONE CORRECTION

To compensate for keystone (trapezoidal) picture distortion, the PLC-XW57 provides vertical keystone correction with a correction range up to ±20 degrees.

### WIDE-RANGE 1.2x ZOOM LENS

Equipped with a high quality short throw lens with 1.2X optical zoom, the PLC-XW57 can throw a crisp, bright 100-inch diagonal image from merely 11.8 feet away.

### BLACKBOARD (GREEN) MODE

For more effective presentations in rooms with dark-surfaced walls, This mode lets you use a blackboard as a projection screen. It adjusts the colors to make images look similar to those projection to an ordinary white screen.

### SECURITY FEATURES

The PIN code lock function prevents others from operating the projector without inputting the correct PIN code. The key lock function, which is set from the operation menu, locks the operation of the top control and remote control buttons.

### USER-SPECIFIED START-UP SCREEN

To create a more professional presentation, logo and image files may be captured for display during the projector's start-up countdown sequence.



PRESENTATION TECHNOLOGIES  
 21605 Plummer Street  
 Chatsworth, CA 91311  
 Ph: 888-337-1215 (toll-free)  
 Fax 818.717.2719  
 www.sanyoprojectors.com

## Specifications

Resolution	XGA (1024 x 768)	
Brightness (typical)	2000 ANSI Lumens	
Contrast Ratio	400 : 1	
Panel System	0.6" TFT P-Si x 3 with Micro Lens	
Number of Pixels	2,359,296 (786,432 x 3)	
Aspect Ratio	4 : 3	
Uniformity	85% (corner to center)	
Scanning Frequency	H Sync : 15-100kHz, V Sync : 50-100Hz	
Dot Clock	110MHz	
Computer Compatibility	UXGA / WXGA / SXGA+ / XGA / SVGA / VGA / MAC	
HDTV Signals	480i / 480p / 575i / 575p / 720p / 1035i / 1080i	
Color System	NTSC / PAL / SECAM / NTSC4.43 / PAL-M / PAL-N	
Projection Lens	F 1.65 - 1.83 / f0.89 - 1.062"	
Zoom / Focus	1 : 1.2 Manual driven	
Image Size (diagonal)	40" - 300"	
Throw Distance	4.6' - 43.3'	
Throw Ratio	1.78 - 2.15:1	
Up/Down Ratio	6 : 1	
Digital Keystone	Vertical : +/- 20%	
Digital Zoom	16x - 1/4 x	
Projection Lamp(s)	200W UHP	
Voltage	100 - 240V	
Power Consumption	250W Normal, 210W Eco	
Fan Noise	26 dB(Eco)	
BTU Rating	853 (Normal)	
Speaker Output	1W ( Mono)	
Weight	6.4 lbs.	
Dimensions	13.0" x 3.2" x 9.3" (not including protrusion)	
Input1	PC or Video	Computer 1 : D-Sub 15 (2) S-Video : D-Sub15 with Optional S-Video Cable (2) Component : D-Sub15 with Optional Component Cable (2) Audio : Stereo Mini-jack (5)
Input2	PC or Video (Common to Monitor Out)	Computer 2 : D-Sub15 (3) S-Video : D-Sub15 with Optional S-Video Cable (3) Component : D-Sub15 with Optional Component Cable (3)
Input3	Video	Composite : RCA x 1 (6) Audio : RCA x 2 (R & L/mono) (7)
Monitor Out (Common)		D-Sub15 (Monitor Out from Input1 (2)) (3)
Variable Audio Out		Stereo Mini-jack (Audio Out from Audio In (5) or (7)) (4)
Communication Terminals		Service Port : Mini Din 8-pin (RS232C) (1)
Included Accessories		1) Owner's Manual (CD-ROM) 2) AC code UL 3P Plug Type 3) PC Cable (Dsub15-Dsub 15) 4) Remote Control 5) AA Battery x 2
Optional Accessories		Component Cable : POA-CA-COMPVGA S-Video Cable : POA-CA-VGAS Serial control Cable (RS232C) : POA-MCSRL Leaser RC Kit : POA-RCKIT03 Mouse RC Kit : POA-RCKIT04 Soft Carrying case : POA-CAC-VCL2 Replacement Lamp : 610 340 0341 Replacement Remote : 645 090 9498

Because its products are subject to continuous improvement, SANYO reserves the right to modify product design and specifications without notice and without incurring any obligations.

