



LEICA PRADOVIT D-1200

Technical Data



Projector	LEICA PRADOVIT D-1200
Projector type	WUXGA DLP digital projector
Display	
Technology	0.98" DMD chip
Resolution	1920 x 1200 pixels = WUXGA
Aspect ratio	16:10
Brightness	2000 ANSI Lumen
Contrast ratio	>2500:1
Lens and lamp	
Leica lens	1.6–2.0:1 zoom lens (manual)
Projection distance	1–15 m
Image size (width/diagonal)	approx. 0.5–9 m / 0.6–11 m
Optical lens shift	approx. 120% vertical
Lamp	220W FusionPlus VIDU UHP from Philips
Lamp life	3000 hours in standard mode / 4000 hours in economy mode
Connectionports	
Video	HDMI 1.3a (HDCP), DVI (HDCP), 1x RCA (YPbPr, YCbCr) (Component Video), 1x S-Video, 1x RCA (Composite Video), HDD-15 (RGBHV, RGBS, RGSB, YUV).
Control	LAN (TCP/IP), RS232, USB, Infrared remote control with laser pointer, Quick-access infrared remote control.
Noise level	<28 dB(A) in standard mode
Dimensions (D x W x H)	234 x 278 x 94 mm
Weight	3,5 kg with lens
Scope of delivery	Transport case, 2 IR remote controls, basic cable set (mains cable VGA, DVI-D, S-Video, Component, Audio/Remote), Startup-Software incl. Demo-Show and Wings-Platinum Basis-Version.
Power supply	90–240V AC, 50/60 Hz, <350W

Projection chart

Aspect ratio (16:10)			Projection distance	
Width (m)	Height (m)	Diagonal (m)	WW (m)	Tele (m)
0,5	0,31	0,59	0,80	1,00
0,8	0,50	0,94	1,28	1,60
1,0	0,63	1,18	1,60	2,00
1,2	0,75	1,42	1,92	2,40
1,5	0,94	1,77	2,40	3,00
2,0	1,25	2,36	3,20	4,00
2,5	1,56	2,95	4,00	5,00
3,0	1,88	3,54	4,80	6,00
3,5	2,19	4,13	5,60	7,00
4,0	2,50	4,72	6,40	8,00
4,5	2,81	5,31	7,20	9,00
5,0	3,13	5,90	8,00	10,00
6,0	3,75	7,08	9,60	12,00
7,0	4,38	8,25	11,20	14,00
7,5	4,69	8,84	12,00	15,00
8,0	5,00	9,43	12,80	
9,0	5,63	10,61	14,40	
9,5	5,94	11,20	15,20	