

PLC-WXU30/WXU30A

WXGA Ultraportable Multimedia Projector



FITS A VARIETY OF APPLICATION SITUATIONS

Offering a wide XGA full 1280 x 800 (16:10) resolution, the PLC-WXU30/WXU30A makes it possible to project high-quality HD images from virtually any location. At 3700 lumens, this extremely bright, yet compact, projector is equally comfortable entertaining the whole family with exquisite HD images from cable/satellite or DVD sources as it is delivering a PC-based business presentation to a select audience in the work place. It also is ideal for projecting larger-than-life video from today's best game consoles.

FITS ANY SET-UP SITUATION

A flexible zoom lens allows for projecting in both short and long distances, from 3-feet to 39.7-feet, to be exact. Keystone correction adjusts for 40 degrees up or down for fast and easy set up.

NETWORKING CAPABILITY

The PLC-WXU30/WXU30A are equipped with SANYO's exclusive PJ Network Interface for wired and wireless networking, a common feature among SANYO's extensive line of commercial projectors. Networking allows the monitoring of projector functions and operation from a long distance via a web browser. Emails can be sent automatically to report operating status. The wireless interface is compatible with IEEE802.11b/g standards, offering transfer speeds up to 54Mbps and providing WEP 64/128-bit security.

POWER OFF AND GO AND ANTI-THEFT ALARM

The units are designed with the Easy-Off function. It's possible to remove the power cord without waiting for the machine to cool down - convenient for quickly clearing away a temporary set-up. As this projector is small and light, a pin code lock is provided to prevent theft. When activated, a loud audio alarm goes off to scare away would-be thieves.

VERSATILE INPUTS

The PLC- WXU30/WXU30A offers excellent flexibility via DVI-I and D-Sub15 inputs. It even has component video inputs. Additionally, there is a D-Sub-15 terminal for a monitor output, achieving greater programming flexibility.

Specifications

| | |
|-----------------------------|---|
| Resolution | WXGA (1280 x 800) |
| Brightness (typical) | 3700 ANSI Lumens |
| Uniformity | 85 % |
| LCD Panel System | 0.7" TFT Poly x3 |
| Number of Pixels | 3,072,000 (1,024,000 x 3) |
| Contrast Ratio | 500:1 (lamp mode "Auto", image mode "Dynamic") |
| Projection Image (diagonal) | 40"-300" |
| Aspect Ratio | 16:10 |
| Throw Distance | 3.2'-39.7' |
| Zoom/Focus | Manual (1:1.6 zoom) |
| Up/Down Ratio | 49:1 |
| Digital Keystone Correction | Vert. +/- 40° |
| Projection System | Dichroic mirror & 4P prism system w/ PBS |
| Projection Lens | F1.7-2.5 / f0.76"-1.19" |
| Lens Throw Ratio | 1.16 - 1.86 :1 |
| Projection Lamp | 275W |
| Scanning Frequency | H 15-100kHz; V 50-100Hz |
| Dot Clock | 140 MHz |
| Color System | NTSC/PAL/SECAM/NTSC4.43/PAL-M&N |
| Computer Compatibility | UXGA, WXGA, SXGA, XGA, SVGA, VGA, MAC analog |
| Sound Output | One-piece, 1-watt Mono |
| Voltage | 100-120/200-240V AC; 50/60/Hz (auto sense/select) |
| BTU Rating | 1242 |
| dB Rating | 30dBa(eco mode) |
| Power Consumption | 364W |
| Dimensions (WxHxD) | 13.15" x3.07"x10.12" (not including adjustable feet) |
| Net Weight | 7.9 lbs. |
| User Maintenance | Clean air filters, replace lamp assembly |
| PC Input Terminals | DVI-I x 1 (w/HDCP) • D-Sub15 x 1 • Audio x 1 (stereo mini-jack : common) |
| Video Input Terminals | Composite video (RCA x 1) • S-Video (mini-Din 4-pin) • R & L/mono audio (RCA x 2) • Component video (D-Sub15 input w/optional cable) • Audio for component video (stereo mini-jack) |
| Output Terminals | D-Sub15 x 1 (monitor out) • Variable audio from PC audio input or Video audio input (stereo mini-jack) |
| Service Port Terminal | Mini Din 8-pin |
| Mouse Control Port | USB type B x 1 |
| Other Terminals | USB for mouse control • RJ45 for wired LAN • SD card |
| Included Accessories | Wireless/Wired remote control with mouse pad and laser pointer • 2 AAA batteries • Owner's manual (quick manual & CD-ROM) • VGA cable • PIN code label • AC power supply cord • CD-ROM(application soft) • Alarm protected seal • Soft carry bag • Strap & Screw for sends cap |
| Optional Accessories | • 610 333 9740 – Replacement lamp • 645 093 6937 – Replacement remote • POA-CACOMPVGA – Component video cable • POA-MCSRL – Serial control cable |
| Warranty | Three years parts and labor; 90 days Initial lamp; Quick repair program under warranty |

Because its products are subject to continuous improvement, SANYO reserves the right to modify product design and specifications without notice and without incurring any obligations.



PRESENTATION TECHNOLOGIES



21605 Plummer Street
Chatsworth, CA 91311
Ph: 888-337-1215 (toll-free)
Fax 818.717.2719
www.sanyoprojectors.com



Remote Control
645 093 6937



Rear Back Panel