



New



- Connection Terminals**
- 1 S-Video/Video
  - 2 PC/Component video input-1
  - 3 Remote-1
  - 4 PC/Component video input-2
  - 5 Remote-2 (I/O)
  - 6 HDMI
  - 7 DVI-D
  - 8 Serial RS-232C (I/O)
  - 9 3G-SDI (UD8400U only)
  - 10 LAN (RJ-45)
  - 11 Power in (3-pin with earth terminal)
  - 12 Main power switch O:Off I:On

Dimensions (unit: mm)



\* The lens focal point is the default set at the time of shipment from the factory.

Specifications

|                         |                                                                                                                                                                                                                                                                                                                        |             |                                                                                     |      |                                                                                     |        |             |     |             |  |                                                                                                                                                                                             |  |           |      |                   |        |             |     |             |  |  |
|-------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------|-------------------------------------------------------------------------------------|------|-------------------------------------------------------------------------------------|--------|-------------|-----|-------------|--|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|-----------|------|-------------------|--------|-------------|-----|-------------|--|--|
| Model                   | UD8400U / UD8400LU                                                                                                                                                                                                                                                                                                     |             | WD8200U / WD8200LU                                                                  |      | XD8100U / XD8100LU                                                                  |        |             |     |             |  |                                                                                                                                                                                             |  |           |      |                   |        |             |     |             |  |  |
| Display technology      | 0.67" 1-Chip DMD                                                                                                                                                                                                                                                                                                       |             | 0.65" 1-Chip DMD                                                                    |      | 0.7" 1-Chip DMD                                                                     |        |             |     |             |  |                                                                                                                                                                                             |  |           |      |                   |        |             |     |             |  |  |
| Resolution              | 1920 x 1200 (Total 2,304,000 pixels)                                                                                                                                                                                                                                                                                   |             | 1280 x 800 (Total 1,024,000 pixels)                                                 |      | 1024 x 768 (Total 786,432 pixels)                                                   |        |             |     |             |  |                                                                                                                                                                                             |  |           |      |                   |        |             |     |             |  |  |
| Brightness              | Dual lamp: 6500 lm<br>Single lamp: 3250 lm                                                                                                                                                                                                                                                                             |             | Dual lamp: 6500 lm<br>Single lamp: 3250 lm                                          |      | Dual lamp: 7000 lm<br>Single lamp: 3500 lm                                          |        |             |     |             |  |                                                                                                                                                                                             |  |           |      |                   |        |             |     |             |  |  |
| Contrast ratio          | 2000 : 1 (on/off)                                                                                                                                                                                                                                                                                                      |             |                                                                                     |      |                                                                                     |        |             |     |             |  |                                                                                                                                                                                             |  |           |      |                   |        |             |     |             |  |  |
| Projection lens         | f=24.5-33.1mm, F = 2.0-2.4                                                                                                                                                                                                                                                                                             |             |                                                                                     |      |                                                                                     |        |             |     |             |  |                                                                                                                                                                                             |  |           |      |                   |        |             |     |             |  |  |
| Zoom / focus            | Powered focus / zoom (zoom ratio 1.35 : 1)                                                                                                                                                                                                                                                                             |             |                                                                                     |      |                                                                                     |        |             |     |             |  |                                                                                                                                                                                             |  |           |      |                   |        |             |     |             |  |  |
| Picture size            | 40" - 300"                                                                                                                                                                                                                                                                                                             |             |                                                                                     |      |                                                                                     |        |             |     |             |  |                                                                                                                                                                                             |  |           |      |                   |        |             |     |             |  |  |
| Throw ratio             | 4.65-2.27                                                                                                                                                                                                                                                                                                              |             | 1.74-2.39                                                                           |      | 1.73-2.36                                                                           |        |             |     |             |  |                                                                                                                                                                                             |  |           |      |                   |        |             |     |             |  |  |
| Source lamp             | <table><tr><td></td><td>Lamp mode</td><td>hour</td></tr><tr><td rowspan="2">Dual (330W x 2)</td><td>Normal</td><td>2,000 hours</td></tr><tr><td>Low</td><td>4,000 hours</td></tr></table>                                                                                                                              |             | Lamp mode                                                                           | hour | Dual (330W x 2)                                                                     | Normal | 2,000 hours | Low | 4,000 hours |  | <table><tr><td></td><td>Lamp mode</td><td>hour</td></tr><tr><td rowspan="2">Single (330W x 1)</td><td>Normal</td><td>4,000 hours</td></tr><tr><td>Low</td><td>8,000 hours</td></tr></table> |  | Lamp mode | hour | Single (330W x 1) | Normal | 4,000 hours | Low | 8,000 hours |  |  |
|                         | Lamp mode                                                                                                                                                                                                                                                                                                              | hour        |                                                                                     |      |                                                                                     |        |             |     |             |  |                                                                                                                                                                                             |  |           |      |                   |        |             |     |             |  |  |
| Dual (330W x 2)         | Normal                                                                                                                                                                                                                                                                                                                 | 2,000 hours |                                                                                     |      |                                                                                     |        |             |     |             |  |                                                                                                                                                                                             |  |           |      |                   |        |             |     |             |  |  |
|                         | Low                                                                                                                                                                                                                                                                                                                    | 4,000 hours |                                                                                     |      |                                                                                     |        |             |     |             |  |                                                                                                                                                                                             |  |           |      |                   |        |             |     |             |  |  |
|                         | Lamp mode                                                                                                                                                                                                                                                                                                              | hour        |                                                                                     |      |                                                                                     |        |             |     |             |  |                                                                                                                                                                                             |  |           |      |                   |        |             |     |             |  |  |
| Single (330W x 1)       | Normal                                                                                                                                                                                                                                                                                                                 | 4,000 hours |                                                                                     |      |                                                                                     |        |             |     |             |  |                                                                                                                                                                                             |  |           |      |                   |        |             |     |             |  |  |
|                         | Low                                                                                                                                                                                                                                                                                                                    | 8,000 hours |                                                                                     |      |                                                                                     |        |             |     |             |  |                                                                                                                                                                                             |  |           |      |                   |        |             |     |             |  |  |
| Computer compatibility  | Resolution: 640 x 400 - 1920 x 1200<br>True: 1920 x 1200,<br>Sync-on-Green available                                                                                                                                                                                                                                   |             | Resolution: 640 x 400 - 1920 x 1200<br>True: 1280 x 800,<br>Sync-on-Green available |      | Resolution: 640 x 400 - 1920 x 1200<br>True: 1024 x 768,<br>Sync-on-Green available |        |             |     |             |  |                                                                                                                                                                                             |  |           |      |                   |        |             |     |             |  |  |
| Video compatibility     | NTSC / NTSC 4.43 / PAL (including PAL-M, N) / SECAM / PAL-60<br>Component video: 480i/p (525i/p), 576i/p (625i/p), 720p (750p 50/60Hz), 1080i (1125i 50/60Hz), 1080p (1125p 50/60Hz)<br>SCART (RGB + 1V sync, only mini D-sub 15-pin Terminal)                                                                         |             |                                                                                     |      |                                                                                     |        |             |     |             |  |                                                                                                                                                                                             |  |           |      |                   |        |             |     |             |  |  |
| Input terminals         | PC: 5 BNC x 1, mini D-sub 15-pin x 1, DVI-D (with HDCP) x 1<br>Video: BNC x 1, S-Video (4-pin) x 1, HDMI (Ver 1.3, Deep Color) x 1<br>3G-SDI x 1 (UD8400U only)                                                                                                                                                        |             |                                                                                     |      |                                                                                     |        |             |     |             |  |                                                                                                                                                                                             |  |           |      |                   |        |             |     |             |  |  |
| Communication terminals | LAN (RJ-45): x 1 (projector control), SERIAL (in): D-sub 9-pin (male) x 1 (direct command is available.), SERIAL (out): D-sub 9-pin (male) x 1 (direct command is available.)<br>Wired remote (in): x 1 (φ3.5mm stereo mini jack), Wired remote (out): x 1 (φ3.5mm stereo mini jack), Remote: D-sub 9-pin (female) x 1 |             |                                                                                     |      |                                                                                     |        |             |     |             |  |                                                                                                                                                                                             |  |           |      |                   |        |             |     |             |  |  |
| Dimensions (W x H x D)  | 19.3" x 7.9" x 16.6" (exclude detachable terminal cover and protrusion)                                                                                                                                                                                                                                                |             |                                                                                     |      |                                                                                     |        |             |     |             |  |                                                                                                                                                                                             |  |           |      |                   |        |             |     |             |  |  |
| Weight                  | 35.3 lbs (exclude detachable terminal cover)                                                                                                                                                                                                                                                                           |             |                                                                                     |      |                                                                                     |        |             |     |             |  |                                                                                                                                                                                             |  |           |      |                   |        |             |     |             |  |  |
| Power supply            | AC 100 - 240V, 50/60Hz                                                                                                                                                                                                                                                                                                 |             |                                                                                     |      |                                                                                     |        |             |     |             |  |                                                                                                                                                                                             |  |           |      |                   |        |             |     |             |  |  |
| Included Accessories    | AC Power Cable, RGB cable, RS-232C cable, Terminal-Cover, Remote Unit (incl. Battery), User Manual CD, Safety Manual, Labels for ceiling mount usage                                                                                                                                                                   |             |                                                                                     |      |                                                                                     |        |             |     |             |  |                                                                                                                                                                                             |  |           |      |                   |        |             |     |             |  |  |
| Warranty                | 3-Years or 10,000 hours (whichever comes first) Limited P&L Warranty, Express Replacement Assistance (ERA) during the warranty period, 1-yr or 500hrs lamp warranty (whichever comes first)                                                                                                                            |             |                                                                                     |      |                                                                                     |        |             |     |             |  |                                                                                                                                                                                             |  |           |      |                   |        |             |     |             |  |  |

\*Varies depending on condition. \*All brand names and product names are trademarks, registered trademarks or trade names of their respective holders. \*Lamp life specification is an estimate based on verification under proper conditions and is not the duration of the warranty. Lamp will shut-off automatically when usage reaches the specified estimated maximum lamp hours. Service life may vary widely depending on usage and operating environment and conditions, as well as users' adherence to the maintenance and cleaning procedures provided in the user manual. \*The above specifications are for the standard model only. Specifications are different for lens-less models. \*HDMI, the HDMI Logo, and High-Definition Multimedia Interface are trademarks or registered trademarks of HDMI Licensing LLC in the United States and other countries.



MITSUBISHI  
ELECTRIC

MULTIMEDIA DATA/VIDEO PROJECTORS

Changes for the Better



The Pinnacle of  
Digital Projectors

Image Quality, Functionality & Reliability  
– The bar has just been raised a level higher.



New

UD8400U/UD8400LU

WD8200U/WD8200LU

XD8100U/XD8100LU



for a greener tomorrow

Eco Changes is the Mitsubishi Electric Group's environmental statement, and expresses the Group's stance on environmental management. Through a wide range of businesses, we are helping contribute to the realization of a sustainable society.

MITSUBISHI DIGITAL ELECTRONICS  
AMERICA, INC.  
Presentation Products Division  
Phone: 888.307.0349  
www.mitsubishi-presentations.com



MITSUBISHI  
ELECTRIC

PRESENTATION PRODUCTS

MITSUBISHI ELECTRIC SALES  
CANADA, INC.  
Display & Imaging Solutions Division  
Phone: 905.475.7728  
www.mitsubishielectric.ca

New publication, effective November 2010.  
Specifications subject to change without notice.

for a greener tomorrow



# Brilliant Support for Various Presentation Venues

including business, education and entertainment

**New** UD8400U / UD8400LU  
WD8200U / WD8200LU  
XD8100U / XD8100LU



Imagine a long presentation or seminar in a large, bright room like a hall or auditorium. The impact of that presentation will depend on the performance of the projector you use. To ensure reliable performance, these projectors are equipped with digital light processing (DLP™) technology that reproduces high-definition images in high contrast and with superior brightness.

Built for durability and easy installation and maintenance, they last and last with minimal upkeep. The 8000 Series are equipped with dual lamps, allowing the continuous projection of images for long periods of time together with greatly increased reliability.

For installation models, our aim was to ensure an advanced level of performance essential for such units.


## High Brightness

### Powerful Large-screen Images in Well-lit Halls/Auditoriums

**7000lm High Brightness\***

The XD8100U delivers a super bright 7000 lumen\* brightness level for presenting in large meeting rooms and conference halls.

\*Maximum brightness of WD8200U and UD8400U is 6500 lumens.



## High Image Quality

### Cutting-edge Technologies Reproduce Strikingly Sharp Images

**Super Resolution**


These projectors are equipped with Mitsubishi Electric's industry-leading, advanced image-processing algorithm, which is also used in our televisions and displays. The technology analyzes blurred components in the original images, estimates high-resolution data not provided in the original signal—and corrects the image quality. The result is the projection of sharp, vivid images in fine detail.



## High Reliability


### Durable and Reliable – Continuous 24/7 Use Capability

The dual lamp system and lamp relay function enables continuous operation with no risk of the image going out. Dust resistance and cooling performance are greatly enhanced by the automated self-cleaning filter and heat-pipe cooling system technologies that have proven so successful in air conditioners, enabling extended continuous use for monitoring and digital signage applications.



**Various Lamp Relay Options**

Continuous, bright projection is ensured through the utilization of a dual-lamp light source and a variety of setting options. When two lamps are in use, one of the lamps can be rested (turned off) once a day or week. Additionally, if only one lamp is being used and it goes out, an automatic back-up function activates the other lamp—enabling nonstop projection.



**Automatic Cleaning Filter**

For 8000 Series, we've utilized the same mechanism (mesh filter and cleaning brush) that has a proven track record in Mitsubishi Electric air conditioners and air purifiers is utilized. It automatically prevents dust from building up in the radiator of the heat-pipe cooling unit for the digital micromirror device (DMD), thereby ensuring trouble-free use for extended periods of time.




**Heat-pipe Cooling System**

Compared to liquid-based cooling systems, this heat-pipe cooling system has a simplified structure and does not require a power supply, enabling a more compact design and reduced costs. Not only is it highly reliable, other benefits include exceptional energy savings, quiet operation and no concerns of liquid leakage.

**Long 4000hrs Lamp Life**

Designed with a lamp temperature controlling system, 8000 Series can support an estimated lamp rating of up to 4000 hours. The long estimated lamp life makes dramatic reductions in overall cost of ownership by decreasing the frequency of lamp replacements.



Lamp life specification is an estimate based on verification under proper conditions and is not the duration of the warranty. Lamp will shut-off automatically when usage reaches the specified estimated maximum lamp hours. Service life may vary widely depending on usage and operating environment and conditions, as well as users' adherence to the maintenance and cleaning procedures provided in the user manual.



For board room, conference hall



For Digital Signage

For Auditorium




## Advanced Features for Increased Expressiveness and Operation Ease

### Ultra Quiet 28dB Operation

Fan noise due to projector operation can be distracting during a presentation or videoconference. The 8000 Series projectors operate at a significantly low noise level of only 28dB (i.e., using a single lamp in “low lamp” mode). As a result—presentations and conferences can be held without distracting projector noise in the background.

#### Examples of Noise Levels




### Geometric Corrections

#### ■ Keystone Correction

Trapezoidal distortion caused when the projector is not positioned directly in front of the screen is corrected in both vertical and horizontal directions.


#### ■ Cornerstone Correction

Pixel conversion is used to correct trapezoidal and diagonal distortion that causes oblique images, ensuring the proper aspect ratio.



#### ■ Curved-surface Projection Correction



Projectors in the 8000 series are equipped with a distortion correction function that can be used when projecting images onto curved surfaces. Coordinates at the image's four corners are adjusted, enabling the projection angle to be adjusted at the time of angled or stacked projection. It is extremely handy for unique applications like projecting images onto special surfaces such as pillars at event sites.



### Multi-screen Solutions


#### ■ Edge Blending

Edge blending creates a seamless image by adjusting the brightness at adjoining edges when using multiple projectors side-by-side to reproduce single widescreen images. This feature can also be utilized for top-bottom projection or a combination of side-by-side and top-bottom images; for example, when images are projected from four projectors in a two-by-two arrangement.



#### ■ Color Matching

The use of multiple projectors to create a larger image can result in color variations due to slight differences in projector image processing. 8000 Series projectors are equipped with a color matching function that resolves this problem. Each projector is adjusted so that the same colors are reproduced when multiple projectors are used simultaneously.



### Interchangeable Color Wheels **Optional**

Projectors come equipped with a color wheel that accentuates brightness, and an optional color wheel for accentuating color is available. A sensor-based detection function is embedded in each unit to detect when a color wheel is replaced, at which time the color wheel index is automatically adjusted. This interchangeability enables a more appropriate expression of the images being reproduced.

### 360° Projection Capability

Images can be projected over a full 360° range along the vertical axis\* including reproduction on the ceiling or floor. The application possibilities are limitless.

\*Excluding use in high-altitude mode.



### Network Connectivity

Projectors are equipped with a RJ-45 LAN terminal for remote operation. Additionally, when used with Crestron RoomView™, integrated control of up to 250 projectors including power on/off control, message display and confirmation of lamp service hours is possible. The 8000 Series are equipped with AMX Device Discovery for simplified device management and compatible with PJLink™.



The trademark of PJLink is trademark applied for registration or registered trademark in Japan, the United States, and other countries and areas.

### Multiple Terminals

Many different interfaces are possible thanks to a variety of terminals including 3G-SDI (UD8400U only), DVI-D (HDCP), HDMI and 5BNC. A control terminal (compatible with RS-232C) is also provided for easier system integration.



(UD8400U)

### ID-compatible Remote Control

ID settings for up to 63 projectors are possible. Setting the IDs allows control of each individual projector when multiple projectors are installed.

### Power Zoom/Focus and Lens Shift

The zoom/focus and lens shift adjustment are powered by an electric motor, ensuring easy operation.

### Stand-by Wattage under 0.3W\*

Stand-by (low) mode power consumption is less than 0.3W, offering increased energy savings and further contributing to environmental preservation.

\*When in stand-by (low) mode. At this time, use of the LAN function, serial output and Remote 1 is not possible.

### Mechanical Shutter

An internal shutter in the projector enables light to be completely blocked when the projector is in Mute mode.

### Lamp Side Access

The lamps can be accessed from the side of the unit.

- OSD menu multilanguage compatibility (19 languages\*)
- 2-Screen mode (PinP: XD8100U Split: WD8200U, UD8400U)
- Direct power off
- Test pattern
- High-altitude mode (2,000 to 2,700 m)
- Closed caption support

\*Previous languages: Chinese, English, French, German, Italian, Japanese, Korean, Polish, Portuguese, Russian, Spanish, Swedish  
Languages added: Dutch, Indonesian, Malaysian, Norwegian, Thai, Turkish, Vietnamese

## UD8400/UD8400LU

Standard Lens (Aspect 16:10)

| Image (WUXGA) |       |        | Distance from Screen |     |                |     | Default Height       | Movable V Position from Default Position |      |    |             | Movable H Position from Default Position |          |    |          |             |
|---------------|-------|--------|----------------------|-----|----------------|-----|----------------------|------------------------------------------|------|----|-------------|------------------------------------------|----------|----|----------|-------------|
| Diagonal Size | Width | Height | Shortest (Wide)      |     | Longest (Tele) |     | Projected Image (HO) | H1                                       | H2   | H1 | H2          | W1                                       | W1       | W1 | V        |             |
| inch          | cm    | inch   | inch                 | cm  | inch           | cm  | inch                 | cm                                       | inch | cm | inch        | cm                                       | inch     | cm | cm       |             |
| 40            | 102   | 34     | 86                   | 21  | 54             | 55  | 1.4                  | 76                                       | 1.9  | 0  | 10 → ← 4    | 26                                       | ← 0 → 10 | 3  | ← 0 → 3  | 8 → 0 → 8   |
| 60            | 152   | 51     | 129                  | 32  | 81             | 83  | 2.1                  | 115                                      | 2.9  | 0  | 15 → ← 6    | 39                                       | ← 0 → 15 | 5  | ← 0 → 5  | 12 → 0 → 12 |
| 80            | 203   | 68     | 172                  | 42  | 108            | 112 | 2.8                  | 154                                      | 3.9  | 0  | 21 → ← 8    | 52                                       | ← 0 → 20 | 7  | ← 0 → 7  | 17 → 0 → 17 |
| 100           | 254   | 85     | 215                  | 53  | 135            | 141 | 3.6                  | 193                                      | 4.9  | 0  | 26 → 0 → 10 | 66                                       | ← 0 → 25 | 8  | ← 0 → 8  | 21 → 0 → 21 |
| 150           | 381   | 127    | 323                  | 79  | 202            | 213 | 5.4                  | 291                                      | 7.4  | 0  | 39 → 0 → 15 | 98                                       | ← 0 → 37 | 12 | ← 0 → 12 | 31 → 0 → 31 |
| 200           | 508   | 170    | 431                  | 106 | 269            | 285 | 7.2                  | 389                                      | 9.9  | 0  | 52 → 0 → 20 | 131                                      | ← 0 → 50 | 16 | ← 0 → 16 | 42 → 0 → 42 |
| 250           | 635   | 212    | 538                  | 132 | 337            | 356 | 9.1                  | -                                        | -    | 0  | 65 → 0 → 24 | 164                                      | ← 0 → 62 | 20 | ← 0 → 20 | 52 → 0 → 52 |
| 300           | 762   | 254    | 646                  | 159 | 404            | 428 | 10.9                 | -                                        | -    | 0  | 77 → 0 → 29 | 197                                      | ← 0 → 75 | 25 | ← 0 → 25 | 62 → 0 → 62 |

OL-XD2000SZ (Aspect 16:10)

| Image (WUXGA) |       |        |     | Distance from Screen |                |                      | Default Height | Movable V Position from Default Position |     |      |    | Movable H Position from Default Position |     |          |    |          |    |          |
|---------------|-------|--------|-----|----------------------|----------------|----------------------|----------------|------------------------------------------|-----|------|----|------------------------------------------|-----|----------|----|----------|----|----------|
| Diagonal Size | Width | Height |     | Shortest (Wide)      | Longest (Tele) | Projected Image (HO) |                | H1                                       | H2  | H1   | H2 | W1                                       | W1  | W1       | V  |          |    |          |
| inch          | cm    | inch   | cm  | inch                 | cm             | inch                 | cm             | inch                                     | cm  | inch | cm | inch                                     | cm  | inch     | cm |          |    |          |
| 40            | 102   | 34     | 86  | 21                   | 54             | 42                   | 1.1            | 59                                       | 1.5 | 0    | 10 | ← 0 → 4                                  | 26  | ← 0 → 10 | 3  | ← 0 → 3  | 8  | ← 0 → 8  |
| 60            | 152   | 51     | 129 | 32                   | 81             | 65                   | 1.6            | 90                                       | 2.3 | 0    | 15 | ← 0 → 6                                  | 39  | ← 0 → 15 | 5  | ← 0 → 5  | 12 | ← 0 → 12 |
| 80            | 203   | 68     | 172 | 42                   | 108            | 87                   | 2.2            | 121                                      | 3.1 | 0    | 21 | ← 0 → 8                                  | 52  | ← 0 → 20 | 7  | ← 0 → 7  | 17 | ← 0 → 17 |
| 100           | 254   | 85     | 215 | 53                   | 135            | 110                  | 2.8            | 152                                      | 3.9 | 0    | 26 | ← 0 → 10                                 | 66  | ← 0 → 25 | 8  | ← 0 → 8  | 21 | ← 0 → 21 |
| 150           | 381   | 127    | 323 | 79                   | 202            | 167                  | 4.2            | 229                                      | 5.8 | 0    | 39 | ← 0 → 15                                 | 98  | ← 0 → 37 | 12 | ← 0 → 12 | 31 | ← 0 → 31 |
| 200           | 508   | 170    | 431 | 106                  | 269            | 224                  | 5.7            | 307                                      | 7.8 | 0    | 52 | ← 0 → 20                                 | 131 | ← 0 → 50 | 16 | ← 0 → 16 | 42 | ← 0 → 42 |
| 250           | 635   | 212    | 538 | 132                  | 337            | 281                  | 7.1            | -                                        | -   | 0    | 65 | ← 0 → 24                                 | 164 | ← 0 → 62 | 20 | ← 0 → 20 | 52 | ← 0 → 52 |
| 300           | 762   | 254    | 646 | 159                  | 404            | 338                  | 8.6            | -                                        | -   | 0    | 77 | ← 0 → 29                                 | 197 | ← 0 → 75 | 25 | ← 0 → 25 | 62 | ← 0 → 62 |

OL-XD2000LZ (Aspect 16:10)

| Image (WUXGA) |       |        |                 | Distance from Screen |                      |      |      | Default Height | Movable V Position from Default Position |      |    |          | Movable H Position from Default Position |          |    |          |    |          |
|---------------|-------|--------|-----------------|----------------------|----------------------|------|------|----------------|------------------------------------------|------|----|----------|------------------------------------------|----------|----|----------|----|----------|
| Diagonal Size | Width | Height | Shortest (Wide) | Longest (Tele)       | Projected Image (HO) | H1   | H2   | H1             | H2                                       | W1   | W1 | W1       | V                                        |          |    |          |    |          |
|               | inch  | cm     |                 |                      |                      | inch | cm   | inch           | cm                                       | inch | cm | inch     | cm                                       | inch     | cm |          |    |          |
| 40            | 102   | 34     | 86              | 21                   | 54                   | -    | -    | 89             | 2.3                                      | 0    | 10 | ← 0 → 4  | 26                                       | ← 0 → 10 | 3  | ← 0 → 3  | 8  | ← 0 → 8  |
| 60            | 152   | 51     | 129             | 32                   | 81                   | 107  | 2.7  | 137            | 3.5                                      | 0    | 15 | ← 0 → 6  | 39                                       | ← 0 → 15 | 5  | ← 0 → 5  | 12 | ← 0 → 12 |
| 80            | 203   | 68     | 172             | 42                   | 108                  | 146  | 3.7  | 185            | 4.7                                      | 0    | 21 | ← 0 → 8  | 52                                       | ← 0 → 20 | 7  | ← 0 → 7  | 17 | ← 0 → 17 |
| 100           | 254   | 85     | 215             | 53                   | 135                  | 164  | 4.7  | 233            | 5.9                                      | 0    | 26 | ← 0 → 10 | 66                                       | ← 0 → 25 | 8  | ← 0 → 8  | 21 | ← 0 → 21 |
| 150           | 381   | 127    | 323             | 79                   | 202                  | 279  | 7.1  | 353            | 9.0                                      | 0    | 39 | ← 0 → 15 | 98                                       | ← 0 → 37 | 12 | ← 0 → 12 | 31 | ← 0 → 31 |
| 200           | 508   | 170    | 431             | 106                  | 269                  | 374  | 9.5  | 473            | 12.0                                     | 0    | 52 | ← 0 → 20 | 131                                      | ← 0 → 50 | 16 | ← 0 → 16 | 42 | ← 0 → 42 |
| 250           | 635   | 212    | 538             | 132                  | 337                  | 470  | 11.9 | 592            | 15.0                                     | 0    | 65 | ← 0 → 24 | 164                                      | ← 0 → 62 | 20 | ← 0 → 20 | 52 | ← 0 → 52 |
| 300           | 762   | 254    | 646             | 159                  | 404                  | 565  | 14.4 | 712            | 18.1                                     | 0    | 77 | ← 0 → 29 | 197                                      | ← 0 → 75 | 25 | ← 0 → 25 | 62 | ← 0 → 62 |

OL-XD2000TZ (Aspect 16:10)

| Image (WUXGA) |       |        | Distance from Screen |     |                | Default Height       | Movable V Position from Default Position |      |      |      | Movable H Position from Default Position |          |          |          |         |          |         |          |
|---------------|-------|--------|----------------------|-----|----------------|----------------------|------------------------------------------|------|------|------|------------------------------------------|----------|----------|----------|---------|----------|---------|----------|
| Diagonal Size | Width | Height | Shortest (Wide)      |     | Longest (Tele) | Projected Image (HO) | H1                                       | H2   | H1   | H2   | W1                                       | W1       | W1       | V        |         |          |         |          |
| inch          | cm    | inch   | inch                 | cm  | inch           | m                    | inch                                     | cm   | cm   | inch | inch                                     | cm       | cm       | cm       |         |          |         |          |
| 40            | 102   | 34     | 21                   | 54  | -              | -                    | 151                                      | 3.8  | 0    | 10   | ← 0 → 4                                  | 26       | ← 0 → 10 | 3        | ← 0 → 3 | 8        | ← 0 → 8 |          |
| 60            | 152   | 51     | 86                   | 32  | 81             | 139                  | 3.5                                      | 229  | 5.8  | 0    | 15                                       | ← 0 → 6  | 39       | ← 0 → 15 | 5       | ← 0 → 5  | 12      | ← 0 → 12 |
| 80            | 203   | 68     | 172                  | 42  | 108            | 167                  | 4.8                                      | 260  | 7.8  | 0    | 21                                       | ← 0 → 8  | 52       | ← 0 → 20 | 7       | ← 0 → 7  | 17      | ← 0 → 17 |
| 100           | 254   | 85     | 215                  | 53  | 135            | 235                  | 6.0                                      | 386  | 9.8  | 0    | 26                                       | ← 0 → 10 | 66       | ← 0 → 25 | 8       | ← 0 → 8  | 21      | ← 0 → 21 |
| 150           | 381   | 127    | 323                  | 79  | 202            | 355                  | 9.0                                      | 581  | 14.8 | 0    | 39                                       | ← 0 → 15 | 98       | ← 0 → 37 | 12      | ← 0 → 12 | 31      | ← 0 → 31 |
| 200           | 508   | 170    | 431                  | 106 | 269            | 475                  | 12.1                                     | 776  | 19.7 | 0    | 52                                       | ← 0 → 20 | 131      | ← 0 → 50 | 16      | ← 0 → 16 | 42      | ← 0 → 42 |
| 250           | 635   | 212    | 538                  | 132 | 337            | 595                  | 15.1                                     | 972  | 24.7 | 0    | 65                                       | ← 0 → 24 | 164      | ← 0 → 62 | 20      | ← 0 → 20 | 52      | ← 0 → 52 |
| 300           | 762   | 254    | 646                  | 159 | 404            | 716                  | 18.2                                     | 1167 | 29.6 | 0    | 77                                       | ← 0 → 29 | 197      | ← 0 → 75 | 25      | ← 0 → 25 | 62      | ← 0 → 62 |

OL-XD8000UZ (Aspect 16:10)


| Image (WUXGA) |       |      |        |                 | Distance from Screen |                      | Default Height | Movable V Position from Default Position |      |      |    | Movable H Position from Default Position |     |          |    |          |    |          |
|---------------|-------|------|--------|-----------------|----------------------|----------------------|----------------|------------------------------------------|------|------|----|------------------------------------------|-----|----------|----|----------|----|----------|
| Diagonal Size | Width |      | Height | Shortest (Wide) | Longest (Tele)       | Projected Image (HO) | H1             | H2                                       | H1   | H2   | W1 | W1                                       | W1  | V        |    |          |    |          |
| inch          | cm    | inch | cm     | inch            | cm                   | inch                 | cm             | inch                                     | cm   | inch | cm | inch                                     | cm  | cm       |    |          |    |          |
| 60            | 152   | 51   | 129    | 32              | 81                   | 234                  | 5.9            | 447                                      | 11.4 | 0    | 15 | ← 0 → 6                                  | 39  | ← 0 → 15 | 5  | ← 0 → 5  | 12 | ← 0 → 12 |
| 80            | 203   | 68   | 172    | 42              | 108                  | 309                  | 7.8            | 594                                      | 15.1 | 0    | 21 | ← 0 → 8                                  | 52  | ← 0 → 20 | 7  | ← 0 → 7  | 17 | ← 0 → 17 |
| 100           | 254   | 85   | 215    | 53              | 135                  | 384                  | 9.8            | 740                                      | 18.8 | 0    | 26 | ← 0 → 10                                 | 66  | ← 0 → 25 | 8  | ← 0 → 8  | 21 | ← 0 → 21 |
| 150           | 381   | 127  | 323    | 79              | 202                  | 573                  | 14.5           | 1107                                     | 28.1 | 0    | 39 | ← 0 → 15                                 | 98  | ← 0 → 37 | 12 | ← 0 → 12 | 31 | ← 0 → 31 |
| 200           | 508   | 170  | 431    | 106             | 269                  | 761                  | 19.3           | 1473                                     | 37.4 | 0    | 52 | ← 0 → 20                                 | 131 | ← 0 → 50 | 16 | ← 0 → 16 | 42 | ← 0 → 42 |
| 250           | 635   | 212  | 538    | 132             | 337                  | 950                  | 24.1           | -                                        | -    | 0    | 65 | ← 0 → 24                                 | 164 | ← 0 → 62 | 20 | ← 0 → 20 | 52 | ← 0 → 52 |
| 300           | 762   | 254  | 646    | 159             | 404                  | 1138                 | 28.9           | -                                        | -    | 0    | 77 | ← 0 → 29                                 | 197 | ← 0 → 75 | 25 | ← 0 → 25 | 62 | ← 0 → 62 |

OL-XD2000FR (Aspect 16:10)

| Image (WXGA)  |  |       | Distance from Screen |  |                      | Default Height |                |
|---------------|--|-------|----------------------|--|----------------------|----------------|----------------|
| Diagonal Size |  | Width | Height               |  | Distance from Screen |                | Default Height |
| inch          |  | cm    | cm                   |  | inch                 |                | m              |
| 40            |  | 102   | 34                   |  | 86                   |                | 21             |
| 60            |  | 152   | 51                   |  | 129                  |                | 32             |
| 80            |  | 203   | 68                   |  | 172                  |                | 42             |
| 100           |  | 254   | 85                   |  | 215                  |                | 53             |
| 150           |  | 381   | 127                  |  | 323                  |                | 79             |

## Screen Size and Projection Distance

Refer to the following table to determine the screen size and projection distance.



Standard Lens (Aspect 16:9)

| Image (1080p) |       |      |        |                 | Distance from Screen |      |                      | Default Height | Movable V Position from Default Position |      |    |      | Movable H Position from Default Position |      |          |    |          |    |          |
|---------------|-------|------|--------|-----------------|----------------------|------|----------------------|----------------|------------------------------------------|------|----|------|------------------------------------------|------|----------|----|----------|----|----------|
| Diagonal Size | Width |      | Height | Shortest (Wide) | Longest (Tall)       |      | Projected Image (HO) | H1             | H2                                       | H1   | H2 | W1   | W1                                       | W1   | W1       |    |          |    |          |
| inch          | cm    | inch | cm     | inch            | m                    | inch | m                    | inch           | cm                                       | inch | cm | inch | cm                                       | inch | cm       |    |          |    |          |
| 40            | 102   | 35   | 89     | 20              | 50                   | 56   | 1.4                  | 78             | 2.0                                      | 1    | 3  | 11   | ← 0 → 4                                  | 27   | ← 0 → 10 | 3  | ← 0 → 3  | 9  | ← 0 → 9  |
| 60            | 152   | 52   | 133    | 29              | 75                   | 86   | 2.2                  | 118            | 3.0                                      | 2    | 4  | 16   | ← 0 → 6                                  | 40   | ← 0 → 15 | 5  | ← 0 → 5  | 13 | ← 0 → 13 |
| 80            | 203   | 70   | 177    | 39              | 100                  | 115  | 2.9                  | 158            | 4.0                                      | 2    | 6  | 21   | ← 0 → 8                                  | 54   | ← 0 → 20 | 7  | ← 0 → 7  | 17 | ← 0 → 17 |
| 100           | 254   | 87   | 221    | 49              | 125                  | 145  | 3.7                  | 198            | 5.0                                      | 3    | 7  | 27   | ← 0 → 10                                 | 67   | ← 0 → 26 | 8  | ← 0 → 8  | 21 | ← 0 → 21 |
| 150           | 381   | 131  | 332    | 74              | 187                  | 219  | 5.6                  | 299            | 7.6                                      | 4    | 11 | 40   | ← 0 → 15                                 | 101  | ← 0 → 38 | 13 | ← 0 → 13 | 32 | ← 0 → 32 |
| 200           | 508   | 174  | 443    | 98              | 249                  | 293  | 7.4                  | 399            | 10.1                                     | 6    | 14 | 53   | ← 0 → 20                                 | 135  | ← 0 → 51 | 17 | ← 0 → 17 | 43 | ← 0 → 43 |
| 250           | 635   | 218  | 553    | 123             | 311                  | 366  | 9.3                  | -              | -                                        | 7    | 18 | 66   | ← 0 → 25                                 | 168  | ← 0 → 64 | 21 | ← 0 → 21 | 53 | ← 0 → 53 |

OL-XD2000SZ (Aspect 16:9)

| Image (1080p) |       |     |        | Distance from Screen |      |                |      | Default Height       | Movable V Position from Default Position |      |    |      | Movable H Position from Default Position |      |          |      |          |    |          |
|---------------|-------|-----|--------|----------------------|------|----------------|------|----------------------|------------------------------------------|------|----|------|------------------------------------------|------|----------|------|----------|----|----------|
| Diagonal Size | Width |     | Height | Shortest (Wide)      |      | Longest (Tele) |      | Projected Image (HO) | H1                                       | H2   | H1 | H2   | W1                                       | W1   | W1       | W1   |          |    |          |
|               | inch  | cm  | inch   | cm                   | inch | cm             | inch |                      | cm                                       | inch | cm | inch | cm                                       | inch | cm       | inch | cm       |    |          |
| 40            | 102   | 35  | 89     | 20                   | 50   | 43             | 1.1  | 60                   | 1.5                                      | 1    | 3  | 11   | ← 0 → 4                                  | 27   | ← 0 → 10 | 3    | ← 0 → 3  | 9  | ← 0 → 9  |
| 60            | 152   | 52  | 133    | 29                   | 75   | 67             | 1.7  | 92                   | 2.3                                      | 2    | 4  | 16   | ← 0 → 6                                  | 40   | ← 0 → 15 | 5    | ← 0 → 5  | 13 | ← 0 → 13 |
| 80            | 203   | 70  | 177    | 39                   | 100  | 90             | 2.3  | 124                  | 3.2                                      | 2    | 6  | 21   | ← 0 → 8                                  | 54   | ← 0 → 20 | 7    | ← 0 → 7  | 17 | ← 0 → 17 |
| 100           | 254   | 87  | 221    | 49                   | 125  | 113            | 2.9  | 156                  | 4.0                                      | 3    | 7  | 27   | ← 0 → 10                                 | 67   | ← 0 → 26 | 8    | ← 0 → 8  | 21 | ← 0 → 21 |
| 150           | 381   | 131 | 332    | 74                   | 187  | 172            | 4.4  | 236                  | 6.0                                      | 4    | 11 | 40   | ← 0 → 15                                 | 101  | ← 0 → 38 | 13   | ← 0 → 13 | 32 | ← 0 → 32 |
| 200           | 508   | 174 | 443    | 93                   | 249  | 230            | 5.9  | 316                  | 8.0                                      | 6    | 14 | 53   | ← 0 → 20                                 | 135  | ← 0 → 51 | 17   | ← 0 → 17 | 43 | ← 0 → 43 |
| 250           | 635   | 218 | 553    | 123                  | 311  | 289            | 7.3  | -                    | 7                                        | 18   | 36 | 66   | ← 0 → 25                                 | 168  | ← 0 → 64 | 21   | ← 0 → 21 | 53 | ← 0 → 53 |