

PJD7383

XGA ULTRA SHORT THROW DLP® PROJECTOR

120HZ AND 3D READY

Short Distance – Big Presentations

The PJD7383 is an advanced ultra short throw DLP® projector which includes BrilliantColor™ technology to produce more vibrant colors, while the high brightness and contrast ratio make this projector shine in virtually any lighting situation. With its ultra short throw lens, it can project an 81-inch image from just 3 feet. The PJD7383 delivers 3000 lumens, 3000:1 dynamic contrast ratio with a 1024 x 768 XGA native resolution, and has a wide range of input options including dual RGB ports, Ethernet RJ45, USB and WiFi (with optional adapter). The PJD7383 can be displayed and managed over the network through its advanced management software. The ViewSonic PJD7383 is the ideal projector for both businesses and schools.



VERSATILE PRESENTATIONS ANYWHERE

- > **Short throw lens for large, stunning images in small places**
The short throw lens enables large images to be projected from short distances in small rooms. A screen size of 81-inch is possible from just 39 inches.
- > **BrilliantColor™ technology**
BrilliantColor technology delivers stunning all-digital clarity with life-like color, sharp graphics and outstanding video. The 6-segment color wheel enhances the yellow color performance that is key to accurate and vivid color reproduction.
- > **PC-Less Slide Show Presentation**
Project your pictures or images directly from a USB flash drive without a PC.
- > **Network Display**
With its advanced management software, you can project up to 4 PCs at the same time with the ability to broadcast up to 8 projectors.
- > **USB Display**
Project your presentations through any USB connection without the hassle of running a bulky VGA cable.
- > **Wireless Capability**
Allow the projector to be WiFi enabled with an optional USB wireless adapter (WPD-100)
- > **Network control through RJ45**
Schedule, manage and monitor the projector remotely and receive e-mail alerts of projector lamp status. Use the unique integrated clock to perform commands even when the host PC is powered down.
- > **Eco-mode extendlamp life**
Extend the life of your lamp up to 6,000 hours and reduce noise output.
- > **Supports Crestron RoomView® Express**
Manage up to 250 network projectors in real time monitoring and control. Manage assets, schedule events and program email alerts with this amazing software.



CRESTRON
RoomView
express



VIEWSONIC
PRODUCTS, PROGRAMS,
AND SERVICES

ViewSonic®
See the difference® 

PJD7383

XGA ULTRA SHORT THROW DLP® PROJECTOR – 120HZ AND 3D-READY



DISPLAY		
Type	0.55" Digital Micromirror Device (DLP™)	
Resolution	XGA 1024x768 (Native)	
Lens	Fixed Lens / Manual Focus	
Keystone	Vertical digital keystone correction: +/- 40 degrees	
Display Size (Diagonal)	30"–300" / 0.762m–7.62m	
Throw Distance	0.37m–3.7m / 1.2ft–12.1ft	
Throw Ratio	0.61:1	
Lamp	210 watt	
Lamp Life (Normal / Eco-mode)	4000 / 6000 hours*	
Brightness	3000 Lumens	
Contrast Ratio	2000:1 static (typ); 3000:1 (dynamic)	
Aspect Ratio	4:3 (native) and 16:9, Auto	
Color Depth	24 bits, 16.7M color (8+8+8)	
Color Wheel	6-Segment RGBCYW / 7200rpm	
Color Gamut	98% NTSC 1931 CIE	

INPUT SIGNAL		
Computer and Video	NTSC M (3.58 MHz), PAL (B, D, G, H, I, M, N, 60), SECAM (B, D, G, K, K1, L), SD 480i/576i, ED 480p/576p, HD 720p/1080i	

COMPATIBILITY		
PC	VGA to UXGA	
Mac®	Up to UXGA (scaled)	

CONNECTOR		
RGB Input	15-pin mini D-sub (x2)	
RGB Output	15-pin mini D-sub	
Composite Input	RCA jack	
S-video Input	4-pin mini-DIN	
Audio Input	3.5mm mini jack (x1), RCA (L/R)x1	
Audio Output	3.5mm mini jack	
Mic-In	3.5mm mini jack	
12V trigger	2mm/1A	
Control	RS-232 (DB-9)	
LAN	RJ-45	
USB	Type A for PC-less slide show presentation – support JPEG, BMP, TIFF, PNG, GIF from USB flash drive, optional wireless USB adapter. Mini-B for direct presentation from PC (not MAC compatible) mouse control	

AUDIO POWER		
Speaker	10W (x1)	
Voltage	100~240VAC (Auto Switching), 50/60Hz (universal)	
Consumption	296W (typ) / <1W (stand-by mode)	

CONTROLS		
Basic	Power, keystone/arrow keys, left/blank, menu/exit, right/panel key lock, auto, mode/enter, source	
OSD	Display: Screen color, Aspect ratio, Keystone, Position, Phase, H. Size, Zoom, 3D sync, 3D sync invert, Color Management Picture: Color Mode, Reference Mode, Brightness, Contrast, Color, Tint, Sharpness, Brilliant Color, Color Temp., Save Settings Source: Quick Auto Search System Setup (Basic): Language, Projector Position, Auto Power Off, Blank Timer, Panel Key lock, Splash Screen, Screen Capture, Message, LAN Control Settings, Standby Settings System Setup (Advanced): High Altitude Mode, DCR, Audio Settings, Menu Settings, Closed Caption, Lamp Settings, Presentation Timer, Security Setting, Reset All Settings Information: Current System Status	

OPERATING CONDITIONS		
Temperature	32°F–104°F (0°C–40°C)	
Humidity	10%–90% (non-condensing)	
Altitude	0–6,000 ft. (1,800m), operational up to 10,000 ft. (3048m)	

NOISE LEVEL		
Normal / Eco-mode	32dB / 27dB	

DIMENSIONS (W x H x D)		
Physical	11.4" x 5.0" x 10.0" / 290mm x 126mm x 254mm	
Packaging	15" x 15.4" x 8.3" / 380mm x 392mm x 210mm	

WEIGHT		
Net	7.7 lb. (3.5 kg)	
Gross	12.1 lb. (5.5 kg)	

REGULATIONS		
CB, UL, cUL, FCC (including ICES-003), CE, UL-Argentina, NOM, TUV-GS, GOST-R, SASO, Ukraine, PSB, C-Tick, Korean-eK, CCC, Hygiene, WEEE, RoHS		

PACKAGE CONTENTS		
ViewSonic projector, power cable, VGA cable, interactive pen, laser remote control with batteries, lens cap, Quick Start Guide, ViewSonic Wizard CD (with User Guide)		

WARRANTY		
3-year limited warranty on parts and labor, 1-year limited warranty on lamp, 1st year Express Exchange® service**		

Optional Accessories

- > Replacement Lamp RLC-057
- > Short throw mount WMK-027
- > Wireless G Presentation Gateway WPG-360
- > USB Wireless Adaptor (802.11b/g/n) WPD-100
- > Extended Express Exchange® PRJ-EE-08-03

Projection Distance		4:3 Aspect Ratio	
M	Feet	M	Inches
0.5	1.6	1.0	39.3
1.0	3.3	2.06	81.1
1.2	3.9	2.44	95.9
1.5	4.9	3.06	120.5
2.5	8.2	5.12	201.6
3.7	12.1	7.56	297.5



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by TUV NORD.

Sales: (888) 881-8781 . SalesInfo@ViewSonic.com . ViewSonic.com

*Running eco-mode exclusively can extend lamp life. **See ViewSonic.com for full Express Exchange details. Specifications and availability are subject to change without notice. Selection, offers and programs may vary by country, see your ViewSonic representative for complete details. Crestron RoomView is a registered trademark of Crestron Electronics, Inc. DLP® and the DLP logo are registered trademarks of Texas Instruments and BrilliantColor™ is a trademark of Texas Instruments. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2010 ViewSonic Corporation. All rights reserved [15342-00B-11/10] PJD7383-1



For more product information, visit us on the web at ViewSonic.com