

	Portable									Short-Throw	Large Venue	
Model	C1355	C1455	C2225	C2227	C2315	C2317	C2455	C2315W	C2317W	S1275	E1655	E1655W
NB: Photos are not scaled to size.												
Display Technology	3LCD	3LCD	3LCD	3LCD	3LCD	3LCD	3LCD	3LCD	3LCD	3LCD	3LCD	3LCD
Brightness (ANSI)	3,100 Lumens	3,600 Lumens	2,600 Lumens	2,600 Lumens	3,100 Lumens	3,100 Lumens	4,000 Lumens	3,100 Lumens	3,100 Lumens	2,600 Lumens	6,500 Lumens	6,000 Lumens
Native Resolution	XGA (1024x768)	XGA (1024x768)	XGA (1024x768)	XGA (1024x768)	XGA (1024x768)	XGA (1024x768)	XGA (1024x768)	WXGA (1280x800)	WXGA (1280x800)	XGA (1024x768)	XGA (1024x768)	WXGA (1280x800)
Max Computer Input	UXGA	UXGA	UXGA	UXGA	UXGA	UXGA	UXGA	UXGA	UXGA	UXGA	UXGA	UXGA
Max Video Input	1080i	1080i	1080i	1080p	1080i	1080p	1080p	1080p	1080p	1080i	1080p	1080p
Contrast Ratio	600:1	600:1	600:1	2500:1	600:1	2500:1	2500:1	600:1	2500:1	600:1	1000:1	1000:1
Panel Size	0.63"	0.63"	0.63"	0.63"	0.63"	0.63"	0.63"	0.59"	0.59"	0.63"	0.79"	0.75"
Lens Type	1.2X, 1/4~16 Digital Focus	1.2X, 1/4~16 Digital Focus	1.2X, 1/4~16 Digital Focus	1.2X, 1/4~16 Digital Focus	1.2X, 1/4~16 Digital Focus	1.2X, 1/4~16 Digital Focus	1.2X, 1/4~16 Digital Focus	1.2X, 1/4~16 Digital Focus	1.2X, 1/4~16 Digital Focus	Fixed Zoom & Lens	1:1.6X, F=1.7~2.2, f=22~35mm, 1/2x1/2~4x4 Digital Focus	
Power Lens Shift	No	No	No	No	No	No	No	No	No	No	H. 10%; V. 50%	H. 10%; V. 50%
Throw Ratio	70"@2.07M	70"@2.07M	70"@2.07M	70"@2.07M	70"@2.07M	70"@2.07M	70"@2.07M	70"@2.07M	70"@2.07M	80"@1M (0.61:1)	60"@1.58M	57"@1.58M
Throw Distance	1.4M~12.7M	1.4M~12.7M	1.4M~12.7M	1.4M~12.7M	1.4M~12.7M	1.4M~12.7M	1.4M~12.7M	1.4M~12.7M	1.4M~12.7M	0.5M~2.56M	0.8M~17.3M	0.8M~17.3M
Native Aspect Ratio	4:3 (Native) 16:9 (Compatible)	4:3 (Native) 16:9 (Compatible)	4:3 (Native) 16:9 (Compatible)	4:3 (Native) 16:9 (Compatible)	4:3 (Native) 16:9 (Compatible)	4:3 (Native) 16:9 (Compatible)	4:3 (Native) 16:9 (Compatible)	4:3 (Native) 16:9 (Compatible)	16:10 (Native) 4:3 (Compatible)	4:3 (Native) 16:9 (Compatible)	4:3 (Native) 16:9 (Compatible)	16:10 (Native) 4:3 (Compatible)
Keystone Correction	Auto, ±30°	Auto, ±30°	Auto, ±30°	Auto, ±30°	Auto, ±30°	Auto, ±30°	Auto, ±30°	Auto, ±30°	Auto, ±30°	Digital, ±30°	Auto, ±30°	Auto, ±30°
Closed Caption	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Inputs	S-Video, Video, VGAx2, Mini-Jack, RCA(L/R), RS232, LAN	S-Video, Video, VGAx2, Mini-Jack, RCA(L/R), RS232, LAN	VGA, Audio, Component, Video, S-Video, RS232	HDMI, LAN, VGA, Audio, Component, Video, S-Video, RS232	VGA, Audio, Component, Video, S-Video, RS232	HDMI, LAN, VGA, Audio, Component, Video, S-Video, RS232	HDMI, LAN, VGA, Audio, Component, Video, S-Video, RS232	HDMI, VGA, Audio, Component, Video, S-Video, RS232	HDMI, LAN, VGA, Audio, Component, Video, S-Video, RS232	S-Video, Component, 2xVGA, Mini Jack, Video, RCA (L/R), LAN, RS232	HDMI, VGA, BNCx5, S-Video, Component, Video	HDMI, VGA, BNCx5, S-Video, Component, Video
Outputs	VGA, Mini-Jack	VGA, Mini-Jack	VGA, Mini Jack	VGA, Mini Jack	VGA, Mini Jack	VGA, Mini Jack	VGA, Mini Jack	VGA, Mini Jack	VGA, Mini Jack	VGA, Mini Jack	VGA, Mini Jack	VGA, Mini Jack
Speaker	Mono 7W	Mono 7W	Stereo 2x3W	Stereo 2x3W	Stereo 2x3W	Stereo 2x3W	Stereo 2x3W	Stereo 2x3W	Stereo 2x3W	Mono 7W	Mono 7W	Mono 7W
Network Control	Wired LAN Monitor & Control		Wired LAN Monitor & Control		Wired LAN Monitor & Control		Wired LAN Monitor & Control	Wired LAN Monitor & Control		Wired LAN Monitor & Control	Wired LAN Monitor & Control	
Lamp	230W	230W	230W	230W	230W	230W	230W	230W	230W	230W	330W	330W
Lamp Life (Nor/Eco)	3,000H/4,000H	3,000H/4,000H	3,000H/4,000H	3,000H/4,000H	3,000H/4,000H	3,000H/4,000H	3,000H/4,000H	3,000H/4,000H	3,000H/4,000H	3,000H/4,000H	3,000H/4,000H	3,000H/4,000H
Standby Power	5W	5W	Below 1W	Below 1W	Below 1W	Below 1W	Below 1W	Below 1W	Below 1W	Below 1W	Below 1W	Below 1W
Power Consumption	280W	280W	280W	280W	280W	280W	280W	280W	280W	280W	490W	490W
Operating Temp.	5°C~35°C	5°C~35°C	5°C~35°C	5°C~35°C	5°C~35°C	5°C~35°C	5°C~35°C	5°C~35°C	5°C~35°C	5°C~35°C	5°C~40°C	5°C~40°C
Storage Temp.	-10°C~60°C	-10°C~60°C	-10°C~60°C	-10°C~60°C	-10°C~60°C	-10°C~60°C	-10°C~60°C	-10°C~60°C	-10°C~60°C	-10°C~60°C	-10°C~60°C	-10°C~60°C
Key Features	Customised startup logo; Auto ceiling; Colorboards; Blankscreen Hotkey; Close Captioning; Anti-theft Bar; Auto source; Easy Maintenance	Customised startup logo; Auto ceiling; Colorboards; Blankscreen Hotkey; Close Captioning; Anti-theft Bar; Auto source; Easy Maintenance	Customised startup logo; Auto ceiling; Colorboards; Blankscreen Hotkey; Close Captioning; Anti-theft Bar; Auto source; Easy Maintenance	HDMI Input; Customised startup logo; Auto ceiling; Colorboards; Blankscreen Hotkey; Close Captioning; Anti-theft Bar; Auto source; Easy Maintenance	Customised startup logo; Auto ceiling; Colorboards; Blankscreen Hotkey; Close Captioning; Anti-theft Bar; Auto source; Easy Maintenance	HDMI Input; Customised startup logo; Auto ceiling; Colorboards; Blankscreen Hotkey; Close Captioning; Anti-theft Bar; Auto source; Easy Maintenance	HDMI Input; Customised startup logo; Auto ceiling; Colorboards; Blankscreen Hotkey; Close Captioning; Anti-theft Bar; Auto source; Easy Maintenance	Customised startup logo; Auto ceiling; Colorboards; Blankscreen Hotkey; Close Captioning; Anti-theft Bar; Auto source; Easy Maintenance	HDMI Input; Customised startup logo; Auto ceiling; Colorboards; Blankscreen Hotkey; Close Captioning; Anti-theft Bar; Auto source; Easy Maintenance	Customised startup logo; Auto ceiling; Colorboards; Blankscreen Hotkey; Close Captioning; Anti-theft Bar; Easy Maintenance	Lens Shift; Easy Lamp & Lens Replacement; Customised startup logo; Auto ceiling; Colorboards; Blankscreen Hotkey; Close Captioning; Anti-theft Bar; Auto source; Easy Maintenance	
Projection Size	40"~300"	40"~300"	40"~300"	40"~300"	40"~300"	40"~300"	40"~300"	40"~300"	40"~300"	40"~200"	40"~300"	40"~300"
Weight	7.7LB	7.7LB	6.4LB	6.4LB	6.4LB	6.4LB	6.4LB	6.4LB	6.4LB	8.37LB	< 22.0LB (Without Lens)	
Note:	C1355, C1455, S1275 are currently not available in US & Canada.											

## ASK Proxima Co., Ltd

◆ Far East Consortium Building, 121 Des Voeux Road, Central, HK. ◆ Website: [www.askproxima.com](http://www.askproxima.com)

Specifications are subject to change without notice. ASKProxima is a registered trademark of ASK Proxima Co., Ltd. in US and other countries. © 2011 ASK Proxima Co., Ltd. Issued April 10, 2011