

DW10

Specifications:

Model	DW10
Resolution	SVGA (800 x 600)
Display Technology	DMD 0.55"
Brightness	2600 lm
Contrast Ratio	2600:1
Uniformity	85%
Lamp	230W OSRAM
Projector life	4000H(eco),3000H(normal)
Dimension	319 . 9mmX308.97mmX138.36mm
Weight	3.6kg
DB Rating	<35dB[Nomal]
Projection Method	front/rear, desktop/ceiling
Cabinet Color	white
Input	2-VGA / S-VIDEO / Video/ USB / RS232
Output	VGA
Computer Compatibility	VGA SVGA XGA SXGA
Video Compatibility	NTSC:M 4.43; PAL: B, G, H, I, M, N; SECAM:M,720p, 576p, 576i,480p, 480i ,1080i
Aspect Ratio	4 : 3(standard)/16 : 9 (compatible)
Digital Keystone Correction	vertical +/-15°auto keystone
Throw Ratio	0.61 @ 77" (0.95m)
Projection Distance	0.4-5m
Image Size	40"-250"
H Scanning Frequency	15-110KHz
V Scanning	50-80Hz

Frequency	
Power Consumption	280W
Power Supply	100-240V AC
speaker	3W
Operating Temperature	5-35°C
Storage Temperature	-20°C~+60°C
OSD Language	5Languages
Accessories (Standard)	User Manual , ACPower Supply Cord , Remote Control 和 Batteries , VGA CABLE , Lens Cap , PIN CODE
Model	DW15
Resolution	SVGA (800 x 600)
Display Technology	DMD 0.55”
Brightness	3100 lm
Contrast Ratio	2600:1
Uniformity	85%
Lamp	230W OSRAM
Projector life	4000H(eco),3000H(normal)
Dimension	319 . 9mmX308.97mmX138.36mm
Weight	3.6kg
DB Rating	<35dB[Nomal]
Projection Method	front/rear, desktop/ceiling
Cabinet Color	white
Input	2*VGA / S-VIDEO / AV/ USB PORT / RS232 / Audio
Output	VGA
Computer Compatibility	VGA SVGA XGA SXGA
Video Compatibility	NTSC:M 4.43; PAL: B, G, H, I, M, N; SECAM:M,720p, 576p, 576i,480p, 480i ,1080i

Aspect Ratio	4 : 3(standard)/16 : 9 (compatible)
Digital Keystone Correction	vertical +/-15°auto keystone
Throw Ratio	0.95m @ 77"
Projection Distance	0.4-5m
Image Size	40"-250"
H Scanning Frequency	15-110KHz
V Scanning Frequency	50-80Hz
Power Consumption	330W
Power Supply	100-240V AC
speaker	3W
Operating Temperature	5-35°C
Storage Temperature	-20°C~+60°C
OSD Language	5Languages
Accessories (Standard)	User Manual , ACPower Supply Cord , Remote Control , Batteries , VGA CABLE , Lens Cap , PIN CODE

DW15

Model	DW15
Resolution	SVGA (800 x 600)
Display Technology	DMD 0.55"
Brightness	3100 lm
Contrast Ratio	2600:1
Uniformity	85%
Lamp	230W OSRAM
Projector life	4000H(eco),3000H(normal)

Dimension	319 . 9mmX308.97mmX138.36mm
Weight	3.6kg
DB Rating	<35dB[Nomal]
Projection Method	front/rear, desktop/ceiling
Cabinet Color	white
Input	2*VGA / S-VIDEO / AV/ USB PORT / RS232 / Audio
Output	VGA
Computer Compatibility	VGA SVGA XGA SXGA
Video Compatibility	NTSC:M 4.43; PAL: B, G, H, I, M, N; SECAM:M,720p, 576p, 576i,480p, 480i ,1080i
Aspect Ratio	4 : 3(standard)/16 : 9 (compatible)
Digital Keystone Correction	vertical +/-15°auto keystone
Throw Ratio	0.95m @ 77"
Projection Distance	0.4-5m
Image Size	40"-250"
H Scanning Frequency	15-110KHz
V Scanning Frequency	50-80Hz
Power Consumption	330W
Power Supply	100-240V AC
speaker	3W
Operating Temperature	5-35°C
Storage Temperature	-20°C~+60°C
OSD Language	5Languages
Accessories	User Manual , ACPower Supply Cord , Remote Control , Batteries , VGA CABLE , Lens Cap , PIN CODE

(Standard)

Accessories :

User Manual /Strap for Lens cap/Power Supply Cord/Remote Control/Batteries/VGA
CABLE/Warranty Card/Certificate of Inspection/Drying AgentLens Cap/Lens Cap