

## Bright and Lightweight, HD, and Wireless Capability

The Qumi Q5, the next generation of Vivitek's series of HD LED pocket projectors, has a brightness level up to 500 lumens and weighs only 1.1 pounds. The Qumi Q5 features a DLP<sup>®</sup> Pico chipset and BrilliantColor™ technologies from Texas Instruments and wireless capability. The Qumi's sleek design and connectivity options allows it to be used with a variety of other portable devices, including, but not limited to smart phones, laptops, netbooks and tablets, digital and video cameras. Versatile and portable, the Vivitek Qumi Q5 is perfect for sharing digital content at work and play.

## Features

- Native WXGA native resolution, HD 720p compatible resolution
- Up to 500 lumens of brightness and 10,000:1 contrast
- Estimated 30,000 hours of operation
- 4GB built-in memory and USB port for memory expansion to display content without a PC
- 3D-Ready via DLP Link
- Connectivity options include: HDMI, Universal I/O for VGA, AV mini-jack, mini-jack audio-out
- Only 1.1 pounds and available in blue, red, yellow, black or white finish



| Specifications             |                                                                                                                                                                     |
|----------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Brightness                 | Up to 500 Lumens                                                                                                                                                    |
| Native Resolution          | WXGA (1280 x 800)                                                                                                                                                   |
| Max. Resolution            | UXGA (1600 x 1200)                                                                                                                                                  |
| Contrast Ratio             | 10,000:1 (Full On/Full Off)                                                                                                                                         |
| Light Source Life and Type | ≈30,000 Hours, LED                                                                                                                                                  |
| Display Type               | HD Pico DLP Technology by Texas Instruments                                                                                                                         |
| Throw Ratio (±3%)          | 1.55:1 (Distance/Width)                                                                                                                                             |
| Image Size (Diagonal)      | 30" to 90" (0.8 to 2.3 m)                                                                                                                                           |
| Projection Distance        | 3.3' to 9.9' (1.0 to 3.0 m)                                                                                                                                         |
| Zoom Ratio                 | Fixed Lens, Manual Focus                                                                                                                                            |
| Aspect Ratio               | 16:10 Native, 4:3 & 16:9 Compatible                                                                                                                                 |
| Offset                     | 102.5%                                                                                                                                                              |
| Keystone Correction        | ± 40° Vertical                                                                                                                                                      |
| Color Spectrum             | 1.07 Billion                                                                                                                                                        |
| Horizontal Scan Rate       | 15, 30 to 90 KHz                                                                                                                                                    |
| Vertical Scan Rate         | 43 to 85 Hz                                                                                                                                                         |
| Speaker                    | 2W Mono                                                                                                                                                             |
| Projection Method          | Table Top, Tripod (¼ - 20) or Ceiling (Front or Rear)                                                                                                               |
| Uniformity                 | 85%                                                                                                                                                                 |
| File Compatibility         | Office Viewer (Doc, XLS, PPT, PDF, TXT)<br>Video (MPEG-4, H.264, Divx™, WMV)<br>Image (JPEG, PNG, BMP, GIF)<br>Audio (MP3, WAV)                                     |
| Computer Compatibility     | UXGA, WXGA, SXGA+, SXGA, XGA, SVGA, VGA Resized;<br>VESA Standards; PC and Macintosh Compatible                                                                     |
| Video Compatibility        | SDTV (480i), EDTV (480p), HDTV (720p, 1080i/p),<br>NTSC/NTSC 4.43, PAL B/G/H/I/M/N 60, SECAM                                                                        |
| I/O Connection Ports       | HDMI, Universal I/O (24-Pin Connector for<br>VGA/Component Input), AV Mini-Jack, Mini-Jack Audio-Out, USB (Type A)                                                  |
| Weight                     | 17.3 oz (1.1 lbs)                                                                                                                                                   |
| Dimensions (W x H x D)     | 6.3" x 1.3" x 4.0" (162 x 32 x 102 mm)                                                                                                                              |
| Noise Level                | 28dB/32dB (Standard / Boost Mode)                                                                                                                                   |
| Power                      | Supply: AC 100-240V, 50/60Hz<br>Consumption: 65W (Boost Mode), <0.5W (Standby)                                                                                      |
| Operating Temperature      | 41 to 104°F (5 to 40°C)                                                                                                                                             |
| Warranty                   | 2-Year Limited Parts and Labor                                                                                                                                      |
| Standard Accessories       | Power Adapter, Universal I/O to VGA Cable, HDMI Cable,<br>3.5mm AV-in Cable, Carrying Pouch, Remote Control,<br>User Manual (CD) Quick Start Guide, Warranty Card   |
| Optional Accessories       | Battery Dock, Wi-Fi USB Dongle                                                                                                                                      |
| UPC                        | 8 14964 33659 0 (White/Q5-WH),<br>8 14964 33661 3 (Black/Q5-BK),<br>8 14964 33663 7 (Red/Q5-RD),<br>8 14964 33665 1 (Blue/Q5-BL),<br>8 14964 33667 5 (Yellow/Q5-YW) |

