


C520

5000:1 / 5500 Lumens



C510W

5000:1 / 5000 Lumens



C5 Series

Super Bright, Highly Capable, Feature-Rich



5000:1 Contrast Ratio

With a 5000:1 contrast ratio, you're ensured of rich picture layering details and clear, crisp images for even the most demanding viewers.



High Brightness for Large Images

Super bright at 5000 and 5500 Lumens, the C5 Series is a great projector solution for meeting rooms, conference rooms and other small to large type environments.



Vertical and Horizontal Keystone Correction/Corner Keystone

Horizontal and vertical digital keystone correction fixes image distortion created when a projector's lens is not perpendicular to the screen. Corner keystone correction allows the adjustment of all four angles of the image. These are ideal tools for when the projection environment is less than ideal.



Hybrid-Filter & Powerful Cooling System

Each projector is furnished with a low-maintenance, replaceable dust filter that effectively reduces smoke and dust from entering the projector. The cooling system is optimized for powerful heat dispersion, even at high altitudes.



Simple, Quick Operational Set Up

Automatic or Manual Keystone correction makes sure that the projected image is ideal, despite projector placement. Automatic image reversal can be done without a menu setting when installed from the ceiling.



1.65x Standard Digital Zoom Lens

Compared to standard 1.2x lenses, the C5 projectors feature a 1.65x zoom lens that meets various installation requirements.



Edge-Blending

The edge-blending feature provides a seamless wide-screen presentation with multiple side-by-side projectors. Images can be perfectly matched for brightness and color correction.



Network Control

With a wired connection via RJ45, control or monitor all projectors through corresponding IP. Turn the projectors on/off, check configurations, view lamp times and operational status through the network.

Specifications

Model	C520	C510W
Display Technology	Liquid Crystal Display	
Display Panel	3 x 0.63"	3 x 0.59"
Brightness	5500 ANSI Lumens	5000 ANSI Lumens
Native Resolution	XGA (1024 x 768)	WXGA (1280 x 800)
Contrast Ratio	5000:1	5000:1
Throw Ratio	Min Zoom: 2.47 - Max Zoom: 1.48	
Projector Lens	1.65x, F = 1.6 - 2.08, f = 19.36 - 31.94mm	
Uniformity	80%	
Distance / Screen Size (Diagonal)	35.4" - 598.4"	37.8" - 628.4"
Aspect Ratio	4:3 (Standard), 16:9 (Compatible)	16:10 (Standard), 4:3 (Compatible)
Keystone	V: ±30° (Auto) H: ±15° (Manual) Corner Keystone	
Input	HDMI, 2-VGA, YCbCr, S-video, Video, 2-USB Audio: 3.5 Mini-Jack, RJ45	HDMI, 2-VGA, YCbCr, S-video, Video, 2-USB Audio: 3.5 Mini-Jack, RJ45
Output(s)	VGA, Audio Out, 12V Trigger	
Control	RS232, RJ45	
PC Compatibility	VGA, SVGA, XGA, SXGA, WXGA, UXGA, Mac	
Video Compatibility	PAL, SECAM, NTSC 4.43, PAL-M, PAL-N, 480i, 480p, 576i, 576p, 720p and 1080i	
Lens Shift H.	±10% (Powered)	
Lens Shift V.	±40% (Powered)	
Lamp	280 Watts	
Lamp Life	(STD Mode) 4000hours, (ECO Mode) 6000hours	
Lamp Replacement	Top Lamp Replacement	
Remote Control	Yes	
H. Synch Freq.	15 - 100KHz	
V. Synch Freq.	48 - 85Hz	
Standby Power	< 0.3 Watts	
Power Supply	100V - 240V @ 50 - 60Hz	
Operating Temp.	32°F - 104°F	
Storage Temp.	68°F - 140°F	
OSD Languages	23 languages including English, German, French, Italian, Spanish, Polish, Swedish, Dutch, Portuguese, Japanese, Traditional Chinese, Korean, Russian, Arabic, Turkish, Finnish, Norwegian, Danish, Indonesian, Czech, Vietnamese, Thai, Farsi	
Speaker	10 Watts	
Dimensions	15.2" x 12.1" x 4.3"	
Weight	10.7Lbs	
Standard Accessories	User Manual (CD), Power Cord, Remote Control, VGA Cable, Warranty Card	
Other Features	1. 360° Lens Shift 2. One Touch Lens Replacement 3. Quick Power off 4. Customized Startup Logo	5. Auto Image Reverse 6. Build in Test Images 7. One Touch Blank Screen 8. Closed Caption 9. Image Zoom in/out 10. Image Freezing, Zoom and Panning 11. Top Cover Lamp Replacement 12. Anti-theft Bar & Lock



Note: I/O Ports shown here are specifically for C500

Make an impact with powerful impressions and effective solutions.

For more information, call (855) 899-6825, email info@askproximausa.com or visit www.askproximausa.com

© ASK Proxima 2014. All rights reserved. ASK Proxima logo is registered trademarks of ASK Proxima Inc. All specifications are subject to change without notice.