



S430
8000:1 / 3600 Lumens



S430W
8000:1 / 3300 Lumens



S4 Series Short Throw, Big Picture



Short-Throw Lens

The short-throw lens can project an image up to 80" (diagonal) from a distance as little as 29", allowing the viewer to see what's on the screen without a shadow.



Vertical and Horizontal Keystone Correction/Corner Keystone

Horizontal and vertical digital keystone correction fixes image distortion created when a projector's lens is not perpendicular to the screen. Corner keystone correction allows the adjustment of all four angles of the image. These are ideal tools for when the projection environment is less than ideal.



8000:1 Contrast Ratio

The high 8000:1 contrast ratio ensures rich picture layering details and provides clear, crisp images for demanding viewers.



10000 hrs

10,000 Hours of Lamp Life

The latest frequency conversion driving technology, the S4 series delivers up to 10,000 hours (in super eco mode) of lamp life up to, reducing the cost of ownership.



Digital Zoom Function

Full screen digital zoom with focus and partial image zoom via remote control.



Simple, Quick Operational Set Up

Automatic or Manual Keystone correction makes sure that the projected image is ideal, despite projector placement. Automatic image reversal can be done without a menu setting when installed from the ceiling.



Edge-Blending

A feature generally found on larger, high-end projectors, but standard in the S4 Series. Edge-blending allows the combination of multiple projectors without the use of an external source to create a large, seamless image.



Hybrid-Filter & Powerful Cooling System

The S4 projectors are furnished with a low-maintenance, replaceable dust filter that effectively reduces smoke and dust from entering the projector. The cooling system is optimized for powerful heat dispersion, even at high altitudes.

Specifications

Model	S430	S430W
Display Technology	Liquid Crystal Display	
Display Panel	3 x 0.63"	3 x 0.59"
Brightness	3600 ANSI Lumens	3300 ANSI Lumens
Native Resolution	XGA (1024 x 768)	WXGA (1280 x 800)
Contrast Ratio	8000:1	
Throw Ratio	0.46 Fixed Lens	
Projector Lens	F = 1.8, f = 6.08mm	
Uniformity	80%	
Distance / Screen Size (Diagonal)	17.9" - 37.1"	19.1" - 39.5"
Aspect Ratio	4:3 (Standard), 16:9 (Compatible)	16:10 (Standard), 4:3 (Compatible)
Keystone	V: ±15° (Auto) H: ±15° (Manual) Corner Keystone	
Input	HDMI, 2-VGA, YCbCr, S-video, Video, 2-USB, 2-Audio In (L/R) Audio: 3.5 Mini-Jack, RJ45	
Output(s)	2-VGA, Audio: 3.5 Mini-Jack	
Control	RS232, RJ45, USB	
PC Compatibility	VGA, SVGA, XGA, SXGA, WXGA, UXGA, Mac	
Video Compatibility	PAL, SECAM, NTSC 4.43, PAL-M, PAL-N, 480i, 480p, 576i, 576p, 720p, 1035i and 1080i	
Lamp	235 Watts	
Lamp Life	(SUPER Mode) 3000hours, (ECO Mode) 10000hours	
Lamp Replacement	Top Lamp Replacement	
Remote Control	Yes	
H. Synch Freq.	15 - 100KHz	
V. Synch Freq.	48 - 85Hz	
Standby Power	< 0.5 Watts	
Power Supply	100V - 240V @ 50 - 60Hz	
Operating Temp.	41°F - 104°F	
Storage Temp.	50°F - 140°F	
OSD Languages	23 languages including English, German, French, Italian, Spanish, Polish, Swedish, Dutch, Portuguese, Japanese, Traditional Chinese, Korean, Russian, Arabic, Turkish, Finnish, Norwegian, Danish, Indonesian, Czech, Vietnamese, Thai, Farsi	
Speaker	10 Watts	
Dimensions	13.2" x 13" x 3.4"	
Weight	8.4Lbs	
Standard Accessories	User Manual (CD), Power Cord, Remote Control, VGA Cable, Quick Start Guide, Battery, Warranty Card	
Other Features	1. Quick Power off 2. Customized Startup Logo 3. Auto Image Reverse 4. Build in Test Images	5. One Touch Blank Screen 6. Closed Caption 7. Image Zoom in/out 8. Image Freezing, Zoom and Panning 9. Top Cover Lamp Replacement 10. Anti-theft Bar & Lock



Note: I/O Ports shown here are specifically for S430W

Make an impact with powerful impressions and effective solutions.

For more information, call (855) 899-6825, email info@askproximausa.com or visit www.askproximausa.com

© ASK Proxima 2014. All rights reserved. ASK Proxima logo is registered trademarks of ASK Proxima Inc. All specifications are subject to change without notice.